



Message Implementation Guideline

DSV_InvoiceMessage

Model: DSV XML INVOICE OUT
Version: v2.0
Issue date: 2026-08-24
Author: DSV A/S, EDI

3 Structure.....	2
4 Guideline	15

Structure

Occurrence	Element/Attribute
	DSV_InvoiceMessage
1 .. 1	xs:sequence
1 .. 1	Header
1 .. 1	xs:sequence
1 .. 1	MessageId
1 .. 1	SenderId
1 .. 1	ReceiverId
1 .. 1	DocumentDate
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
1 .. 1	DocumentCode
1 .. 1	Function
1 .. 1	Version
1 .. 1	Invoice
1 .. 1	xs:sequence
1 .. 1	InvoiceId
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	CustomFieldType
0 .. 1	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1	PartyDetails
required	Role
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. unbounded	Contact
required	Type
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
0 .. unbounded	FinancialInstitution
required	Role
1 .. 1	xs:sequence
0 .. 1	AccountHolderId
0 .. 1	AccountHolderName

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	InstitutionNameCode
0 .. 1	ResponsibleAgencyCode
0 .. 1	InstitutionBranchId
0 .. 1	InstitutionName
0 .. 1	InstitutionBranchLocationName
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	Documents
1 .. 1	xs:sequence
0 .. unbounded	Document
1 .. 1	xs:sequence
0 .. 1	DocumentCode
0 .. 1	Currencies
1 .. 1	xs:sequence
0 .. unbounded	CurrencyDetails
1 .. 1	xs:sequence
0 .. 1	Currency
1 .. 1	xs:sequence
0 .. 1	CurrencyUsage
0 .. 1	CurrencyIdentification
0 .. 1	CurrencyCode
0 .. 1	CurrencyRate
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	PaymentTerms
1 .. 1	xs:sequence
0 .. unbounded	PaymentTermsDetails
1 .. 1	xs:sequence
1 .. 1	PaymentTerms
required	Type
1 .. 1	xs:sequence
0 .. 1	PaymentTermsDescription
0 .. 1	PeriodType
0 .. 1	PeriodCount
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	DateTime
0 .. 1	TransportStages
1 .. 1	xs:sequence
0 .. unbounded	TransportStage
1 .. 1	xs:sequence
0 .. 1	Stage
required	Type
1 .. 1	xs:sequence
0 .. 1	ModeOfTransport
0 .. 1	TransportId
0 .. 1	CarrierId
0 .. 1	CarrierName
0 .. 1	TransportType
0 .. 1	TransportMeansName
0 .. 1	TransportMeansNationality
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportServices
1 .. 1	xs:sequence
0 .. unbounded	ServiceGroup
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	PriorityCode
0 .. unbounded	ServiceGroup <ShipmentService>
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	TermsOfDelivery
1 .. 1	xs:sequence
0 .. 1	Terms
1 .. 1	xs:sequence
0 .. 1	TermsCode
0 .. 1	CodeId
0 .. unbounded	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	EquipmentUnits
1 .. 1	xs:sequence
0 .. unbounded	EquipmentUnit
1 .. 1	xs:sequence
0 .. 1	EquipmentType
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	ISOCODE
0 .. 1	PackingMode
0 .. 1	EquipmentSizeDescription
0 .. 1	NumberOfUnits
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded	Measurement
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dimensions
1 .. 1	xs:sequence
0 .. unbounded	Dimension
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Length

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	Width
0 .. 1	Height
0 .. 1	SealIds
1 .. 1	xs:sequence
0 .. unbounded	Seal
1 .. 1	xs:sequence
0 .. 1	SealId
0 .. 1	SealParty
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportMovements
1 .. 1	xs:sequence
0 .. unbounded	TransportMovement
optional	Type
1 .. 1	xs:sequence
0 .. 1	Code
0 .. 1	Description
0 .. 1	TemperatureControl
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Fixed
0 .. 1	HumidityPercentage
0 .. 1	RangeDetails
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Minimum
0 .. 1	Maximum
0 .. 1	InvoiceLines
1 .. 1	xs:sequence
0 .. unbounded	InvoiceLine
1 .. 1	xs:sequence
0 .. 1	LineItem
1 .. 1	xs:sequence
0 .. 1	LineItemNumber
0 .. 1	ItemIdentifier
0 .. 1	ItemDescriptions

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. unbounded optional	ItemDescription
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	Code
0 .. 1	Description
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded required	Measurement
1 .. 1	Type
0 .. 1	Uom
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded required required	Date
1 .. 1	Type
0 .. 1	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	EquipmentUnits
1 .. 1	xs:sequence
0 .. unbounded	EquipmentUnit
1 .. 1	xs:sequence
0 .. 1	EquipmentType
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	ISOCODE
0 .. 1	PackingMode
0 .. 1	EquipmentSizeDescription
0 .. 1	NumberOfUnits
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded required	Measurement
1 .. 1	Type
0 .. 1	Uom
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dimensions
1 .. 1	xs:sequence
0 .. unbounded required	Dimension
1 .. 1	Type
0 .. 1	Uom
1 .. 1	xs:sequence
0 .. 1	Length
0 .. 1	Width
0 .. 1	Height
0 .. 1	SealIds
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. unbounded	Seal
1 .. 1	xs:sequence
0 .. 1	SealId
0 .. 1	SealParty
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportMovements
1 .. 1	xs:sequence
0 .. unbounded	TransportMovement
optional	Type
1 .. 1	xs:sequence
0 .. 1	Code
0 .. 1	Description
0 .. 1	TemperatureControl
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Fixed
0 .. 1	HumidityPercentage
0 .. 1	RangeDetails
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Minimum
0 .. 1	Maximum
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	DescriptionCode
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. unbounded required	MonetaryAmount
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1 required optional	Reference
	Type
	CustomFieldType
0 .. 1 required required	Date
1 .. 1	Type
0 .. 1	Format
	xs:sequence
	DateTime
0 .. 1	Packages
1 .. 1	xs:sequence
0 .. unbounded	PackageGroup
1 .. 1	xs:sequence
0 .. 1	Package
1 .. 1	xs:sequence
1 .. 1	PackageQuantity
0 .. 1	PackageCode
0 .. 1	Packageld
1 .. 1	xs:sequence
1 .. 1	InstructionCode
0 .. 1	Marks
1 .. 1	xs:sequence
1 .. unbounded	ShippingMark
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1 required	Location
1 .. 1	Type
	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded required required	Date
1 .. 1	Type
0 .. 1	Format
	xs:sequence
0 .. 1	DateTime

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1	PartyDetails
required	<i>Role</i>
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	<i>Type</i>
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. unbounded	Contact
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	<i>Type</i>
optional	<i>Identifier</i>
optional	<i>CustomFieldType</i>
0 .. 1	Date
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
	AllowancesorCharges

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	
1 .. 1	xs:sequence
0 .. unbounded	AllowanceOrChargeGroup
1 .. 1	xs:sequence
0 .. 1	AllowanceOrCharge
required	<i>AllowanceOrChargeCode</i>
1 .. 1	xs:sequence
0 .. 1	AllowanceOrChargeIdentifier
0 .. 1	SpecialServiceDescriptionCode
0 .. 1	SpecialServiceDescription
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmountGroup
1 .. 1	xs:sequence
0 .. 1	MonetaryAmount
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Currencies
1 .. 1	xs:sequence
0 .. unbounded	CurrencyDetails
1 .. 1	xs:sequence
0 .. 1	Currency
1 .. 1	xs:sequence
0 .. 1	CurrencyCode
0 .. 1	CurrencyRate
0 .. 1	Taxes
1 .. 1	xs:sequence
0 .. unbounded	TaxDetails
1 .. 1	xs:sequence
0 .. 1	Tax
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	TaxAmount
0 .. 1	TaxRate
0 .. 1	TaxCode
0 .. 1	TaxCategory
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Rate
optional	<i>Type</i>
0 .. 1	TransportStages
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. unbounded	TransportStage
1 .. 1	xs:sequence
0 .. 1	Stage
required	Type
1 .. 1	xs:sequence
0 .. 1	ModeOfTransport
0 .. 1	TransportId
0 .. 1	CarrierId
0 .. 1	CarrierName
0 .. 1	TransportType
0 .. 1	TransportMeansName
0 .. 1	TransportMeansNationality
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	TermsOfDelivery
1 .. 1	xs:sequence
0 .. 1	Terms
1 .. 1	xs:sequence
0 .. 1	TermsCode
0 .. 1	Codeld
0 .. unbounded	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	Type
1 .. 1	xs:sequence
0 .. 1	Amount

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Taxes
1 .. 1	xs:sequence
0 .. unbounded	TaxDetails
1 .. 1	xs:sequence
0 .. 1	Tax
required	Type
1 .. 1	xs:sequence
0 .. 1	TaxAmount
0 .. 1	TaxCode
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	Type
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType

Guideline

Element/Attribute	Annotation
DSV_InvoiceMessage	General Notes Schema guide for the outbound invoice standard XML V2 message
xs:sequence	Occurrence 1 .. 1
Header	Occurrence 1 .. 1 Type Header General Notes Creditnote Examples <Header> <Messageld>12485236</Messageld> <SenderId>SenderIdIdentification</SenderId> <ReceiverId>ReceiverIdIdentification</ReceiverId> <DocumentDate Type="DocumentDate" Format="DateTime"> <DateTime>202608081300</DateTime> </DocumentDate> <DocumentCode>Invoice</DocumentCode> <Function>New</Function> <Version>2.0</Version> </Header>
xs:sequence	Occurrence 1 .. 1
Messageld	Occurrence 1 .. 1 Type xs:string General Notes MESSAGE IDENTIFIER
SenderId	Occurrence 1 .. 1 Type xs:string General Notes SENDER IDENTIFICATION Mutually agreed
ReceiverId	Occurrence 1 .. 1 Type xs:string General Notes RECEIVER IDENTIFICATION Mutually agreed
DocumentDate	Occurrence 1 .. 1 Type Date General Notes DOCUMENT / MESSAGE DATE
Type	Type xs:string Use required General Notes DATE TYPE
Format	Applicable Codes IssueDate Document Issued Date Type xs:string Use required General Notes DATE FORMAT
DateTime	Applicable Codes DateTime CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes MESSAGE / DOCUMENT DATE
DocumentCode	Occurrence 1 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, **Grey** = Group

DSV public

Element/Attribute	Annotation
	General Notes DOCUMENT TYPE
	Applicable Codes
	CreditNote CreditNote
	Invoice Invoice
Function	Occurrence 1 .. 1 Type xs:string General Notes DOCUMENT/MESSAGE FUNCTION
	Applicable Codes
	Delete Delete
	New New
	Update Update
Version	Occurrence 1 .. 1 Type xs:string General Notes MESSAGE VERSION
	Applicable Codes
	2.0 Version 2.0
Invoice	Occurrence 1 .. 1 Type Invoice
xs:sequence	Occurrence 1 .. 1
Invoiceld	Occurrence 1 .. 1 Type xs:string General Notes INVOICE IDENTIFIER
	Examples <Invoiceld>INVOICE123</Invoiceld>
Dates	Occurrence 0 .. 1 Type DateList General Notes INVOICE DATES
	Examples <Dates> <Date Format="DateTimeSec" Type="IssueDate"> <DateTime>202608081700</DateTime> </Date> <Date Format="Date" Type="DueDate"> <DateTime>20260831</DateTime> </Date> <Date Format="Date" Type="InvoiceIssue"> <DateTime>20260808</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type Date General Notes INVOICE DATE
Type	Type xs:string Use required General Notes DATE TYPE
	Applicable Codes
	InvoiceIssue Invoice Issue Date
	IssueDate Document Issued Date
Format	Type xs:string Use required General Notes DATE FORMAT

Element/Attribute	Annotation
	Applicable Codes
	Date YYYYMMDD
	DateTime YYYYMMDDHHMM
	DateTimeSec CCYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes DATE / TIME
FreeTextData	Occurrence 0 .. 1
	Type FreeTextList
	General Notes INVOICE FREE TEXT
	Examples
	<FreeTextData>
	<FreeText Type="Note">
	<TextLine1>Notes Text Line 1</TextLine1>
	<TextLine2>Notes Text Line 2</TextLine2>
	<TextLine3>Notes Text Line 3</TextLine3>
	<TextLine4>Notes Text Line 4</TextLine4>
	<TextLine5>Notes Text Line 5</TextLine5>
	</FreeText>
	</FreeTextData>
	<FreeTextData>
	<FreeText Type="DocumentIssuerDeclaration" >
	<TextLine1>EAN:991122333</TextLine1>
	</FreeText>
	</FreeTextData>
xs:sequence	Occurrence 1 .. 1
FreeText	Occurrence 0 .. unbounded
	Type FreeText
Type	Type xs:string
	Use required
	General Notes FREE TEXT TYPE
	Applicable Codes
	DocumentIssuerDeclaration Document Issuer Declaration
	Note Note
xs:sequence	Occurrence 1 .. 1
TextLine1	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 1
TextLine2	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 2
TextLine3	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 3
TextLine4	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 4
TextLine5	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 5
Locations	Occurrence 0 .. 1
	Type LocationGroupList

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation
	General Notes INVOICE LOCATIONS Examples <Locations> <LocationGroup> <Location Type="DSVOrigin"> <LocationIdentification Type="DSVBranch"> <LocationIdentifier>BRY</LocationIdentifier> </LocationIdentification> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DK</LocationIdentifier> </LocationIdentification> <LocationIdentification Type="DSVDepartment"> <LocationIdentifier>FES</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type Location
Type	Type xs:string
	Use required
	General Notes LOCATION TYPE
	Applicable Codes DSVOrigin DSVOrigin
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
Type	Type xs:string
	General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes DSVBookingOffice DSV Booking Office (Only used for Road Freight) DSVBranch DSV Branch (Only used for Air, Sea & Rail) DSVDepartment DSV Department (Only used for Air, Sea & Rail) IATA IATA airport code ISOCountry Originating Country ISO Code (Only used for Air, Sea & Rail) UN UN Location code
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION IDENTIFIER
References	Occurrence 0 .. 1
	Type ReferenceGroupList
	Examples <References> <ReferenceGroup> <Reference Type="ShipmentReference" >SKUL1234567</Reference> </ReferenceGroup>



Element/Attribute	Annotation
	Examples <ReferenceGroup> <Reference Type="HouseBill" >111-12345678</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="MasterBill" >111-89012345</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ShipperReference">S42900531</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">ConsRef1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="OrderReference" >SI1HA1123456</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="BookingReference">ABCDE-12345</Reference> <Date Format="DateTimeSec" Type="ReferenceDate"> <DateTime>20260806144600</DateTime> </Date> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes INVOICE REFERENCE
Type	Type xs:string Use required General Notes REFERENCE TYPE Predefined Types listed, additional reference types to be agreed
Applicable Codes AirWayBill Air waybill number CargoManifestNo Cargo manifest number, Transport Id ConsigneeReference Consignee Reference ExchangeRate Exchange Rate GINCNumber Waybill number, GINC HouseBill House bill of lading number LanguageCode Language Code MasterBill Master Bill OrderReference Order Reference OriginatorsReference Originator's Reference PaymentId Payment Id PaymentReference Payment Reference RoadWaybill Road Waybill number, SIS ShipmentReference Shipment reference number ShipperReference Shipper Reference TaxCategory Tax and Category TransactionsCount Transactions Count TransportInstructionNumber Transport instruction number USDToEURExchangeRate USD To EUR Exchange Rate	
CustomField Type	Type xs:string Use optional

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation
	General Notes CUSTOM FIELD TYPE Use to be agreed
Date	Occurrence 0 .. 1 Type Date General Notes INVOICE REFERENCE DATE
<i>Type</i>	Type xs:string Use required General Notes INVOICE REFERENCE DATE TYPE
<i>Format</i>	Applicable Codes ReferenceDate Reference Date Type xs:string Use required General Notes INVOICE REFERENCE DATE FORMAT
<i>xs:sequence</i>	Applicable Codes DateTime CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS
DateTime	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes INVOICE REFERENCE DATE/TIME
Parties	Occurrence 0 .. 1 Type PartiesList
<i>xs:sequence</i>	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded Type Party
<i>xs:sequence</i>	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1 Type PartyDetails General Notes INVOICE PARTY DETAILS
	Examples <pre> <PartyDetails Role="InvoiceIssuer"> <Id>InvoiceIssuerID</Id> <Assignor>InvoiceIssuer</Assignor> <PartyName>InvoiceIssuer Name</PartyName> <AddressLine1>InvoiceIssuer Addr Line 1</AddressLine1> <AddressLine2>InvoiceIssuer Addr Line 2</AddressLine2> <AddressLine3>InvoiceIssuer Addr Line 3</AddressLine3> <CityName>InvoiceIssuer City</CityName> <State>InvoiceIssuer State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails> </pre>
<i>Role</i>	Type xs:string Use required General Notes INVOICE PARTY ROLE
	Applicable Codes InvoiceIssuer Invoice issuer Invoicee Invoicee
<i>xs:sequence</i>	Occurrence 1 .. 1
Id	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER



Element/Attribute	Annotation
Assignor	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER ASSIGNOR
PartyName	Occurrence 0 .. 1 Type xs:string General Notes PARTY NAME
AddressLine1	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1 Type xs:string General Notes PARTY CITY NAME
State	Occurrence 0 .. 1 Type xs:string General Notes PARTY STATE OR PROVINCE
PostCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY LOCATION ISO COUNTRY CODE
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes INVOICE PARTY LOCATIONS Examples <pre> <Locations> <LocationGroup> <Location Type="PhysicalLocation"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen V</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type Location
Type	Type xs:string Use required General Notes INVOICE PARTY LOCATIONTYPE



Element/Attribute	Annotation
	Applicable Codes
	PhysicalLocation Place of Physical Location
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
Type	Type xs:string
	General Notes INVOICE PARTY LOCATIONTYPE
	Applicable Codes
	UN UN Location Code
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
	General Notes INVOICE PARTY LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1
	Type xs:string
	General Notes INVOICE PARTY LOCATION NAME
Contact	Occurrence 0 .. unbounded
	Type Contact
	General Notes PARTY CONTACT DETAILS
	Examples
	<Contact Type="InformationContact">
	<Name>Contact name</Name>
	<Phone>Contact Phone</Phone>
	<Mobile>Contact Mobile</Mobile>
	<Fax>Contact Fax</Fax>
	<Email>Contact Email</Email>
	</Contact>
Type	Type xs:string
	Use required
	General Notes PARTY CONTACT TYPE
	Applicable Codes
	AccountsReceivableContact Accounts Receivable Contact
	InformationContact Information Contact
xs:sequence	Occurrence 1 .. 1
ContactId	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CONTACT ID
Name	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CONTACT PHONE NUMBER
Mobile	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CONTACT MOBILE NUMBER
Fax	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CONTACT FAX NUMBER
Email	Occurrence 0 .. 1
	Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 22 / 76



Element/Attribute	Annotation
	General Notes PARTY CONTACT E-MAIL ADDRESS
FinancialInstitution	Occurrence 0 .. unbounded Type FinancialInstitution General Notes PARTY FINANCIAL INSTITUTION DETAILS ex of how the FinancialInstitution can look like, please always check the payment details with your DSV contact. Examples <FinancialInstitution Role="InvoiceIssuer"> <AccountHolderId>IBAN: SE6195000099601800786939</ AccountHolderId> <AccountHolderName>DSV Air & Sea A/S</ AccountHolderName> <InstitutionNameCode>NDEASESS</InstitutionNameCode> <ResponsibleAgencyCode>SWIFT</ ResponsibleAgencyCode> <InstitutionBranchId>786939</InstitutionBranchId> <InstitutionName>9960</InstitutionName> <InstitutionBranchLocationName>NORDEA SE</ InstitutionBranchLocationName> </FinancialInstitution>
Role	Type xs:string Use required General Notes FINANCIAL INSTITUTION ROLE Applicable Codes InvoiceIssuer Invoice issuer
xs:sequence	Occurrence 1 .. 1
AccountHolderId	Occurrence 0 .. 1 Type xs:string General Notes ACCOUNT HOLDER IDENTIFIER IBAN nr/BankAddress
AccountHolderName	Occurrence 0 .. 1 Type xs:string General Notes ACCOUNT HOLDER NAME
InstitutionNameCode	Occurrence 0 .. 1 Type xs:string General Notes INSTITUTION NAME CODE SWIFT code
ResponsibleAgencyCode	Occurrence 0 .. 1 Type xs:string General Notes RESPONSIBLE AGENCY CODE if SWIFT is used, then SWIFT is present Applicable Codes SWIFT SWIFT
InstitutionBranchId	Occurrence 0 .. 1 Type xs:string General Notes INSTITUTION BRANCH IDENTIFIER BankAccount number
InstitutionName	Occurrence 0 .. 1 Type xs:string General Notes INSTITUTION NAME BranchNumber of Name of Bank

Element/Attribute	Annotation				
InstitutionBranchLocationName	Occurrence 0 .. 1 Type xs:string General Notes INSTITUTION BRANCH LOCATION NAME Name of Bank				
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes PARTY REFERENCES Examples <References> <ReferenceGroup> <Reference Type="VAT Registration number">VAT Registration number</Reference> </ReferenceGroup> </References>				
xs:sequence	Occurrence 1 .. 1				
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup Occurrence 1 .. 1				
xs:sequence	Occurrence 0 .. 1				
Reference	Occurrence 0 .. 1 Type Reference General Notes REFERENCE				
<i>Type</i>	Type xs:string Use required General Notes REFERENCE TYPE Predefined Types listed, additional reference types to be agreed				
<table border="1"> <thead> <tr> <th colspan="2">Applicable Codes</th></tr> </thead> <tbody> <tr> <td>VAT</td><td>VAT Registration number</td></tr> </tbody> </table>		Applicable Codes		VAT	VAT Registration number
Applicable Codes					
VAT	VAT Registration number				
<i>Identifier</i>	Type xs:string Use optional General Notes REFERENCE IDENTIFIER				
<i>CustomFieldType</i>	Type xs:string Use optional General Notes REFERENCE CUSTOM FIELD TYPE Use to be agreed				
Documents	Occurrence 0 .. 1 Type DocumentList General Notes PARTY DOCUMENT DETAILS Examples <Documents> <Document> <DocumentCode>ConsignmentInvoice</DocumentCode> </Document> </Documents>				
xs:sequence	Occurrence 1 .. 1				
Document	Occurrence 0 .. unbounded Type Document Occurrence 1 .. 1				
xs:sequence	Occurrence 0 .. 1				
DocumentCode	Occurrence 0 .. 1 Type xs:string				



Element/Attribute	Annotation
	General Notes DOCUMENT TYPE
	Applicable Codes
	ConsignmentInvoice Consignment invoice
	ConsolidatedInvoice Consolidated invoice
Currencies	Occurrence 0 .. 1 Type CurrencyGroupList General Notes INVOICE CURRENCIES Examples <Currencies> <CurrencyDetails> <Currency> <CurrencyUsage>InvoiceCurrency</CurrencyUsage> <CurrencyIdentification>InvoiceCurrency</CurrencyIdentification> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>3.6000</CurrencyRate> </Currency> <Dates> <Date Format="DateTimeSec" Type="RateOfExchange"> <DateTime>20260801145400</DateTime> </Date> </Dates> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyUsage>LocalCurrency</CurrencyUsage> <CurrencyIdentification>LocalCurrency</CurrencyIdentification> <CurrencyCode>ILS</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> <Dates> <Date Format="DateTimeSec" Type="RateOfExchange"> <DateTime>20260728083000</DateTime> </Date> </Dates> </CurrencyDetails> </Currencies>
xs:sequence	Occurrence 1 .. 1
CurrencyDetails	Occurrence 0 .. unbounded Type CurrencyGroup
xs:sequence	Occurrence 1 .. 1
Currency	Occurrence 0 .. 1 Type Currency
xs:sequence	Occurrence 1 .. 1
CurrencyUsage	Occurrence 0 .. 1 Type xs:string General Notes CURRENCY USAGE Applicable Codes
HomeCurrency	HomeCurrency
InvoicingCurrency	Invoicing Currency
CurrencyIdentification	Occurrence 0 .. 1 Type xs:string General Notes CURRENCY IDENTIFICATION
CurrencyCode	Occurrence 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation
	General Notes CURRENCY CODE
	Applicable Codes
	HomeCurrency Home Currency
	InvoicingCurrency Invoicing Currency
CurrencyRate	Occurrence 0 .. 1 Type xs:string General Notes CURRENCY RATE
Dates	Occurrence 0 .. 1 Type DateList
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type Date General Notes INVOICE CURRENCY DATE
Type	Type xs:string Use required General Notes DATE TYPE
	Applicable Codes
Format	RateOfExchange Rate of exchange date/time Type xs:string Use required General Notes DATE FORMAT
	Applicable Codes
	Date YYYYMMDD
	DateTime YYYYMMDDHHMM
	DateTimeSec CCYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string General Notes DATE / TIME
PaymentTerms	Occurrence 0 .. 1 Type PaymentTermsList General Notes INVOICE PAYMENT TERMS
	Examples <PaymentTerms> <PaymentTermsDetails> <PaymentTerms Type="FixedDate"> <PaymentTermsDescription>Fixed date</ PaymentTermsDescription> <PeriodCount>0</PeriodCount> </PaymentTerms> <Dates> <Date Format="Date" Type="DueDate"> <DateTime>20260831</DateTime> </Date> </Dates> </PaymentTermsDetails> </PaymentTerms>
xs:sequence	Occurrence 1 .. 1
PaymentTermsDetails	Occurrence 0 .. unbounded Type PaymentTermsDetails
xs:sequence	Occurrence 1 .. 1
PaymentTerms	Occurrence 1 .. 1 Type PaymentTerms

Element/Attribute	Annotation
Type	Type xs:string Use required General Notes PAYMENT TERMS TYPE
PaymentTermsDescription	Applicable Codes ContractBasis Contract Basis DatingGiven Dating Given EndOfMonth End of Month FixedDate Fixed Date PreviouslyAgreedUpon Previously Agreed Upon
PeriodType	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes PAYMENT TERMS DESCRIPTION
PeriodCount	Occurrence 0 .. 1 Type xs:string General Notes PERIOD TYPE
Dates	Applicable Codes Day Day Month Month Occurrence 0 .. 1 Type xs:string General Notes PERIOD COUNT
Date	Occurrence 0 .. 1 Type DateList General Notes PAYMENT TERMS DATES Examples <Dates> <Date Format="Date" Type="DueDate"> <DateTime>2060831</DateTime> </Date> </Dates>
Format	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type Date Type xs:string Use required General Notes PAYMENT DATE TYPE
DateTime	Applicable Codes DueDate DueDate Type xs:string Use required General Notes PAYMENT DATE FORMAT
TransportStages	Applicable Codes Date YYYYMMDD Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes PAYMENT DATE / TIME
	Occurrence 0 .. 1 Type TransportStageList General Notes INVOICE TRANSPORT STAGES
	Occurrence 1 .. 1



Element/Attribute	Annotation												
TransportStage	Occurrence 0 .. unbounded Type TransportStage												
xs:sequence	Occurrence 1 .. 1												
Stage	Occurrence 0 .. 1 Type Stage General Notes TRANSPORTATION STAGE Examples <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> <TransportId>017W</TransportId> <CarrierId>12345678</CarrierId> <CarrierName>Carrier line</CarrierName> <TransportType>Main</TransportType> <TransportMeansName>Vesselname</TransportMeansName> <TransportMeansNationality>DK</TransportMeansNationality> </Stage>												
Type	Type xs:string Use required General Notes TRANSPORTATION STAGE TYPE Applicable Codes <table> <tr> <td>MainCarriage</td><td>Main Carriage</td></tr> <tr> <td>PlannedLeg1</td><td>Main carriage - first carrier</td></tr> <tr> <td>PlannedLeg2</td><td>Main carriage - second carrier</td></tr> <tr> <td>PlannedLeg3</td><td>Main carriage - third carrier</td></tr> <tr> <td>PlannedLeg4</td><td>Main carriage - fourth carrier</td></tr> <tr> <td>PlannedLeg5</td><td>Main carriage - fifth carrier</td></tr> </table>	MainCarriage	Main Carriage	PlannedLeg1	Main carriage - first carrier	PlannedLeg2	Main carriage - second carrier	PlannedLeg3	Main carriage - third carrier	PlannedLeg4	Main carriage - fourth carrier	PlannedLeg5	Main carriage - fifth carrier
MainCarriage	Main Carriage												
PlannedLeg1	Main carriage - first carrier												
PlannedLeg2	Main carriage - second carrier												
PlannedLeg3	Main carriage - third carrier												
PlannedLeg4	Main carriage - fourth carrier												
PlannedLeg5	Main carriage - fifth carrier												
xs:sequence	Occurrence 1 .. 1												
ModeOfTransport	Occurrence 0 .. 1 Type xs:string General Notes MODE OF TRANSPORTATION Applicable Codes <table> <tr> <td>Air</td><td>Air transportation</td></tr> <tr> <td>Road</td><td>Road transportation</td></tr> <tr> <td>Sea</td><td>Sea transportation</td></tr> </table>	Air	Air transportation	Road	Road transportation	Sea	Sea transportation						
Air	Air transportation												
Road	Road transportation												
Sea	Sea transportation												
TransportId	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT IDENTIFICATION												
CarrierId	Occurrence 0 .. 1 Type xs:string General Notes CARRIER IDENTIFICATION Air & Sea: DSV carrier identifier Road: Not used												
CarrierName	Occurrence 0 .. 1 Type xs:string General Notes CARRIER NAME Road: Not used												
TransportType	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT TYPE Road: Not used												
TransportMeansName	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NAME Sea: Vessel Name												

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEFG.FX

Page: 28 / 76



Element/Attribute	Annotation																				
	Air & Road: Not used																				
TransportMeansNationality	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NATIONALITY Sea: Vessel Nationality Air & Road: Not used																				
Dates	Occurrence 0 .. 1 Type DateList General Notes TRANSPORTATION DATES Examples <Dates> <Date Format="DateTimeSec" Type="ScheduledDeparture"> <DateTime>20260721093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentDeparture"> <DateTime>20260721093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledArrival"> <DateTime>20260719000100</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentArrival"> <DateTime>20260719000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDeparture"> <DateTime>20260721093500</DateTime> </Date> </Dates>																				
xs:sequence	Occurrence 1 .. 1																				
Date	Occurrence 0 .. unbounded Type Date																				
Type	Type xs:string Use required General Notes TRANSPORTATION DATE TYPE Applicable Codes <table> <tr> <td>ActualArrival</td><td>Actual Time of Arrival</td></tr> <tr> <td>ActualDelivery</td><td>Actual Delivery date/time</td></tr> <tr> <td>ActualDeparture</td><td>Actual Time of Departure</td></tr> <tr> <td>EstimatedArrival</td><td>Estimated Time of Arrival</td></tr> <tr> <td>EstimatedDelivery</td><td>Delivery date/time, estimated</td></tr> <tr> <td>EstimatedDeparture</td><td>Estimated Time of Departure</td></tr> <tr> <td>ScheduledArrival</td><td>Scheduled Time of Arrival</td></tr> <tr> <td>ScheduledDeparture</td><td>Scheduled Time of Departure</td></tr> <tr> <td>ScheduledShipmentArrival</td><td>Scheduled Shipment Time of Arrival</td></tr> <tr> <td>ScheduledShipmentDeparture</td><td>Scheduled Shipment Time of Departure</td></tr> </table>	ActualArrival	Actual Time of Arrival	ActualDelivery	Actual Delivery date/time	ActualDeparture	Actual Time of Departure	EstimatedArrival	Estimated Time of Arrival	EstimatedDelivery	Delivery date/time, estimated	EstimatedDeparture	Estimated Time of Departure	ScheduledArrival	Scheduled Time of Arrival	ScheduledDeparture	Scheduled Time of Departure	ScheduledShipmentArrival	Scheduled Shipment Time of Arrival	ScheduledShipmentDeparture	Scheduled Shipment Time of Departure
ActualArrival	Actual Time of Arrival																				
ActualDelivery	Actual Delivery date/time																				
ActualDeparture	Actual Time of Departure																				
EstimatedArrival	Estimated Time of Arrival																				
EstimatedDelivery	Delivery date/time, estimated																				
EstimatedDeparture	Estimated Time of Departure																				
ScheduledArrival	Scheduled Time of Arrival																				
ScheduledDeparture	Scheduled Time of Departure																				
ScheduledShipmentArrival	Scheduled Shipment Time of Arrival																				
ScheduledShipmentDeparture	Scheduled Shipment Time of Departure																				
Format	Type xs:string Use required General Notes TRANSPORTATION DATE FORMAT Applicable Codes <table> <tr> <td>DateTime</td><td>CCYYMMDDHHMM</td></tr> <tr> <td>DateTimeInterval</td><td>CCYYMMDDHHMM- CCYYMMDDHHMM</td></tr> <tr> <td>DateTimeSec</td><td>CCYYMMDDHHMMSS</td></tr> </table>	DateTime	CCYYMMDDHHMM	DateTimeInterval	CCYYMMDDHHMM- CCYYMMDDHHMM	DateTimeSec	CCYYMMDDHHMMSS														
DateTime	CCYYMMDDHHMM																				
DateTimeInterval	CCYYMMDDHHMM- CCYYMMDDHHMM																				
DateTimeSec	CCYYMMDDHHMMSS																				
xs:sequence	Occurrence 1 .. 1																				
DateTime	Occurrence 0 .. 1 Type xs:string																				

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEF.FX

Page: 29 / 76



Element/Attribute	Annotation																																						
	General Notes TRANSPORTATION DATE/TIME																																						
TransportServices	Occurrence 0 .. 1 Type ServiceGroupList General Notes TRANSPORTATION STAGE SERVICES REQUIRED First occurrence is Main Service Additional services will be provided in subsequent occurrences Examples <pre> <TransportServices> <ServiceGroup> <TransportService> <ServiceCode>FCL</ServiceCode> </TransportService> </ServiceGroup> <ServiceGroup> <TransportService> <ServiceCode>Insurance</ServiceCode> </TransportService> </ServiceGroup> <ServiceGroup> <TransportService> <ServiceCode>STD</ServiceCode> </TransportService> </ServiceGroup> </TransportServices> </pre>																																						
xs:sequence	Occurrence 1 .. 1																																						
ServiceGroup	Occurrence 0 .. unbounded Type ServiceGroup																																						
xs:sequence	Occurrence 1 .. 1																																						
TransportService	Occurrence 0 .. 1 Type TransportService																																						
xs:sequence	Occurrence 1 .. 1																																						
ServiceCode	Occurrence 0 .. 1 Type xs:string General Notes TYPE OF SERVICE REQUIRED Applicable Codes <table> <tr><td>Before10</td><td>Express 10:00</td></tr> <tr><td>Before12</td><td>Express 12:00</td></tr> <tr><td>Before16</td><td>Express 16:00</td></tr> <tr><td>Before7</td><td>Express 07:00</td></tr> <tr><td>Crane</td><td>Crane required loading or unloading or both</td></tr> <tr><td>FCL</td><td>Full Container Load</td></tr> <tr><td>FTL</td><td>Full Truckload</td></tr> <tr><td>HAZ</td><td>Hazardous goods</td></tr> <tr><td>IATA</td><td>Air - IATA</td></tr> <tr><td>InNightproduct</td><td>InNight product</td></tr> <tr><td>LCL</td><td>Less Than Container Load</td></tr> <tr><td>LSE</td><td>Air - LSE</td></tr> <tr><td>LTL</td><td>Less Than Truckload</td></tr> <tr><td>Lift</td><td>Tail lift</td></tr> <tr><td>Notification</td><td>Notify</td></tr> <tr><td>OMEX</td><td>Omex service goods</td></tr> <tr><td>PersonalDeliveryService</td><td>Personal delivery service</td></tr> <tr><td>PreAdvice</td><td>Pre-advice</td></tr> <tr><td>ePallet</td><td>E-service pallet</td></tr> </table>	Before10	Express 10:00	Before12	Express 12:00	Before16	Express 16:00	Before7	Express 07:00	Crane	Crane required loading or unloading or both	FCL	Full Container Load	FTL	Full Truckload	HAZ	Hazardous goods	IATA	Air - IATA	InNightproduct	InNight product	LCL	Less Than Container Load	LSE	Air - LSE	LTL	Less Than Truckload	Lift	Tail lift	Notification	Notify	OMEX	Omex service goods	PersonalDeliveryService	Personal delivery service	PreAdvice	Pre-advice	ePallet	E-service pallet
Before10	Express 10:00																																						
Before12	Express 12:00																																						
Before16	Express 16:00																																						
Before7	Express 07:00																																						
Crane	Crane required loading or unloading or both																																						
FCL	Full Container Load																																						
FTL	Full Truckload																																						
HAZ	Hazardous goods																																						
IATA	Air - IATA																																						
InNightproduct	InNight product																																						
LCL	Less Than Container Load																																						
LSE	Air - LSE																																						
LTL	Less Than Truckload																																						
Lift	Tail lift																																						
Notification	Notify																																						
OMEX	Omex service goods																																						
PersonalDeliveryService	Personal delivery service																																						
PreAdvice	Pre-advice																																						
ePallet	E-service pallet																																						

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation
PriorityCode	Applicable Codes eParcel E-service parcel Occurrence 0 .. 1 Type xs:string
ServiceGroup <ShipmentService>	Applicable Codes Express Express Service HighSpeed High Speed Service Normal Normal Service Occurrence 0 .. unbounded Type ServiceGroup
TransportService	Occurrence 1 .. 1 Occurrence 0 .. 1 Type TransportService Examples <TransportService> <ServiceCode>OMEX</ServiceCode> </TransportService>
ServiceCode	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes Type of SERVICE CODE
FreeTextData	Occurrence 0 .. 1 Type FreeTextList General Notes FREETEXT NOTE FOR SHIPMENTSERVICES Examples <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
FreeText	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type FreeText Type xs:string Use required
TextLine1	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes FREETEXT NOTE FOR SHIPMENTSERVICES
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes TRANSPORTATION STAGE LOCATIONS Examples <Locations> <LocationGroup> <Location Type="Loading"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DE</LocationIdentifier> <LocationName>Germany</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>DEHAM</LocationIdentifier> <LocationName>Hamburg</LocationName> </LocationIdentification>

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 31 / 76



Element/Attribute	Annotation
Examples <pre> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>US</LocationIdentifier> <LocationName>United States</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>USCPT</LocationIdentifier> <LocationName>Carpinteria</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Unloading"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>US</LocationIdentifier> <LocationName>United States</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>USHOU</LocationIdentifier> <LocationName>Houston</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DK</LocationIdentifier> <LocationName>Denmark</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>DKGLS</LocationIdentifier> <LocationName>Glostrup</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>	
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type Location
<i>Type</i>	Type xs:string
	Use required
	General Notes TRANSPORTATION LOCATION TYPE
Applicable Codes	
Departure	Place of Departure
Destination	Place of Destination
PlaceOfLoading	Place of Loading
PlaceOfUnloading	Place of Unloading
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
<i>Type</i>	Type xs:string



Element/Attribute	Annotation						
	General Notes LOCATION IDENTIFIER TYPE						
	Applicable Codes						
	<table> <tr> <td>GS1</td><td>GS1</td></tr> <tr> <td>IATA</td><td>IATA</td></tr> <tr> <td>UN</td><td>UN</td></tr> </table>	GS1	GS1	IATA	IATA	UN	UN
GS1	GS1						
IATA	IATA						
UN	UN						
xs:sequence	Occurrence 1 .. 1						
LocationIdentifier	Occurrence 0 .. 1						
	Type xs:string						
	General Notes LOCATION IDENTIFIER						
LocationName	Occurrence 0 .. 1						
	Type xs:string						
	General Notes LOCATION NAME						
References	Occurrence 0 .. 1						
	Type ReferenceGroupList						
	General Notes TRANSPORTATION STAGE REFERENCES						
	Examples						
	<pre> <References> <ReferenceGroup> <Reference Type="TransportMasterType">CLD</ Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="MasterBill">ABC123456</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="VesselLloydsIMO">XXXXXXX</ Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="TransportMasterId">DEFG123456</ Reference> </ReferenceGroup> <Reference Type="Originator_ShipmentId">ShipmentId1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ShipperReference">ShipperRef2</ Reference> </ReferenceGroup> </References> </pre>						
xs:sequence	Occurrence 1 .. 1						
ReferenceGroup	Occurrence 0 .. unbounded						
	Type ReferenceGroup						
xs:sequence	Occurrence 1 .. 1						
Reference	Occurrence 0 .. 1						
	Type Reference						
	General Notes TRANSPORTATION STAGE REFERENCE						
Type	Type xs:string						
	Use required						
	General Notes TRANSPORTATION STAGE REFERENCE TYPE						
Identifier	Type xs:string						
	Use optional						
	General Notes TRANSPORTATION STAGE REFERENCE IDENTIFIER						



Element/Attribute	Annotation
<i>CustomFieldType</i>	Type xs:string Use optional General Notes TRANSPORTATION STAGE REFERENCE CUSTOM FIELD TYPE Use to be agreed
TermsOfDelivery	Occurrence 0 .. 1 Type TermsGroup General Notes INVOICE TERMS OF DELIVERY Examples <TermsOfDelivery> <Terms> <TermCode>CIP</TermCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>
<i>xs:sequence</i>	Occurrence 1 .. 1
Terms	Occurrence 0 .. 1 Type Terms General Notes INVOICE TERMS OF DELIVERY
<i>xs:sequence</i>	Occurrence 1 .. 1
TermsCode	Occurrence 0 .. 1 Type xs:string General Notes TERM CODE
CodeId	Occurrence 0 .. 1 Type xs:string General Notes TYPE OF TERM CODE Applicable Codes CombiTerms Combi Terms IncoTerms INCO Terms
Location	Occurrence 0 .. unbounded Type Location General Notes TERMS OF DELIVERY LOCATION
<i>Type</i>	Type xs:string Use required General Notes TERM LOCATION TYPE Applicable Codes NamedPlace Named Place
<i>xs:sequence</i>	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
<i>Type</i>	Type xs:string General Notes LOCATION IDENTIFIER TYPE Applicable Codes GS1 GS1 IATA IATA UN UN



Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1 Type xs:string General Notes LOCATION NAME
EquipmentUnits	Occurrence 0 .. 1 Type EquipmentUnitList General Notes INVOICE EQUIPMENT INFORMATION Examples For containerized sea freight: <EquipmentUnits> <EquipmentUnit> <EquipmentType> <Type>Container</Type> <UnitId>ABCD1234567</UnitId> <SizeTypeCode>40HC</SizeTypeCode> <ISOCODE>40HC</ISOCODE> <PackingMode>LCL</PackingMode> <EquipmentSizeDescription>Forty foot high cube</EquipmentSizeDescription> </EquipmentType> <NumberOfUnits>1</NumberOfUnits> <SealIds> <Seal> <SealId>EFGH123456789</SealId> <SealParty>Shipper</SealParty> </Seal> </SealIds>
xs:sequence	Occurrence 1 .. 1
EquipmentUnit	Occurrence 0 .. unbounded Type EquipmentUnit General Notes EQUIPMENTUNIT
xs:sequence	Occurrence 1 .. 1
EquipmentType	Occurrence 0 .. 1 Type EquipmentType General Notes EQUIPMENT TYPE INFORMATION
xs:sequence	Occurrence 1 .. 1
Type	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT TYPE Applicable Codes Container Shipping Container EFP Euro Flat Pallet EUR Euro Pallet Trailer Trailer
UnitId	Occurrence 0 .. 1 Type xs:string General Notes INVOICE CONTAINER NUMBER
SizeTypeCode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER SIZE AND TYPE

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 35 / 76



Element/Attribute	Annotation
	DSV specified Container Type for Shipping Container
	Applicable Codes
	20GP 20 ft General Purpose
	20RE 20 ft Reefer
	40GP 40 ft General Purpose
	40HC 40 ft High Cube
	40NOR 40 ft high Cube, self powered Reefer
	40RE 40 ft Reefer
	40REHC 40 ft High Cube Reefer
ISOCode	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER ISO CODE
PackingMode	Occurrence 0 .. 1 Type xs:string General Notes PACKINGMODE
	Applicable Codes
	FCL Full Container Load
	LCL Less than full Container Load
EquipmentSizeDescription	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT SIZE DESCRIPTION
NumberOfUnits	Occurrence 0 .. 1 Type xs:decimal General Notes NUMBER OF UNITS
Measurements	Occurrence 0 .. 1 Type MeasurementList General Notes EQUIPMENT MEASUREMENTS Examples <Measurements> <Measurement Type="Volume" Uom="MTQ"> <Measure>64.510</Measure> </Measurement> <Measurement Type="Weight" Uom="KGM"> <Measure>19315.200</Measure> </Measurement> </Measurements>
xs:sequence	Occurrence 1 .. 1
Measurement	Occurrence 0 .. unbounded Type Measurement
Type	Type xs:string Use required General Notes EQUIPMENT MEASUREMENT TYPE
	Applicable Codes
	TareWeight
	Volume
	Weight
Uom	Type xs:string General Notes EQUIPMENT MEASUREMENT UNIT OF MEASURE
	Applicable Codes
	KGM Kilograms
	MTQ Cubic metres
xs:sequence	Occurrence 1 .. 1



Element/Attribute	Annotation
Measure	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MEASUREMENT
Dimensions	Occurrence 0 .. 1 Type DimensionsList General Notes EQUIPMENT DIMENSIONS Examples <Dimensions> <Dimension Type="Container" Uom="MTR"> <Length>36.000</Length> <Width>28.000</Width> <Height>40.000</Height> </Dimension> </Dimensions>
xs:sequence	Occurrence 1 .. 1
Dimension	Occurrence 0 .. unbounded Type Dimension Type xs:string Use required General Notes EQUIPMENT DIMENSION TYPE Applicable Codes Container
Type	
Uom	Type xs:string General Notes EQUIPMENT DIMENSION UNIT OF MEASURE Applicable Codes MTR
xs:sequence	Occurrence 1 .. 1
Length	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION LENGTH
Width	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION WIDTH
Height	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION HEIGHT
SealIds	Occurrence 0 .. 1 Type SealList General Notes SEAL INFORMATION FOR SHIPPING CONTAINERS Examples <SealIds> <Seal> <SealId>XX-12345678</SealId> </Seal> </SealIds>
xs:sequence	Occurrence 1 .. 1
Seal	Occurrence 0 .. unbounded Type Seal
xs:sequence	Occurrence 1 .. 1
SealId	Occurrence 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 37 / 76



Element/Attribute	Annotation
	General Notes SEAL NUMBER
SealParty	Occurrence 0 .. 1 Type xs:string General Notes SEALING PARTY
	Applicable Codes
	Shipper Shipper Sealing Party
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes EQUIPMENT REFERENCES Examples <References> <ReferenceGroup> <Reference Type="PackingMode">FCL</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="DeliveryMode">FCL</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes EQUIPMENT REFERENCE
Type	Type xs:string Use required General Notes EQUIPMENT REFERENCE TYPE
	Applicable Codes
	MasterBill Master bill of lading number OrderReference Order Reference PackageNumber Package Number ProofOfDeliveryNumber Proof of delivery reference number RoadWaybill Road Waybill number, SIS ShipmentReference Shipment reference number ShipperReference Shipper Reference TransportInstructionNumber Transport instruction number VehicleId Vehicle identification number (VIN) VesselCountryOfRegistration Vessel Country of Registration VesselId Vessel identifier
Identifier	Type xs:string Use optional General Notes REFERENCE IDENTIFIER
CustomFieldType	Type xs:string Use optional General Notes CUSTOM FIELD TYPE Use to be agreed
Dates	Occurrence 0 .. 1 Type DateList General Notes CONTAINER DATES Examples <Dates>



Element/Attribute	Annotation
	Examples <Date Format="DateTimeSec" Type="EstimatedCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="RequestedCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledCollection"> <DateTime>20260818120500</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedDelivery"> <DateTime>20260802124800</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDelivery"> <DateTime>20260823090200</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedFullPickup"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLOnBoardVessel"> <DateTime>20260806013500</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLUnloadFromVessel"> <DateTime>20260815135900</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateIn"> <DateTime>20260801085600</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateOut"> <DateTime>20260818101000</DateTime> </Date> <Date Format="DateTimeSec" Type="ContainerParkEmptyPickupGateOut"> <DateTime>20260830121700</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
	Type Date
Type	Type xs:string
	Use required
	General Notes CONTAINER DATE TYPE
	Applicable Codes
	VerifiedDate
Format	Type xs:string
	Use required
	General Notes CONTAINER DATE FORMAT
	Applicable Codes
	DateTime YYYYMMDDHHMM
	DateTimeInterval YYYYMMDDHHMM- YYYYMMDDHHMM
	DateTimeSec YYYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 39 / 76



Element/Attribute	Annotation
	General Notes CONTAINER DATE/TIME
TransportMovements	Occurrence 0 .. 1 Type TransportMovementList General Notes EQUIPMENT TRANSPORT MOVEMENTS Examples <TransportMovements> <TransportMovement Type="DeliveryMode"> <Code>CFS</Code> <Description>DSC</Description> </TransportMovement> </TransportMovements>
xs:sequence	Occurrence 1 .. 1
TransportMovement	Occurrence 0 .. unbounded Type CodeDescription
Type	Type xs:string Use optional General Notes EQUIPMENT TRANSPORT MOVEMENTS TYPE Applicable Codes DeliveryMode
xs:sequence	Occurrence 1 .. 1
Code	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MOVEMENT CODE Applicable Codes CFS/CFS CFS/CY CFS/DR CY/CFS CY/CY CY/DR DR/CFS DR/CY DR/DR FCL/FCL FCL/LCL LCL/FCL LCL/LCL RO/RO
Description	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MOVEMENT DESCRIPTION
TemperatureControl	Occurrence 0 .. 1 Type TemperatureControl General Notes CONTAINER TEMPERATURE Examples <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> <HumidityPercentage>25</HumidityPercentage> </TemperatureControl>
Type	Type xs:string Use required General Notes TEMPERATURE CONTROL TYPE

Element/Attribute	Annotation
	Applicable Codes
	Container
<i>Uom</i>	Type xs:string General Notes TEMPERATURE UNIT OF MEASURE
	Applicable Codes
	CEL Celsius
	FAH Fahrenheit
xs:sequence	Occurrence 1 .. 1
Fixed	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE
HumidityPercentage	Occurrence 0 .. 1 Type xs:string General Notes HUMIDITY PERCENTAGE
RangeDetails	Occurrence 0 .. 1 Type RangeDetails General Notes RANGE DETAILS
	Examples <RangeDetails Type="Container" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>
<i>Type</i>	Type xs:string Use required General Notes RANGE DETAILS TYPE
	Applicable Codes
	Container
<i>Uom</i>	Type xs:string General Notes TEMPERATURE UNIT OF MEASURE
	Applicable Codes
	CEL Celsius
	FAH Fahrenheit
xs:sequence	Occurrence 1 .. 1
Minimum	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE MINIMUM
Maximum	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE MAXIMUM
InvoiceLines	Occurrence 0 .. 1 Type InvoiceLinesList General Notes INVOICE LINES
xs:sequence	Occurrence 1 .. 1
InvoiceLine	Occurrence 0 .. unbounded Type LinelItem General Notes INVOICE LINE
xs:sequence	Occurrence 1 .. 1
LinelItem	Occurrence 0 .. 1 Type InvoiceLine General Notes INVOICE LINE IDENTIFIERS



Element/Attribute	Annotation		
	Examples <LinItem> <LineNumber>1</LineNumber> <ItemIdentifier>ABCD1234567</ItemIdentifier> </LinItem>		
xs:sequence	Occurrence 1 .. 1		
LineNumber	Occurrence 0 .. 1 Type xs:string General Notes LINE ITEM NUMBER		
ItemIdentifier	Occurrence 0 .. 1 Type xs:string General Notes ITEM IDENTIFIER		
ItemDescriptions	Occurrence 0 .. 1 Type ItemDescriptionList General Notes LINE ITEM DESCRIPTIONS Examples <ItemDescriptions> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>1</ItemCharacteristicCode> <ItemDescription>AES Filing Fee</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>2</ItemCharacteristicCode> <ItemDescription>Pick up/ Collection</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>8</ItemCharacteristicCode> <ItemDescription>Inland/Linehaul/Haulage</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>9</ItemCharacteristicCode> <ItemDescription>THC (Terminal Handling Charge) Import</ItemDescription> </ItemDescription> </ItemDescriptions>		
xs:sequence	Occurrence 1 .. 1		
ItemDescription	Occurrence 0 .. unbounded Type CodeDescription General Notes ITEM DESCRIPTION		
Type	Type xs:string Use optional General Notes ITEM DESCRIPTION TYPE		
	Applicable Codes <table> <tr> <th>Semi-Structured</th><th>Semi-Structured</th></tr> </table>	Semi-Structured	Semi-Structured
Semi-Structured	Semi-Structured		
xs:sequence	Occurrence 1 .. 1		
Code	Occurrence 0 .. 1 Type xs:string General Notes ITEM CODE		
Description	Occurrence 0 .. 1 Type xs:string General Notes ITEM DESCRIPTION		
Measurements	Occurrence 0 .. 1 Type MeasurementList		

Element/Attribute	Annotation														
	General Notes LINE ITEM MEASUREMENTS Examples <Measurements> <Measurement Type="GrossWeight" Uom="KGM"> <Measure>10.03</Measure> </Measurement> <Measurement Type="NetWeight" Uom="KGM"> <Measure>8.03</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.03</Measure> </Measurement> <Measurement Type="LoadingMeters" Uom="MTR"> <Measure>2.05</Measure> </Measurement> <Measurement Type="PalletSpaces" Uom="PLL"> <Measure>5</Measure> </Measurement> </Measurements>														
xs:sequence	Occurrence 1 .. 1														
Measurement	Occurrence 0 .. unbounded Type Measurement General Notes MEASUREMENT														
Type	Type xs:string Use required General Notes MEASUREMENT TYPE														
	Applicable Codes <table> <tr> <td>ChargeableWeight</td><td>Chargeable weight</td></tr> <tr> <td>ConsignmentGrossWeight</td><td>Consignment gross weight</td></tr> <tr> <td>GrossWeight</td><td>Gross weight</td></tr> <tr> <td>LoadingMeters</td><td>Loading Meters</td></tr> <tr> <td>NetWeight</td><td>Net weight</td></tr> <tr> <td>PalletSpaces</td><td>Pallet Spaces</td></tr> <tr> <td>Volume</td><td>Volume</td></tr> </table>	ChargeableWeight	Chargeable weight	ConsignmentGrossWeight	Consignment gross weight	GrossWeight	Gross weight	LoadingMeters	Loading Meters	NetWeight	Net weight	PalletSpaces	Pallet Spaces	Volume	Volume
ChargeableWeight	Chargeable weight														
ConsignmentGrossWeight	Consignment gross weight														
GrossWeight	Gross weight														
LoadingMeters	Loading Meters														
NetWeight	Net weight														
PalletSpaces	Pallet Spaces														
Volume	Volume														
Uom	Type xs:string General Notes MEASUREMENT UNIT OF MEASURE														
	Applicable Codes <table> <tr> <td>KGM</td><td>Kilograms</td></tr> <tr> <td>MTQ</td><td>Cubic metres</td></tr> <tr> <td>MTR</td><td>Linear Meters</td></tr> <tr> <td>PLL</td><td>Pallets</td></tr> </table>	KGM	Kilograms	MTQ	Cubic metres	MTR	Linear Meters	PLL	Pallets						
KGM	Kilograms														
MTQ	Cubic metres														
MTR	Linear Meters														
PLL	Pallets														
xs:sequence	Occurrence 1 .. 1														
Measure	Occurrence 0 .. 1 Type xs:string General Notes MEASUREMENT VALUE														
Dates	Occurrence 0 .. 1 Type DateList General Notes INVOICE LINE DATES Examples <Dates> <Date Format="DateTimeSec" Type="EstimatedCollection"> <DateTime>20260802160000</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualCollection"> <DateTime>20260803080000</DateTime>														



Element/Attribute	Annotation
	Examples </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type Date General Notes DATE
Type	Type xs:string Use required General Notes INVOICE LINE DATE TYPE
	Applicable Codes
	ActualArrival Transport means arrival date time, actual ActualCollection Collection date/time, latest ActualDelivery Delivery date/time, actual ActualDeparture Transport means departure date/time, actual CargoPickup Cargo pick-up date / time Collection Collection date/time, earliest ConsignmentLoading Consignment loading date time DeliveryRequested Delivery Requested EstimatedDelivery Delivery date/time, estimated ScheduledArrival Scheduled Arrival ScheduledDelivery Delivery date/time, 1st schedule ScheduledDeparture Scheduled Departure ScheduledShipmentArrival Completion date or time, scheduled ScheduledShipmentDeparture Start date or time, scheduled ShipmentReqDate Shipment requested date/time
Format	Type xs:string Use required General Notes INVOICE LINE DATE FORMAT
	Applicable Codes
	Date YYYYMMDD DateTime YYYYMMDDHHMM DateTimeInterval YYYYMMDDHHMM- YYYYMMDDHHMM DateTimeSec YYYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string General Notes INVOICE LINE DATE / TIME
EquipmentUnits	Occurrence 0 .. 1 Type EquipmentUnitList General Notes INVOICE LINE EQUIPMENT INFORMATION
	Examples <EquipmentUnits> <EquipmentUnit> <EquipmentType> <Type>Container</Type> <UnitId>ABCD1234567</UnitId> <SizeTypeCode>45G1</SizeTypeCode> <ISOCODE>ISOCODEEQD</ISOCODE> <PackingMode>FCL</PackingMode> </EquipmentType> </EquipmentUnit>

Element/Attribute	Annotation
	Examples </EquipmentUnits>
xs:sequence	Occurrence 1 .. 1
EquipmentUnit	Occurrence 0 .. unbounded Type EquipmentUnit General Notes EQUIPMENT UNIT DETAILS
xs:sequence	Occurrence 1 .. 1
EquipmentType	Occurrence 0 .. 1 Type EquipmentType General Notes EQUIPMENT TYPE INFORMATION
xs:sequence	Occurrence 1 .. 1
Type	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT TYPE
	Applicable Codes
	Container Ocean Container EFP Euro Flat Pallet EUR Euro Pallet Trailer Trailer
UnitId	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER NUMBER
SizeTypeCode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER SIZE AND TYPE DSV specified Container Type for Shipping Container
	Applicable Codes
	20GP 20 ft General Purpose 20RE 20 ft Reefer 40GP 40 ft General Purpose 40HC 40 ft High Cube 40NOR 40 ft high Cube, self powered Reefer 40RE 40 ft Reefer 40REHC 40 ft High Cube Reefer
ISOCODE	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER ISO CODE
PackingMode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER PACKING MODE
	Applicable Codes
	BBK Break Bulk - BBK BCN Buyer's Consolidation - BCN FCL Full, single consignment - FCL GRP Groupage - GRP LCL Full, mixed consignment - LCL ROR Roll on/Roll off - ROR
EquipmentSizeDescription	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT SIZE DESCRIPTION
NumberOfUnits	Occurrence 0 .. 1 Type xs:decimal

Element/Attribute	Annotation
	General Notes NUMBER OF UNITS
Measurements	Occurrence 0 .. 1 Type MeasurementList General Notes EQUIPMENT MEASUREMENTS Examples <Measurements> <Measurement Type="Volume" Uom="MTQ"> <Measure>64.510</Measure> </Measurement> <Measurement Type="Weight" Uom="KGM"> <Measure>19315.200</Measure> </Measurement> </Measurements>
xs:sequence	Occurrence 1 .. 1
Measurement	Occurrence 0 .. unbounded Type Measurement Type xs:string Use required General Notes EQUIPMENT MEASUREMENT TYPE Applicable Codes TareWeight Volume Weight
Type	Type xs:string Use required General Notes EQUIPMENT MEASUREMENT TYPE
Uom	Type xs:string General Notes EQUIPMENT MEASUREMENT UNIT OF MEASURE Applicable Codes KGM Kilograms MTQ Cubic metres
xs:sequence	Occurrence 1 .. 1
Measure	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MEASUREMENT
Dimensions	Occurrence 0 .. 1 Type DimensionsList General Notes EQUIPMENT DIMENSIONS Examples <Dimensions> <Dimension Type="Container" Uom="MTR"> <Length>36.000</Length> <Width>28.000</Width> <Height>40.000</Height> </Dimension> </Dimensions>
xs:sequence	Occurrence 1 .. 1
Dimension	Occurrence 0 .. unbounded Type Dimension Type xs:string Use required General Notes EQUIPMENT DIMENSION TYPE Applicable Codes Container
Type	Type xs:string Use required General Notes EQUIPMENT DIMENSION TYPE
Uom	Type xs:string



Element/Attribute	Annotation
	General Notes EQUIPMENT DIMENSION UNIT OF MEASURE
	Applicable Codes
	MTR
xs:sequence	Occurrence 1 .. 1
Length	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION LENGTH
Width	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION WIDTH
Height	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION HEIGHT
SealIds	Occurrence 0 .. 1 Type SealList General Notes SEAL INFORMATION FOR SHIPPING CONTAINERS Examples <SealIds> <Seal> <SealId>XX-12345678</SealId> </Seal> </SealIds>
xs:sequence	Occurrence 1 .. 1
Seal	Occurrence 0 .. unbounded Type Seal
xs:sequence	Occurrence 1 .. 1
SealId	Occurrence 0 .. 1 Type xs:string General Notes SEAL NUMBER
SealParty	Occurrence 0 .. 1 Type xs:string General Notes SEALING PARTY
	Applicable Codes
	Shipper Shipper Sealing Party
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes EQUIPMENT REFERENCES Examples <References> <ReferenceGroup> <Reference Type="PackingMode">FCL</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="DeliveryMode">FCL</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation																								
	General Notes EQUIPMENT REFERENCE																								
<i>Type</i>	Type xs:string Use required General Notes EQUIPMENT REFERENCE TYPE																								
	Applicable Codes <table> <tr> <td>MasterBill</td><td>Master bill of lading number</td></tr> <tr> <td>OrderReference</td><td>Order Reference</td></tr> <tr> <td>PackageNumber</td><td>Package Number</td></tr> <tr> <td>PackingMode</td><td>Container Packing Mode</td></tr> <tr> <td>ProofOfDeliveryNumber</td><td>Proof of delivery reference number</td></tr> <tr> <td>RoadWaybill</td><td>Road Waybill number, SIS</td></tr> <tr> <td>ShipmentReference</td><td>Shipment reference number</td></tr> <tr> <td>ShipperReference</td><td>Shipper Reference</td></tr> <tr> <td>TransportInstructionNumber</td><td>Transport instruction number</td></tr> <tr> <td>VehicleId</td><td>Vehicle identification number (VIN)</td></tr> <tr> <td>VesselCountryOfRegistration</td><td>Vessel Country of Registration</td></tr> <tr> <td>VesselId</td><td>Vessel identifier</td></tr> </table>	MasterBill	Master bill of lading number	OrderReference	Order Reference	PackageNumber	Package Number	PackingMode	Container Packing Mode	ProofOfDeliveryNumber	Proof of delivery reference number	RoadWaybill	Road Waybill number, SIS	ShipmentReference	Shipment reference number	ShipperReference	Shipper Reference	TransportInstructionNumber	Transport instruction number	VehicleId	Vehicle identification number (VIN)	VesselCountryOfRegistration	Vessel Country of Registration	VesselId	Vessel identifier
MasterBill	Master bill of lading number																								
OrderReference	Order Reference																								
PackageNumber	Package Number																								
PackingMode	Container Packing Mode																								
ProofOfDeliveryNumber	Proof of delivery reference number																								
RoadWaybill	Road Waybill number, SIS																								
ShipmentReference	Shipment reference number																								
ShipperReference	Shipper Reference																								
TransportInstructionNumber	Transport instruction number																								
VehicleId	Vehicle identification number (VIN)																								
VesselCountryOfRegistration	Vessel Country of Registration																								
VesselId	Vessel identifier																								
<i>Identifier</i>	Type xs:string Use optional General Notes REFERENCE IDENTIFIER																								
<i>CustomFieldType</i>	Type xs:string Use optional General Notes CUSTOM FIELD TYPE Use to be agreed																								
Dates	Occurrence 0 .. 1 Type DateList General Notes CONTAINER DATES Examples <Dates> <Date Format="DateTimeSec" Type="EstimatedCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="RequestedCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledCollection"> <DateTime>20260818120500</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualCollection"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedDelivery"> <DateTime>20260802124800</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDelivery"> <DateTime>20260823090200</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedFullPickup"> <DateTime>20260830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLOnBoardVessel"> <DateTime>20260806013500</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLUnloadFromVessel"> <DateTime>20260815135900</DateTime> </Date>																								



Element/Attribute	Annotation
	Examples <Date Format="DateTimeSec" Type="FCLWharfGateIn"> <DateTime>20260801085600</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateOut"> <DateTime>20260818101000</DateTime> </Date> <Date Format="DateTimeSec" Type="ContainerParkEmptyPickupGateOut"> <DateTime>20260830121700</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
	Type Date
<i>Type</i>	Type xs:string
	Use required
	General Notes CONTAINER DATE TYPE
	Applicable Codes
	VerifiedDate
<i>Format</i>	Type xs:string
	Use required
	General Notes CONTAINER DATE FORMAT
	Applicable Codes
	DateTime YYYYMMDDHHMM
	DateTimeInterval YYYYMMDDHHMM- YYYYMMDDHHMM
	DateTimeSec YYYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes CONTAINER DATE/TIME
TransportMovements	Occurrence 0 .. 1
	Type TransportMovementList
	General Notes EQUIPMENT TRANSPORT MOVEMENTS
	Examples <TransportMovements> <TransportMovement Type="DeliveryMode"> <Code>CFS</Code> <Description>DSC</Description> </TransportMovement> </TransportMovements>
xs:sequence	Occurrence 1 .. 1
TransportMovement	Occurrence 0 .. unbounded
	Type CodeDescription
<i>Type</i>	Type xs:string
	Use optional
	General Notes EQUIPMENT TRANSPORT MOVEMENTS TYPE
	Applicable Codes
	DeliveryMode
xs:sequence	Occurrence 1 .. 1
Code	Occurrence 0 .. 1
	Type xs:string



Element/Attribute	Annotation
	General Notes EQUIPMENT MOVEMENT CODE Applicable Codes CFS/CFS CFS/CY CFS/DR CY/CFS CY/CY CY/DR DR/CFS DR/CY DR/DR FCL/FCL FCL/LCL LCL/FCL LCL/LCL RO/RO
Description	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MOVEMENT DESCRIPTION
TemperatureControl	Occurrence 0 .. 1 Type TemperatureControl General Notes CONTAINER TEMPERATURE Examples <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> <HumidityPercentage>25</HumidityPercentage> </TemperatureControl>
Type	Type xs:string Use required General Notes TEMPERATURE CONTROL TYPE Applicable Codes Container
Uom	Type xs:string General Notes TEMPERATURE UNIT OF MEASURE Applicable Codes CEL Celsius FAH Fahrenheit
xs:sequence	Occurrence 1 .. 1
Fixed	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE
HumidityPercentage	Occurrence 0 .. 1 Type xs:string General Notes HUMIDITY PERCENTAGE
RangeDetails	Occurrence 0 .. 1 Type RangeDetails General Notes RANGE DETAILS Examples <RangeDetails Type="Container" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>

Element/Attribute	Annotation
<i>Type</i>	Type xs:string Use required General Notes RANGE DETAILS TYPE
	Applicable Codes Container
<i>Uom</i>	Type xs:string General Notes TEMPERATURE UNIT OF MEASURE
	Applicable Codes CEL Celsius FAH Fahrenheit
<i>xs:sequence</i>	Occurrence 1 .. 1
Minimum	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE MINIMUM
Maximum	Occurrence 0 .. 1 Type xs:string General Notes TEMPERATURE MAXIMUM
FreeTextData	Occurrence 0 .. 1 Type FreeTextList General Notes INVOICE LINE FREE TEXT DATA Examples <FreeTextData> <FreeText Type="GoodsDescription" > <TextLine1>ENGINE UNDERDECK</TextLine1> </FreeText> <FreeText Type="ServiceCharacteristic" > <TextLine1>BCN</TextLine1> </FreeText> <FreeText Type="OtherServiceInformation" > <TextLine1>OSI1</TextLine1> <TextLine2>OSI2</TextLine2> <TextLine3>OS3</TextLine3> <TextLine4>OS4</TextLine4> <TextLine5>OS5</TextLine5> </FreeText> </FreeTextData>
<i>xs:sequence</i>	Occurrence 1 .. 1
FreeText	Occurrence 0 .. unbounded Type FreeText
<i>Type</i>	Type xs:string Use required General Notes FREE TEXT TYPE
	Applicable Codes GeneralInformation General information GoodsDescription Goods Description NatureOfCargo Nature Of Cargo OtherServiceInformation Other Service Information ServiceCharacteristic Service Characteristic
<i>xs:sequence</i>	Occurrence 1 .. 1
DescriptionCode	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT DESCRIPTION CODE
TextLine1	Occurrence 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation						
	General Notes FREE TEXT LINE 1						
TextLine2	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 2						
TextLine3	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 3						
TextLine4	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 4						
TextLine5	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 5						
MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountList General Notes INVOICE LINE MONETARY AMOUNTS Examples <MonetaryAmounts> <MonetaryAmount Type="InsuranceAmount"> <Amount>500.05</Amount> <Currency>EUR</Currency> </MonetaryAmount> <MonetaryAmount Type="InsuranceValue"> <Amount>1313.13</Amount> <Currency>USD</Currency> </MonetaryAmount> <MonetaryAmount Type="LineTaxAmount"> <Amount>0.00</Amount> <Currency>USD</Currency> </MonetaryAmount> <MonetaryAmount Type="LineAmountInclTax"> <Amount>-54.0000</Amount> <Currency>USD</Currency> </MonetaryAmount> <MonetaryAmount Type="LineAmountExclTax"> <Amount>-54.00</Amount> <Currency>USD</Currency> </MonetaryAmount> </MonetaryAmounts>						
xs:sequence	Occurrence 1 .. 1						
MonetaryAmount	Occurrence 0 .. unbounded Type MonetaryAmount General Notes MONETARY AMOUNT						
Type	Type xs:string Use required General Notes MONETARY AMOUNT TYPE Applicable Codes <table> <tr> <td>LineAmountExclTax</td><td>LineAmountExclTax</td></tr> <tr> <td>LineAmountInclTax</td><td>LineAmountInclTax</td></tr> <tr> <td>LineTaxAmount</td><td>LineTaxAmount</td></tr> </table>	LineAmountExclTax	LineAmountExclTax	LineAmountInclTax	LineAmountInclTax	LineTaxAmount	LineTaxAmount
LineAmountExclTax	LineAmountExclTax						
LineAmountInclTax	LineAmountInclTax						
LineTaxAmount	LineTaxAmount						
xs:sequence	Occurrence 1 .. 1						
Amount	Occurrence 0 .. 1 Type xs:string						



Element/Attribute	Annotation
	General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1 Type xs:string General Notes MONETARY CURRENCY TYPE
	Applicable Codes
	HomeCurrency HomeCurrency
	InvoicingCurrency Invoicing Currency
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes INVOICE LINE REFERENCES Examples <References> <ReferenceGroup> <Reference Type="Shipper Reference">DEF00531</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">ABC00281</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="RoadWaybill">1234567890</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup General Notes REFERENCE GROUP
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes INVOICE LINE REFERENCE
Type	Type xs:string Use required General Notes INVOICE LINE REFERENCE TYPE
	Applicable Codes
	AgentsReference Agent's reference
	AirWayBill Air waybill number
	CargoManifestNo Cargo manifest number, Transport Id
	ConsigneeOrderNumber Consignee's order number
	ConsigneeReference Consignee Reference
	ConsignmentId Consignment id, carrier assigned
	CustomField Custom Field
	CustomerReferenceNumber Customer reference number
	DeliveryAgreement Delivery Agreement
	DocumentReference Document Reference
	ExternalReference External reference customer reference number
	GINCNumber Waybill number, GINC
	HouseBill House bill of lading number
	MasterBill Master bill of lading number
	OrderReference Order Reference
	PackageNumber Package Number

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation
	Applicable Codes ProofOfDeliveryNumber Proof of delivery reference number RoadWaybill Road Waybill number, SIS ShipmentReference Shipment reference number ShipperReference Shipper Reference TransportInstructionNumber Transport instruction number VehicleId Vehicle identification number (VIN) VesselCountryOfRegistration Vessel Country of Registration VesselId Vessel identifier
<i>CustomFieldType</i>	Type xs:string Use optional General Notes CUSTOM FIELD TYPE Use to be agreed
Date	Occurrence 0 .. 1 Type Date General Notes INVOICE REFERENCE DATE
<i>Type</i>	Type xs:string Use required General Notes INVOICE REFERENCE DATE TYPE
<i>Format</i>	Applicable Codes ReferenceDate Reference Date Type xs:string Use required General Notes INVOICE REFERENCE DATE FORMAT
<i>xs:sequence</i>	Applicable Codes DateTime CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS
DateTime	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes INVOICE REFERENCE DATE/TIME
Packages	Occurrence 0 .. 1 Type PackageGroupList General Notes INVOICE LINE PACKAGE DETAILS Examples <Packages> <PackageGroup> <Package> <PackageQuantity>1</PackageQuantity> <PackageCode>PLL</PackageCode> </Package> <PackageId> <InstructionCode>PackageMarks</InstructionCode> <Marks> <ShippingMark>Line16416416416416416</ShippingMark> </Marks> </PackageId> </PackageGroup> </Packages>
<i>xs:sequence</i>	Occurrence 1 .. 1
PackageGroup	Occurrence 0 .. unbounded Type PackageGroup General Notes PACKAGE GROUP

Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
Package	Occurrence 0 .. 1 Type Package General Notes PACKAGE
xs:sequence	Occurrence 1 .. 1
PackageQuantity	Occurrence 1 .. 1 Type xs:string General Notes PACKAGE QUANTITY
PackageCode	Occurrence 0 .. 1 Type xs:string General Notes PACKAGE CODE
Packageld	Occurrence 0 .. 1 Type Packageld General Notes PACKAGE ID
xs:sequence	Occurrence 1 .. 1
InstructionCode	Occurrence 1 .. 1 Type xs:string General Notes PACKAGE INSTRUCTION TYPE
Marks	Applicable Codes PackageMarks Package Marks and Numbers Occurrence 0 .. 1 Type Marks General Notes MARKS
xs:sequence	Occurrence 1 .. 1
ShippingMark	Occurrence 1 .. unbounded Type xs:string General Notes PACKAGE SHIPPING MARK
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes INVOICE LINE LOCATIONS Examples <Locations> <LocationGroup> <Location Type="PlaceOfLoading" > <LocationIdentification Type="IATA" > <LocationIdentifier>LineCAMTR</LocationIdentifier> <LocationName>LineMontreal</LocationName> </LocationIdentification> <LocationIdentification Type="IATA" > <LocationIdentifier>LineCAMTR</LocationIdentifier> <LocationName>LineMontreal</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="PlaceOfUnloading" > <LocationIdentification> <LocationIdentifier>LineGBSOU</LocationIdentifier> <LocationName>LineSouthampton</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations>

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV XML INVOICE OUT; v2.0

Issue date: 2026-08-24

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 55 / 76

Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup General Notes LOCATION GROUP
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type Location General Notes INVOICE LINE LOCATION
Type	Type xs:string Use required General Notes LOCATION TYPE
	Applicable Codes
	Departure Place of Departure
	Destination Place of Destination
	PlaceOfLoading Place of Loading
	PlaceOfUnloading Place of Unloading
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification General Notes LOCATION IDENTIFICATION
Type	Type xs:string General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes
	GS1 GS1
	IATA IATA
	UN UN
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1 Type xs:string General Notes LOCATION NAME
Dates	Occurrence 0 .. 1 Type DateList General Notes INVOICE LINE DATES
	Examples
	<Dates>
	<Date Format="DateTimeSec" Type="EstimatedCollection">
	<DateTime>20260802160000</DateTime>
	</Date>
	<Date Format="DateTimeSec" Type="ActualCollection">
	<DateTime>20260803080000</DateTime>
	</Date>
	</Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type Date General Notes DATE
Type	Type xs:string Use required



Element/Attribute	Annotation
	General Notes INVOICE LINE DATE TYPE
	Applicable Codes
	ActualArrival Transport means arrival date time, actual
	ActualCollection Collection date/time, latest
	ActualDelivery Delivery date/time, actual
	ActualDeparture Transport means departure date/ time, actual
	CargoPickup Cargo pick-up date / time
	Collection Collection date/time, earliest
	ConsignmentLoading Consignment loading date time
	DeliveryRequested Delivery Requested
	EstimatedDelivery Delivery date/time, estimated
	ScheduledArrival Scheduled Arrival
	ScheduledDelivery Delivery date/time, 1st schedule
	ScheduledDeparture Scheduled Departure
	ScheduledShipmentArrival Completion date or time, scheduled
	ScheduledShipmentDeparture Start date or time, scheduled
	ShipmentReqDate Shipment requested date/time
<i>Format</i>	Type xs:string
	Use required
	General Notes INVOICE LINE DATE FORMAT
	Applicable Codes
	Date YYYYMMDD
	DateTime YYYYMMDDHHMM
	DateTimeInterval YYYYMMDDHHMM- YYYYMMDDHHMM
	DateTimeSec YYYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes INVOICE LINE DATE / TIME
Parties	Occurrence 0 .. 1
	Type PartiesList
	General Notes INVOICE LINE PARTIES
	Examples
	<Parties>
	<Party>
	<PartyDetails Role="Consignor" >
	<Id>1234567890</Id>
	<PartyName>Consignor</PartyName>
	<AddressLine1>Street</AddressLine1>
	<CityName>City</CityName>
	<PostCode>123 45</PostCode>
	<CountryCode>SE</CountryCode>
	</PartyDetails>
	</Party>
	<Party>
	<PartyDetails Role="Despatch" >
	<Id>1234567890</Id>
	<PartyName>Consignor</PartyName>
	<AddressLine1>Street</AddressLine1>
	<CityName>City</CityName>
	<PostCode>123 45</PostCode>
	<CountryCode>SE</CountryCode>
	</PartyDetails>
	</Party>



Element/Attribute	Annotation
	Examples <Party> <PartyDetails Role="Consignee" > <Id>9876543210</Id> <PartyName>Consignee</PartyName> <AddressLine1>Street 1</AddressLine1> <AddressLine2>Street 2</AddressLine2> <CityName>City</CityName> <PostCode>678 90</PostCode> <CountryCode>AE</CountryCode> </PartyDetails> </Party> </Parties>
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded
	Type Party
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1
	Type PartyDetails
	General Notes INVOICE LINE PARTY DETAILS
	General Notes INVOICE LINE PARTY DETAILS
Role	Type xs:string
	Use required
	General Notes PARTY ROLE
	Applicable Codes
	Carrier Carrier Party
	Consignee Consignee Party
	Consignor Consignor Party
	Consolidator Consolidator
	Deconsolidator Deconsolidator
	Delivery Delivery Party
	DeliveryAgent Delivery Agent
	DeliveryLocalCartage Delivery Local Cartage
	Despatch Despatch Party
	Forwarder Forwarder
	FreightForwarder Freight Forwarder
	FreightPayer Freight/charges Payer
	Notify Notify Party
	OrderingCustomer Ordering Customer
	PickupAgent Pickup Agent
	PickupLocalCartage Pickup Local Cartage
	ShipFrom Ship From
	ShipTo Ship To
	Supplier Supplier
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY IDENTIFIER
Assignor	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY IDENTIFIER ASSIGNOR
PartyName	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY NAME



Element/Attribute	Annotation
AddressLine1	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS CITY NAME
State	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS STATE / PROVINCE
PostCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS ISO COUNTRY CODE
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes INVOICE PARTY LOCATIONS Examples <pre> <Locations> <LocationGroup> <Location Type="PhysicalLocation"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen V</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type Location
Type	Type xs:string Use required General Notes INVOICE PARTY LOCATIONTYPE Applicable Codes PhysicalLocation Place of Physical Location
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
Type	Type xs:string General Notes INVOICE PARTY LOCATIONTYPE

Element/Attribute	Annotation
	Applicable Codes UN UN Location Code
xs:sequence	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes INVOICE PARTY LOCATION IDENTIFIER
LocationIdentifier	
LocationName	Occurrence 0 .. 1 Type xs:string General Notes INVOICE PARTY LOCATION NAME
Contact	Occurrence 0 .. unbounded Type Contact General Notes PARTY CONTACT DETAILS Examples <Contact Type="InformationContact"> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
Type	Type xs:string Use required General Notes PARTY CONTACT TYPE
	Applicable Codes AccountsReceivableContact Accounts Receivable Contact InformationContact Information Contact
xs:sequence	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT ID
ContactId	
Name	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT PHONE NUMBER
Mobile	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT MOBILE NUMBER
Fax	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT FAX NUMBER
Email	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT E-MAIL ADDRESS
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes PARTY REFERENCES Examples <References> <ReferenceGroup>

Element/Attribute	Annotation
	Examples <Reference Type="VAT Registration number">VAT Registration number</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes REFERENCE
Type	Type xs:string Use required General Notes REFERENCE TYPE Predefined Types listed, additional reference types to be agreed
Identifier	Applicable Codes VAT VAT Registration number Type xs:string Use optional General Notes REFERENCE IDENTIFIER
CustomFieldType	Type xs:string Use optional General Notes REFERENCE CUSTOM FIELD TYPE Use to be agreed
Date	Occurrence 0 .. 1 Type Date General Notes INVOICE REFERENCE DATE
Type	Type xs:string Use required General Notes INVOICE REFERENCE DATE TYPE
Format	Applicable Codes ReferenceDate Reference Date Type xs:string Use required General Notes INVOICE REFERENCE DATE FORMAT
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string General Notes INVOICE REFERENCE DATE/TIME Applicable Codes DateTime CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS
AllowancesorCharges	Occurrence 0 .. 1 Type AllowancesorChargesGroupList General Notes INVOICE LINE ALLOWANCES AND CHARGES Examples <AllowancesorCharges> <AllowanceOrChargeGroup>

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation
	Examples <AllowanceOrCharge AllowanceOrChargeCode="C"> <AllowanceOrChargeIdentifier>FRT</ AllowanceOrChargeIdentifier> <SpecialServiceDescriptionCode>0001</ SpecialServiceDescriptionCode> <SpecialServiceDescription>Freight</ SpecialServiceDescription> </AllowanceOrCharge> <MonetaryAmounts> <MonetaryAmountGroup> <MonetaryAmount Type="TotalAmount"> <Amount>11896.2000</Amount> <Currency>DKK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="TaxableAmount"> <Amount>11896.2000</Amount> <Currency>DKK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> </MonetaryAmounts> </AllowanceOrCharge>
xs:sequence	Occurrence 1 .. 1
AllowanceOrChargeGroup	Occurrence 0 .. unbounded Type AllowanceOrChargeGroup
xs:sequence	Occurrence 1 .. 1
AllowanceOrCharge	Occurrence 0 .. 1 Type AllowanceOrCharge
	General Notes ALLOWANCE OR CHARGE DETAILS



Element/Attribute	Annotation
	Examples <AllowanceOrChargeGroup> <AllowanceOrCharge AllowanceOrChargeCode="C"> <AllowanceOrChargeIdentifier>FRT</ AllowanceOrChargeIdentifier> <SpecialServiceDescriptionCode>0001</ SpecialServiceDescriptionCode> <SpecialServiceDescription>Freight</ SpecialServiceDescription> </AllowanceOrCharge> </AllowanceOrChargeGroup>
— AllowanceOrChargeCode	Type xs:string Use required Applicable Codes A Allowance C Charge
— xs:sequence	Occurrence 1 .. 1
— AllowanceOrChargeIdentifier	Occurrence 0 .. 1 Type xs:string General Notes ALLOWANCE OR CHARGE IDENTIFIER
— SpecialServiceDescriptionCode	Occurrence 0 .. 1 Type xs:string General Notes SPECIAL SERVICE DESCRIPTION CODE
— SpecialServiceDescription	Occurrence 0 .. 1 Type xs:string General Notes SPECIAL SERVICE DESCRIPTION
— MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountGroupList General Notes ALLOWANCE OR CHARGE MONETARY AMOUNTS Examples <MonetaryAmountGroup> <MonetaryAmount Type="TotalAmount"> <Amount>11896.2000</Amount> <Currency>DKK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="TaxableAmount"> <Amount>11896.2000</Amount> <Currency>DKK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies>



Element/Attribute	Annotation
	Examples
	<pre> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="TotalDutyTaxFeeAmount"> <Amount>0.0000</Amount> <Currency>DKK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="AllowanceorChargeAmountInclTax"> <Amount>1746.0000</Amount> <Currency>USD</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount </pre>

Element/Attribute	Annotation
	Examples Type="AllowanceorChargeAmountExclTax"> <Amount>1746.0000</Amount> <Currency>USD</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="TaxAmount"> <Amount>0.0000</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</
	CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyCode>USD</CurrencyCode> <CurrencyRate>1.0000</CurrencyRate> </Currency> </CurrencyDetails> <CurrencyDetails> <Currency> <CurrencyCode>DKK</CurrencyCode> <CurrencyRate>6.8134</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> </MonetaryAmounts>
xs:sequence	Occurrence 1 .. 1
MonetaryAmountGroup	Occurrence 0 .. unbounded
	Type MonetaryAmountGroup
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. 1
	Type MonetaryAmount
	General Notes MONETARY AMOUNT DETAILS
Type	Type xs:string
	Use required
	General Notes MONETARY AMOUNT TYPE
Applicable Codes	
AllowanceorChargeAmountExclTax	AllowanceorChargeAmountExclTax
AllowanceorChargeAmountInclTax	AllowanceorChargeAmountInclTax
TaxAmount	TaxAmount
TaxableAmount	TaxableAmount

Element/Attribute	Annotation
	Applicable Codes
	TotalAmount TotalAmount
	TotalDutyTaxFeeAmount TotalDutyTaxFeeAmount
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT CURRENCY TYPE
	Applicable Codes
	HomeCurrency Home Currency
	InvoicingCurrency Invoicing Currency
Currencies	Occurrence 0 .. 1
	Type CurrencyGroupList
	General Notes MONETARY AMOUNT CURRENCY DETAILS
	Examples
	<Currencies>
	<CurrencyDetails>
	<Currency>
	<CurrencyCode>USD</CurrencyCode>
	<CurrencyRate>1.0000</CurrencyRate>
	</Currency>
	</CurrencyDetails>
	<CurrencyDetails>
	<Currency>
	<CurrencyCode>DKK</CurrencyCode>
	<CurrencyRate>6.8134</CurrencyRate>
	</Currency>
	</CurrencyDetails>
	</Currencies>
xs:sequence	Occurrence 1 .. 1
CurrencyDetails	Occurrence 0 .. unbounded
	Type CurrencyGroup
xs:sequence	Occurrence 1 .. 1
Currency	Occurrence 0 .. 1
	Type Currency
	General Notes CURRENCY DETAILS
xs:sequence	Occurrence 1 .. 1
CurrencyCode	Occurrence 0 .. 1
	Type xs:string
	General Notes CURRENCY CODE
	Applicable Codes
	HomeCurrency Home Currency
	Invoicing Currency Invoicing Currency
	Payment Currency Payment Currency
	PricingCurrency Pricing Currency
CurrencyRate	Occurrence 0 .. 1
	Type xs:string
	General Notes CURRENCY RATE

Element/Attribute	Annotation		
Taxes	Occurrence 0 .. 1 Type TaxGroupList General Notes ALLOWANCE OR CHARGE TAX DETAILS Examples <Taxes> <TaxDetails> <Tax Type="TaxAmount"> <TaxAmount>0.0000</TaxAmount> <TaxRate>TaxRate</TaxRate> <TaxCode>FREEMOM</TaxCode> <TaxCategory>VAT</TaxCategory> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmountHomeCurrency"> <Amount>0.0000</Amount> <Currency>USD</Currency> <CurrencyType>TaxAmountHomeCurrency</ CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> <TaxDetails> <Tax Type="TaxAmount"> <TaxAmount>0.0000</TaxAmount> <TaxRate>TaxRate</TaxRate> <TaxCode>FREEMOM</TaxCode> <TaxCategory>VAT</TaxCategory> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmountInvoiceCurrency"> <Amount>0.0000</Amount> <Currency>DKK</Currency> <CurrencyType>TaxAmountInvoiceCurrency</ CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> </Taxes> <Rate Type="ExchangeRate">6.8134</Rate>		
xs:sequence	Occurrence 1 .. 1		
TaxDetails	Occurrence 0 .. unbounded Type TaxGroup General Notes TAX DETAILS		
xs:sequence	Occurrence 1 .. 1		
Tax	Occurrence 0 .. 1 Type Tax General Notes TAX DETAILS		
<i>Type</i>	Type xs:string Use required General Notes TAX TYPE Applicable Codes <table> <tr> <td>TaxAmount</td><td>TaxAmount</td></tr> </table>	TaxAmount	TaxAmount
TaxAmount	TaxAmount		
xs:sequence	Occurrence 1 .. 1		
TaxAmount	Occurrence 0 .. 1 Type xs:string		

Element/Attribute	Annotation
	General Notes TAX AMOUNT
TaxRate	Occurrence 0 .. 1 Type xs:string General Notes TAX RATE
TaxCode	Occurrence 0 .. 1 Type xs:string General Notes TAX CODE
TaxCategory	Applicable Codes ValueAddedTax ValueAddedTax Occurrence 0 .. 1 Type xs:string General Notes TAX CATEGORY Applicable Codes ExemptTax Exempt from tax MixedTaxRate Mixed tax rate StandardRate Standard rate VATReverseCharge VAT Reverse Charge ZeroRatedGoods Zero rated goods
MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountList General Notes ALLOWANCE OR CHARGE TAX MONETARY AMOUNTS
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded Type MonetaryAmount
Type	Type xs:string Use required General Notes TAX MONETARY AMOUNT TYPE Applicable Codes TaxAmountHomeCurrency TaxAmountHomeCurrency TaxAmountInvoiceCurrency TaxAmountInvoiceCurrency
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1 Type xs:string General Notes TAX MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type xs:string General Notes TAX MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1 Type xs:string General Notes TAX MONETARY AMOUNT CURRENCY TYPE Applicable Codes HomeCurrency Home Currency Invoicing Currency Invoicing Currency
Rate	Occurrence 0 .. 1 Type Rate General Notes RATE
Type	Type xs:string Use optional General Notes RATE TYPE Applicable Codes ExchangeRate ExchangeRate

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation												
TransportStages	Occurrence 0 .. 1 Type TransportStageList General Notes INVOICE LINE TRANSPORT STAGES												
xs:sequence	Occurrence 1 .. 1												
TransportStage	Occurrence 0 .. unbounded Type TransportStage												
xs:sequence	Occurrence 1 .. 1												
Stage	Occurrence 0 .. 1 Type Stage General Notes TRANSPORTATION STAGE Examples <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> <TransportId>017W</TransportId> <CarrierId>12345678</CarrierId> <CarrierName>Carrier line</CarrierName> <TransportType>Main</TransportType> <TransportMeansName>Vesselname</TransportMeansName> <TransportMeansNationality>DK</TransportMeansNationality> </Stage>												
Type	Type xs:string Use required General Notes TRANSPORTATION STAGE TYPE Applicable Codes <table> <tr> <td>MainCarriage</td><td>Main Carriage</td></tr> <tr> <td>PlannedLeg1</td><td>Main carriage - first carrier</td></tr> <tr> <td>PlannedLeg2</td><td>Main carriage - second carrier</td></tr> <tr> <td>PlannedLeg3</td><td>Main carriage - third carrier</td></tr> <tr> <td>PlannedLeg4</td><td>Main carriage - fourth carrier</td></tr> <tr> <td>PlannedLeg5</td><td>Main carriage - fifth carrier</td></tr> </table>	MainCarriage	Main Carriage	PlannedLeg1	Main carriage - first carrier	PlannedLeg2	Main carriage - second carrier	PlannedLeg3	Main carriage - third carrier	PlannedLeg4	Main carriage - fourth carrier	PlannedLeg5	Main carriage - fifth carrier
MainCarriage	Main Carriage												
PlannedLeg1	Main carriage - first carrier												
PlannedLeg2	Main carriage - second carrier												
PlannedLeg3	Main carriage - third carrier												
PlannedLeg4	Main carriage - fourth carrier												
PlannedLeg5	Main carriage - fifth carrier												
xs:sequence	Occurrence 1 .. 1												
ModeOfTransport	Occurrence 0 .. 1 Type xs:string General Notes MODE OF TRANSPORTATION Applicable Codes <table> <tr> <td>Air</td><td>Air transportation</td></tr> <tr> <td>Road</td><td>Road transportation</td></tr> <tr> <td>Sea</td><td>Sea transportation</td></tr> </table>	Air	Air transportation	Road	Road transportation	Sea	Sea transportation						
Air	Air transportation												
Road	Road transportation												
Sea	Sea transportation												
TransportId	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT IDENTIFICATION												
CarrierId	Occurrence 0 .. 1 Type xs:string General Notes CARRIER IDENTIFICATION Air & Sea: DSV carrier identifier Road: Not used												
CarrierName	Occurrence 0 .. 1 Type xs:string General Notes CARRIER NAME Road: Not used												
TransportType	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT TYPE												



Element/Attribute	Annotation																				
	Road: Not used																				
TransportMeansName	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NAME Sea: Vessel Name Air & Road: Not used																				
TransportMeansNationality	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NATIONALITY Sea: Vessel Nationality Air & Road: Not used																				
Dates	Occurrence 0 .. 1 Type DateList General Notes TRANSPORTATION DATES Examples <Dates> <Date Format="DateTimeSec" Type="ScheduledDeparture"> <DateTime>20260721093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentDeparture"> <DateTime>20260721093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledArrival"> <DateTime>20260719000100</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentArrival"> <DateTime>20260719000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDeparture"> <DateTime>20260721093500</DateTime> </Date> </Dates>																				
xs:sequence	Occurrence 1 .. 1																				
Date	Occurrence 0 .. unbounded Type Date																				
Type	Type xs:string Use required General Notes TRANSPORTATION DATE TYPE Applicable Codes <table> <tr> <td>ActualArrival</td><td>Actual Time of Arrival</td></tr> <tr> <td>ActualDelivery</td><td>Actual Delivery date/time</td></tr> <tr> <td>ActualDeparture</td><td>Actual Time of Departure</td></tr> <tr> <td>EstimatedArrival</td><td>Estimated Time of Arrival</td></tr> <tr> <td>EstimatedDelivery</td><td>Delivery date/time, estimated</td></tr> <tr> <td>EstimatedDeparture</td><td>Estimated Time of Departure</td></tr> <tr> <td>ScheduledArrival</td><td>Scheduled Time of Arrival</td></tr> <tr> <td>ScheduledDeparture</td><td>Scheduled Time of Departure</td></tr> <tr> <td>ScheduledShipmentArrival</td><td>Scheduled Shipment Time of Arrival</td></tr> <tr> <td>ScheduledShipmentDeparture</td><td>Scheduled Shipment Time of Departure</td></tr> </table>	ActualArrival	Actual Time of Arrival	ActualDelivery	Actual Delivery date/time	ActualDeparture	Actual Time of Departure	EstimatedArrival	Estimated Time of Arrival	EstimatedDelivery	Delivery date/time, estimated	EstimatedDeparture	Estimated Time of Departure	ScheduledArrival	Scheduled Time of Arrival	ScheduledDeparture	Scheduled Time of Departure	ScheduledShipmentArrival	Scheduled Shipment Time of Arrival	ScheduledShipmentDeparture	Scheduled Shipment Time of Departure
ActualArrival	Actual Time of Arrival																				
ActualDelivery	Actual Delivery date/time																				
ActualDeparture	Actual Time of Departure																				
EstimatedArrival	Estimated Time of Arrival																				
EstimatedDelivery	Delivery date/time, estimated																				
EstimatedDeparture	Estimated Time of Departure																				
ScheduledArrival	Scheduled Time of Arrival																				
ScheduledDeparture	Scheduled Time of Departure																				
ScheduledShipmentArrival	Scheduled Shipment Time of Arrival																				
ScheduledShipmentDeparture	Scheduled Shipment Time of Departure																				
Format	Type xs:string Use required General Notes TRANSPORTATION DATE FORMAT Applicable Codes <table> <tr> <td>DateTime</td><td>CCYYMMDDHHMM</td></tr> </table>	DateTime	CCYYMMDDHHMM																		
DateTime	CCYYMMDDHHMM																				



Element/Attribute	Annotation
	Applicable Codes
	DateTimeInterval CCYYMMDDHHMM-CCYYMMDDHHMM
	DateTimeSec CCYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes TRANSPORTATION DATE/TIME
Locations	Occurrence 0 .. 1
	Type LocationGroupList
	General Notes TRANSPORTATION STAGE LOCATIONS
	Examples
	<pre> <Locations> <LocationGroup> <Location Type="Loading"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DE</LocationIdentifier> <LocationName>Germany</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>DEHAM</LocationIdentifier> <LocationName>Hamburg</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>US</LocationIdentifier> <LocationName>United States</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>USCPT</LocationIdentifier> <LocationName>Carpinteria</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Unloading"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>US</LocationIdentifier> <LocationName>United States</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>USHOU</LocationIdentifier> <LocationName>Houston</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DK</LocationIdentifier> <LocationName>Denmark</LocationName> </LocationIdentification> <LocationIdentification Type="UN"> <LocationIdentifier>DKGLS</LocationIdentifier> <LocationName>Glostrup</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation
	Examples </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type Location
<i>Type</i>	Type xs:string
	Use required
	General Notes TRANSPORTATION LOCATION TYPE
	Applicable Codes
	Departure Place of Departure
	Destination Place of Destination
	PlaceOfLoading Place of Loading
	PlaceOfUnloading Place of Unloading
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
<i>Type</i>	Type xs:string
	General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes
	GS1 GS1
	IATA IATA
	UN UN
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION NAME
TermsOfDelivery	Occurrence 0 .. 1
	Type TermsGroup
	General Notes INVOICE TERMS OF DELIVERY
	Examples <TermsOfDelivery> <Terms> <TermCode>CIP</TermCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>
xs:sequence	Occurrence 1 .. 1
Terms	Occurrence 0 .. 1
	Type Terms
	General Notes INVOICE TERMS OF DELIVERY

Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
TermsCode	Occurrence 0 .. 1 Type xs:string General Notes TERM CODE
Codeld	Occurrence 0 .. 1 Type xs:string General Notes TYPE OF TERM CODE
Applicable Codes	
CombiTerms	Combi Terms
IncoTerms	INCO Terms
Location	Occurrence 0 .. unbounded Type Location General Notes TERMS OF DELIVERY LOCATION
Type	Type xs:string Use required General Notes TERM LOCATION TYPE
Applicable Codes	
NamedPlace	Named Place
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
Type	Type xs:string General Notes LOCATION IDENTIFIER TYPE
Applicable Codes	
GS1	GS1
IATA	IATA
UN	UN
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1 Type xs:string General Notes LOCATION NAME
MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountList General Notes INVOICE MONETARY AMOUNTS
Examples	
<pre> <MonetaryAmounts> <MonetaryAmount Type="TotalAmount" > <Amount>6790.38</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalAmount" > <Amount>5552.18</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxableAmount" > <Amount>6790.38</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> </pre>	

Element/Attribute	Annotation						
	Examples <MonetaryAmount Type="TaxableAmount" > <Amount>5552.18</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts>						
xs:sequence	Occurrence 1 .. 1						
MonetaryAmount	Occurrence 0 .. unbounded Type MonetaryAmount General Notes MONETARY AMOUNT						
Type	Type xs:string Use required General Notes MONETARY AMOUNT TYPE						
	Applicable Codes <table> <tr> <td>TaxableAmount</td><td>TaxableAmount</td></tr> <tr> <td>TotalAmount</td><td>TotalAmount</td></tr> <tr> <td>TotalDutyTaxFeeAmount</td><td>TotalDutyTaxFeeAmount</td></tr> </table>	TaxableAmount	TaxableAmount	TotalAmount	TotalAmount	TotalDutyTaxFeeAmount	TotalDutyTaxFeeAmount
TaxableAmount	TaxableAmount						
TotalAmount	TotalAmount						
TotalDutyTaxFeeAmount	TotalDutyTaxFeeAmount						
xs:sequence	Occurrence 1 .. 1						
Amount	Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT						
Currency	Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT CURRENCY						
CurrencyType	Occurrence 0 .. 1 Type xs:string General Notes MONETARY CURRENCY TYPE						
	Applicable Codes <table> <tr> <td>HomeCurrency</td><td>HomeCurrency</td></tr> <tr> <td>InvoicingCurrency</td><td>Invoicing Currency</td></tr> </table>	HomeCurrency	HomeCurrency	InvoicingCurrency	Invoicing Currency		
HomeCurrency	HomeCurrency						
InvoicingCurrency	Invoicing Currency						
Taxes	Occurrence 0 .. 1 Type TaxGroupList General Notes INVOICE TAX DETAILS						
xs:sequence	Occurrence 1 .. 1						
TaxDetails	Occurrence 0 .. unbounded Type TaxGroup Examples <Taxes> <TaxDetails> <Tax Type="TotalTaxInvoiceCurrency"> <TaxAmount>0.00</TaxAmount> <TaxCode>ValueAddedTax</TaxCode> </Tax> </Taxes>						

Element/Attribute	Annotation
	Examples </TaxDetails> <TaxDetails> <Tax Type="TotalTaxHomeCurrency"> <TaxAmount>0.0000</TaxAmount> <TaxCode>ValueAddedTax</TaxCode> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmountInvoiceCurrency"> <Amount>0.0000</Amount> <Currency>DKK</Currency> <CurrencyType>TaxAmountInvoiceCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> </Taxes>
xs:sequence	Occurrence 1 .. 1
Tax	Occurrence 0 .. 1
Type	Type Tax
	Type xs:string
	Use required
	General Notes TAX TYPE
	Applicable Codes
	TotalTaxHomeCurrency TotalTaxHomeCurrency
	TotalTaxInvoiceCurrency TotalTaxInvoiceCurrency
xs:sequence	Occurrence 1 .. 1
TaxAmount	Occurrence 0 .. 1
	Type xs:string
	General Notes TAX AMOUNT
TaxCode	Occurrence 0 .. 1
	Type xs:string
	General Notes TAX CODE
	Applicable Codes
	ValueAddedTax ValueAddedTax
MonetaryAmounts	Occurrence 0 .. 1
	Type MonetaryAmountList
	General Notes INVOICE TAX MONETARY AMOUNTS
	Examples <MonetaryAmounts> <MonetaryAmount Type="TaxAmountInvoiceCurrency"> <Amount>0.0000</Amount> <Currency>DKK</Currency> <CurrencyType>TaxAmountInvoiceCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts>
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded
	Type MonetaryAmount
Type	Type xs:string
	Use required
	General Notes MONETARY AMOUNT TYPE



Element/Attribute	Annotation
	Applicable Codes
	TaxAmountHomeCurrency TaxAmountHomeCurrency
	TaxAmountInvoiceCurrency TaxAmountInvoiceCurrency
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1
	Type xs:string
	General Notes MONETARY AMOUNT CURRENCY TYPE
	Applicable Codes
	HomeCurrency HomeCurrency
	InvoicingCurrency Invoicing Currency