



Message Implementation Guideline

DSV_ShipmentMessage

Model: DSV SHIPMENT XML OUT
Version: v2.0
Issue date: 2026-08-28
Author: DSV A/S, EDI

3 Structure.....	2
4 Guideline	16

Structure

Occurrence	Element/Attribute
	DSV_ShipmentMessage
1 .. 1	xs:sequence
1 .. 1	Header
1 .. 1	xs:sequence
1 .. 1	MessageId
1 .. 1	SenderId
1 .. 1	ReceiverId
1 .. 1	DocumentDate
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
1 .. 1	DocumentCode
1 .. 1	Function
1 .. 1	Version
1 .. 1	Shipment
1 .. 1	xs:sequence
0 .. 1	ShipmentId
optional	<i>Type</i>
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportServices
1 .. 1	xs:sequence
0 .. unbounded	ServiceGroup
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	PriorityCode
0 .. unbounded	ServiceGroup <Services>
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	<i>Type</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
required	<i>Format</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	DateTime
0 .. 1	Parties
1 .. 1	<i>xs:sequence</i>
0 .. unbounded	Party
1 .. 1	<i>xs:sequence</i>
0 .. 1	PartyDetails
required	<i>Role</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	Locations
1 .. 1	<i>xs:sequence</i>
0 .. unbounded	LocationGroup
1 .. 1	<i>xs:sequence</i>
0 .. 1	Location
required	<i>Type</i>
1 .. 1	<i>xs:sequence</i>
1 .. unbounded	LocationIdentification
	<i>Type</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. unbounded	Contact
required	<i>Type</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
0 .. 1	References
1 .. 1	<i>xs:sequence</i>
0 .. unbounded	ReferenceGroup
1 .. 1	<i>xs:sequence</i>
0 .. 1	Reference
required	<i>Type</i>
optional	<i>Identifier</i>
0 .. 1	References
1 .. 1	<i>xs:sequence</i>
0 .. unbounded	ReferenceGroup

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
0 .. 1	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	Type
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	DescriptionCode
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	ControlTotals
1 .. 1	xs:sequence
0 .. unbounded	ControlTotal
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Quantity
0 .. 1	Documents
1 .. 1	xs:sequence
0 .. unbounded	Document
1 .. 1	xs:sequence
0 .. 1	DocumentCode
0 .. 1	DocumentCopies
0 .. 1	DocumentOriginals
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	LocationIdentifier
0 .. 1	TermsOfDelivery
1 .. 1	xs:sequence
0 .. 1	Terms
1 .. 1	xs:sequence
0 .. 1	TermsCode
0 .. 1	CodeId
0 .. unbounded required	Location
1 .. 1	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	CustomFieldType
0 .. 1	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	Requirements
1 .. 1	xs:sequence
0 .. unbounded	Requirement
1 .. 1	xs:sequence
0 .. 1	GovernmentalRequirements
1 .. 1	xs:sequence
0 .. 1	TransportMovementCode
0 .. 1	InvolvementCode
0 .. 1	Documents
1 .. 1	xs:sequence
0 .. unbounded	Document
1 .. 1	xs:sequence
0 .. 1	DocumentCode
0 .. 1	ChargeMethodology
1 .. 1	xs:sequence
0 .. unbounded	PaymentInstructions
1 .. 1	xs:sequence
0 .. 1	PaymentInstruction
1 .. 1	xs:sequence
0 .. 1	PaymentCode
0 .. 1	TransportStages
1 .. 1	xs:sequence
0 .. unbounded	TransportStage
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1 required	Stage
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	ModeOfTransport
0 .. 1	TransportId
0 .. 1	CarrierId
0 .. 1	CarrierName
0 .. 1	TransportType
0 .. 1	TransportMeansName
0 .. 1	TransportMeansNationality
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded required	Date
required	Type
1 .. 1	Format
0 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportServices
1 .. 1	xs:sequence
0 .. unbounded	ServiceGroup
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	PriorityCode
0 .. unbounded	ServiceGroup <Services>
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded required	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1 required	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1	PartyDetails
required	Role
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. unbounded	Contact
required	Type
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. unbounded	Party <DSVOperator>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1 required	PartyDetails
	Role
0 .. unbounded required	Contact
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Email
0 .. 1	GoodsItems
1 .. 1	xs:sequence
0 .. unbounded	GoodsItem
1 .. 1	xs:sequence
0 .. 1	Item
1 .. 1	xs:sequence
0 .. 1	Sequence
0 .. 1	ItemNumber
0 .. 1	PackageQty
0 .. 1	PackageType
0 .. 1	HandlingInstructions
1 .. 1	xs:sequence
0 .. unbounded	HandlingInstruction
1 .. 1	xs:sequence
0 .. 1	Code
0 .. 1	Description
0 .. 1	TemperatureControl
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Fixed
0 .. 1	RangeDetails
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Minimum
0 .. 1	Maximum
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded required	MonetaryAmount
	Type

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	ProductIds
1 .. 1	xs:sequence
0 .. unbounded	ProductId
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	ItemId
0 .. 1	ItemType
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	DescriptionCode
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded	Measurement
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dimensions
1 .. 1	xs:sequence
0 .. unbounded	Dimension
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	Length
0 .. 1	Width
0 .. 1	Height
0 .. 1	NumberOfUnits
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	<i>Type</i>
0 .. 1	Packagelds
1 .. 1	xs:sequence
0 .. unbounded	Packageld
1 .. 1	xs:sequence
1 .. 1	InstructionCode
0 .. 1	Marks
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
1 .. unbounded	ShippingMark
0 .. unbounded required	GoodsIdentities
1 .. 1	Type
1 .. unbounded	xs:sequence
0 .. 1	GoodsIdentifier
1 .. 1	GoodsPlacementIds
1 .. unbounded	xs:sequence
0 .. 1	GoodsPlacementId
1 .. 1	DangerousGoodsDetails
0 .. unbounded	xs:sequence
1 .. 1	DangerousGoodsDetail
0 .. 1	xs:sequence
1 .. 1	DangerousGoods
0 .. 1	xs:sequence
0 .. 1	Regulation
0 .. 1	HazardClass
0 .. 1	AdditionalHazardClass
0 .. 1	HazardVersionId
0 .. 1	UNDGNumber
0 .. 1	FlashPointDescription
0 .. 1	FlashPointTemperature
0 .. 1	FlashpointUom
0 .. 1	DangerLevelCode
0 .. 1	EMSNumber
0 .. 1	MFAGNumber
0 .. 1	TremCardNumber
0 .. 1	UpperPlate
0 .. 1	LowerPlate
0 .. 1	Labels
1 .. 1	xs:sequence
1 .. 4	Label
0 .. 1	PackingInstruction
0 .. 1	TransportMeansCode
0 .. 1	TunnelCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded required	FreeText
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	DescriptionCode
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded required	Measurement
1 .. 1	Type
0 .. 1	Uom
1 .. 1	xs:sequence
0 .. 1	Measure

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	Quantities
1 .. 1	xs:sequence
0 .. unbounded	Quantity
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Quantity
0 .. 1	ContainerNumber
0 .. 1	EquipmentUnits
1 .. 1	xs:sequence
0 .. unbounded	EquipmentUnit
1 .. 1	xs:sequence
0 .. 1	EquipmentType
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	ISOCODE
0 .. 1	PackingMode
0 .. 1	EquipmentSizeDescription
0 .. 1	FullOrEmptyIndicator
0 .. 1	NumberOfUnits
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded	Measurement
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dimensions
1 .. 1	xs:sequence
0 .. unbounded	Dimension
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Length
0 .. 1	Width
0 .. 1	Height
0 .. 1	SealIds
1 .. 1	xs:sequence
0 .. unbounded	Seal
1 .. 1	xs:sequence
0 .. 1	SealId
0 .. 1	SealParty
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
0 .. 1	Dates

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportMovements
1 .. 1	xs:sequence
0 .. unbounded	TransportMovement
optional	Type
1 .. 1	xs:sequence
0 .. 1	Code
0 .. 1	Description
0 .. 1	TransportServices
1 .. 1	xs:sequence
0 .. unbounded	ServiceGroup
1 .. 1	xs:sequence
0 .. 1	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	Type
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. unbounded	FreeText <Notes>
required	Type
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1	PartyDetails
required	Role
optional	AddressOverride
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. unbounded	Contact
required	Type
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
0 .. 1	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TemperatureControl
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Fixed
0 .. 1	HumidityPercentage

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public

Occurrence	Element/Attribute
0 .. 1 required	RangeDetails
	- Type - Uom - xs:sequence Minimum Maximum
0 .. 1 1 .. 1	Parties
	- xs:sequence Party
0 .. unbounded 1 .. 1	PartyDetails
	- Role - xs:sequence Id Assignor PartyName AddressLine1 AddressLine2 AddressLine3 CityName State PostCode CountryCode
0 .. 1 required	Locations
1 .. 1	- xs:sequence LocationGroup
0 .. unbounded 1 .. 1	Location
	- Type - xs:sequence LocationIdentification
1 .. unbounded	- Type - xs:sequence LocationIdentifier LocationName
0 .. unbounded required	Contact
1 .. 1	- Type - xs:sequence ContactId Name Phone Mobile Fax Email
0 .. 1 1 .. 1	References
	- xs:sequence ReferenceGroup
0 .. unbounded 1 .. 1	Reference
	Type
0 .. 1	Flags

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

DSV public



Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. unbounded	Flag
	Type



Guideline

Element/Attribute	Annotation
DSV_ShipmentMessage	General Notes Shipment.xsd V2 ----- Added: /Shipment/ShipmentId attributes Type and Qualifier /Shipment/TransportServices/ServiceGroup /Shipment/TransportServices/ServiceGroup/FreeTextData /Shipment/TransportServices/ServiceGroup/Dates /Shipment/TransportServices/ServiceGroup/Parties /Shipment/TransportServices/ServiceGroup/References /Shipment/TermsOfDelivery/Terms/DeliveryCode /Shipment/TermsOfDelivery/Terms/TransportChargesCode /Shipment/TransportStages/TransportStage/TransportServices /Shipment/TransportStages/TransportStage/Parties /Shipment/TransportStages/TransportStage/FreeTextData /Shipment/TransportStages/TransportStage/CodeDescriptions /Shipment/TransportStages/TransportStage/Flags /Shipment/Parties/Party/FinancialInstitution /Shipment/Parties/Party/Documents /Shipment/Goodsltems/Goodsltem/Item/Sequence /Shipment/Goodsltems/Goodsltem/Quantities /Shipment/Goodsltems/Goodsltem/Packagelds/References /Shipment/Goodsltems/Goodsltem/Packagelds/Dates /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/CodeDescriptions /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Quantities /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Flags /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Contact /Shipment/Goodsltems/Goodsltem/ContainerNumber /Shipment/Goodsltems/Goodsltem/Flags /Shipment/Goodsltems/Goodsltem/CodeDescriptions /Shipment/EquipmentUnits/EquipmentUnit/Measurements /Shipment/EquipmentUnits/EquipmentUnit/Dimensions /Shipment/EquipmentUnits/EquipmentUnit/TransportMovements /Shipment/EquipmentUnits/EquipmentUnit/RangeDetails /Shipment/EquipmentUnits/EquipmentUnit/Parties /Shipment/EquipmentUnits/EquipmentUnit/CodeDescriptions /Shipment/Orders /Shipment/Milestones Changes: /Shipment/TermsOfDelivery/Terms/TermCode to /Shipment/TermsOfDelivery/Terms/TermsCode
xs:sequence	Occurrence 1 .. 1

Element/Attribute	Annotation
Header	Occurrence 1 .. 1 Type Header Examples <Header> <MessageId>12485236</MessageId> <SenderId>SenderIdIdentification</SenderId> <ReceiverId>ReceiverIdIdentification</ReceiverId> <DocumentDate Type="DocumentDate" Format="DateTimeSec"> <DateTime>20250812000000</DateTime> </DocumentDate> <DocumentCode>ForwardingInstruction</DocumentCode> <Function>New</Function> <Version>2.0</Version> </Header>
xs:sequence	Occurrence 1 .. 1
MessageId	Occurrence 1 .. 1 Type xs:string General Notes MESSAGE IDENTIFICATION
SenderId	Occurrence 1 .. 1 Type xs:string General Notes SENDER IDENTIFICATION Mutually agreed
ReceiverId	Occurrence 1 .. 1 Type xs:string General Notes RECEIVER IDENTIFICATION Mutually agreed
DocumentDate	Occurrence 1 .. 1 Type Date
<i>Type</i>	Type xs:string Use required General Notes DOCUMENT / MESSAGE DATE TYPE
<i>Format</i>	Applicable Codes IssueDate Document Issued Date Type xs:string Use required General Notes DOCUMENT / MESSAGE DATE FORMAT
xs:sequence	Applicable Codes DateTime CCYYMMDDHHMM
DateTime	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes DOCUMENT MESSAGE DATE/TIME
DocumentCode	Occurrence 1 .. 1 Type xs:string General Notes DOCUMENT TYPE
Function	Applicable Codes BookingRequest Booking Request Message ForwardingInstruction Forwarding Instruction Message Occurrence 1 .. 1 Type xs:string General Notes DOCUMENT / MESSAGE FUNCTION
	Applicable Codes Delete Delete/ Cancel Shipment



Element/Attribute	Annotation
Version	Applicable Codes
	New New Shipment
	Update Update Shipment
	Occurrence 1 .. 1 Type xs:string General Notes DOCUMENT / MESSAGE VERSION
Shipment	Applicable Codes
	2.0 Version 2.0
	Occurrence 1 .. 1 Type Shipment
	General Notes SHIPMENT IDENTIFIER
ShipmentId	Examples <ShipmentId>ABC0011222</ShipmentId>
	Occurrence 1 .. 1 Type ShipmentId
	General Notes SHIPMENT IDENTIFIER
	Examples <ShipmentId>ABC0011222</ShipmentId>
Type	Applicable Codes
	Booking Order Management Booking
	LoadPlan Order Management Load Plan
	Occurrence 0 .. 1 Type DateList
Dates	Examples <Dates> <Date Type="IssueDate" Format="DateTime"> <DateTime>202508130900</DateTime> </Date> <Date Type="Collection" Format="Date"> <DateTime>20250820</DateTime> </Date> <Date Type="DeliveryRequested" Format="DateTimeInterval"> <DateTime>202508021200-202508021700</DateTime> </Date> </Dates>
	Occurrence 0 .. 1 Type DateList
	Examples <Dates> <Date Type="IssueDate" Format="DateTime"> <DateTime>202508130900</DateTime> </Date> <Date Type="Collection" Format="Date"> <DateTime>20250820</DateTime> </Date> <Date Type="DeliveryRequested" Format="DateTimeInterval"> <DateTime>202508021200-202508021700</DateTime> </Date> </Dates>
	Occurrence 0 .. 1 Type DateList
Date	Applicable Codes
	Collection Collection date/time, earliest
	DeliveryRequested Delivery date/time, requested
	EstimatedCollection Shipment date/time, promised for
Type	EstimatedDelivery Delivery date/time, estimated
	GoodsAvailable Goods Available
	GoodsStorage Goods Storage
	HouseBillIssued House Bill issued
Type	Receipt Receipt date/time
	RequestedCollection Shipment date/time, requested
	RequestedDelivery Requested Delivery Date/ Time
	ScheduledCollection Goods collection or pick-up date/ time, planned
Type	ScheduledDelivery Delivery date/time, 1st schedule
	Occurrence 1 .. 1 Type xs:string Use required General Notes SHIPMENT DATE TYPE
	Applicable Codes
	Collection Collection date/time, earliest
	DeliveryRequested Delivery date/time, requested
	EstimatedCollection Shipment date/time, promised for
	EstimatedDelivery Delivery date/time, estimated
	GoodsAvailable Goods Available
	GoodsStorage Goods Storage
	HouseBillIssued House Bill issued
	Receipt Receipt date/time
	RequestedCollection Shipment date/time, requested
	RequestedDelivery Requested Delivery Date/ Time
	ScheduledCollection Goods collection or pick-up date/ time, planned
	ScheduledDelivery Delivery date/time, 1st schedule



Element/Attribute	Annotation
<i>Format</i>	Type xs:string Use required General Notes SHIPMENT DATE FORMAT Applicable Codes Date YYYYMMDD DateTime YYYYMMDDHHMM DateTimeInterval YYYYMMDDHHMM-YYYYMMDDHHMM
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string General Notes SHIPMENT DATE/TIME
TransportServices	Occurrence 0 .. 1 Type ServiceGroupList General Notes TRANSPORT SERVICES First occurrence is Main Service Additional services will be provided in subsequent occurrences
xs:sequence	Occurrence 1 .. 1
ServiceGroup	Occurrence 0 .. unbounded Type ServiceGroup Examples <ServiceGroup> <TransportService> <ServiceCode>ROAD_LTL</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService> </ServiceGroup>
xs:sequence	Occurrence 1 .. 1
TransportService	Occurrence 0 .. 1 Type TransportService General Notes MAIN TRANSPORT SERVICE Examples <TransportService> <ServiceCode>ROAD_LTL</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService>
xs:sequence	Occurrence 1 .. 1
ServiceCode	Occurrence 0 .. 1 Type xs:string General Notes TYPE OF SERVICE REQUIRED Applicable Codes Air_IATA Air - IATA Air_LSE Air - LSE Before10 DSV specific value for Express 10: 00 Before12 DSV specific value for Express 12: 00 Before16 DSV specific value for Express 16: 00 Before7 DSV specific value for Express 07: 00 Crane DSV specific value for Crane



Element/Attribute	Annotation
	Applicable Codes HAZ required loading or unloading or both DSV specific value for Hazardous goods InNightproduct DSV specific value for INGT - InNight product Lift DSV specific value for LIFT-Tail lift Notification DSV specific value for NTFY - Notify OMEX DSV specific value for Omex service goods PersonalDeliveryService DSV specific value for PDS - Personal delivery service PreAdvice DSV specific value for PADV - Pre-advice Rail_FCL Rail - Full Container Load Rail_LCL Road - Less Than Truckload Road_FTL Road - Full Truckload Road_LTL Road - Less Than Truckload Sea_FCL Sea - Full Container Load Sea_LCL Sea - Less Than Container Load ePallet DSV specific value for EPLT - E-service pallet eParcel DSV specific value for EPRC- E-service collie
PriorityCode	Occurrence 0 .. 1 Type xs:string General Notes SERVICE PRIORITY CODE Only provided for Main Service (First TransportService)
ServiceGroup <Services>	Applicable Codes Express Express Service HighSpeed High Speed Service Normal Normal Service
xs:sequence	Occurrence 0 .. unbounded Type ServiceGroup
TransportService	Occurrence 1 .. 1 Type TransportService Examples <TransportService> <ServiceCode>OMEX</ServiceCode> </TransportService>
xs:sequence	Occurrence 0 .. 1 Type TransportService
ServiceCode	Occurrence 1 .. 1 Type xs:string General Notes Type of SERVICE CODE
	Applicable Codes Air_IATA Air - IATA Air_LSE Air - LSE Before10 DSV specific value for Express 10: 00 Before12 DSV specific value for Express 12: 00 Before16 DSV specific value for Express 16: 00 Before7 DSV specific value for Express 07: 00

Element/Attribute	Annotation
	Applicable Codes Crane DSV specific value for Crane required loading or unloading or both HAZ DSV specific value for Hazardous goods InNightproduct DSV specific value for INGT - InNight product Lift DSV specific value for LIFT-Tail lift Notification DSV specific value for NTFY - Notify OMEX DSV specific value for Omex service goods PersonalDeliveryService DSV specific value for PDS - Personal delivery service PreAdvice DSV specific value for PADV - Pre-advice Rail_FCL Rail - Full Container Load Rail_LCL Road - Less Than Truckload Road_FTL Road - Full Truckload Road_LTL Road - Less Than Truckload Sea_FCL Sea - Full Container Load Sea_LCL Sea - Less Than Container Load ePallet DSV specific value for EPLT - E-service pallet eParcel DSV specific value for EPRC- E-service collie
FreeTextData	Occurrence 0 .. 1 Type FreeTextList Examples <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
xs:sequence	Occurrence 1 .. 1
FreeText	Occurrence 0 .. unbounded Type FreeText
Type	Type xs:string Use required
	Applicable Codes ServiceDescription Service Description ServiceNote Service Note
xs:sequence	Occurrence 1 .. 1
TextLine1	Occurrence 0 .. 1 Type xs:string
Dates	Occurrence 0 .. 1 Type DateList Examples <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type Date
Type	Type xs:string Use required



Element/Attribute	Annotation
	Applicable Codes
	Booked Booked
<i>Format</i>	Type xs:string
	Use required
	Applicable Codes
<i>xs:sequence</i>	DateTimeSec CCYYMMDDHHMMSS
DateTime	Occurrence 1 .. 1
	Occurrence 0 .. 1
	Type xs:string
Parties	Occurrence 0 .. 1
	Type PartiesList
	General Notes TRANSPORT SERVICES PARTY
	Examples
	<Parties>
	<Party>
	<PartyDetails Role="Contractor">
	<Id>124563556</Id>
	<Assignor>DSV</Assignor>
	<PartyName>XYZ</PartyName>
	<AddressLine1>.</AddressLine1>
	<AddressLine2>AWDC</AddressLine2>
	<AddressLine3>AWDC</AddressLine3>
	<CityName>City</CityName>
	<State>State</State>
	<PostCode>1234</PostCode>
	<CountryCode>XY</CountryCode>
	</PartyDetails><Locations>
	<LocationGroup>
	<Location Type="Departure">
	<LocationIdentification Type="UN">
	<LocationIdentifier>DKHOR</LocationIdentifier>
	</LocationIdentification>
	</Location>
	</LocationGroup>
	<LocationGroup>
	<Location Type="Destination">
	<LocationIdentification Type="UN">
	<LocationIdentifier>ZAJNB</LocationIdentifier>
	<LocationName>Johannesburg</LocationName>
	</LocationIdentification>
	<LocationIdentification Type="IATA">
	<LocationIdentifier>JNB</LocationIdentifier>
	<LocationName>Johannesburg</LocationName>
	</LocationIdentification>
	</Location>
	</LocationGroup>
	</Locations>
	<Contact Type="InformationContact">
	<ContactId>XYX</ContactId>
	<Name>AGHJFGH</Name>
	<Phone>123456789</Phone>
	<Mobile>1234567890</Mobile>
	<Fax>12345678</Fax>
	<Email>XYZ@ABC.COM</Email>
	</Contact>
	<References>
	<ReferenceGroup>
	<Reference Type="ServiceReference">SerRef1</Reference>
	</ReferenceGroup>
	</References>



Element/Attribute	Annotation		
	Examples </Party> </Parties>		
xs:sequence	Occurrence 1 .. 1		
Party	Occurrence 0 .. unbounded		
	Type Party		
xs:sequence	Occurrence 1 .. 1		
PartyDetails	Occurrence 0 .. 1		
	Type PartyDetails		
	Examples <PartyDetails Role="Contractor"> <Id>124563556</Id> <Assignor>DSV</Assignor> <PartyName>XYZ</PartyName> <AddressLine1></AddressLine1> <AddressLine2>AWDC</AddressLine2> <AddressLine3>AWDC</AddressLine3> <CityName>City</CityName> <State>State</State> <PostCode>1234</PostCode> <CountryCode>XY</CountryCode> </PartyDetails>		
<i>Role</i>	Type xs:string Use required		
	Applicable Codes <table> <tr> <td>Contractor</td><td>Service Contractor</td></tr> </table>	Contractor	Service Contractor
Contractor	Service Contractor		
xs:sequence	Occurrence 1 .. 1		
Id	Occurrence 0 .. 1		
	Type xs:string		
Assignor	Occurrence 0 .. 1		
	Type xs:string		
PartyName	Occurrence 0 .. 1		
	Type xs:string		
AddressLine1	Occurrence 0 .. 1		
	Type xs:string		
AddressLine2	Occurrence 0 .. 1		
	Type xs:string		
AddressLine3	Occurrence 0 .. 1		
	Type xs:string		
CityName	Occurrence 0 .. 1		
	Type xs:string		
State	Occurrence 0 .. 1		
	Type xs:string		
PostCode	Occurrence 0 .. 1		
	Type xs:string		
CountryCode	Occurrence 0 .. 1		
	Type xs:string		
Locations	Occurrence 0 .. 1		
	Type LocationGroupList		
	Examples <Locations> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </LocationGroup> </Locations>		

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV SHIPMENT XML OUT; v2.0

Issue date: 2026-08-28

Print date: 2026-08-28

Generated by GEFEF.FX

Page: 23 / 73

Element/Attribute	Annotation
	Examples </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="UN"> <LocationIdentifier>ZAJNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> <LocationIdentification Type="IATA"> <LocationIdentifier>JNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type Location
Type	Type xs:string
	Use required
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
Type	Type xs:string
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
LocationName	Occurrence 0 .. 1
	Type xs:string
Contact	Occurrence 0 .. unbounded
	Type Contact
	Examples <Contact Type="InformationContact"> <ContactId>XYX</ContactId> <Name>AGHJFGH</Name> <Phone>123456789</Phone> <Mobile>1234567890</Mobile> <Fax>12345678</Fax> <Email>XYZ@ABC.COM</Email> </Contact>
Type	Type xs:string
	Use required
xs:sequence	Occurrence 1 .. 1
ContactId	Occurrence 0 .. 1
	Type xs:string
Name	Occurrence 0 .. 1
	Type xs:string
Phone	Occurrence 0 .. 1
	Type xs:string
Mobile	Occurrence 0 .. 1
	Type xs:string
Fax	Occurrence 0 .. 1
	Type xs:string

Element/Attribute	Annotation
Email	Occurrence 0 .. 1 Type xs:string
References	Occurrence 0 .. 1 Type ReferenceGroupList Examples <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required
<i>Identifier</i>	Type xs:string Use optional
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes TRANSPORT SERVICES REFERENCES Examples <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required
<i>Identifier</i>	Type xs:string Use optional
Date	Occurrence 0 .. 1 Type Date
<i>Type</i>	Type xs:string Use required
<i>Format</i>	Type xs:string Use required
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string
MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountList

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation				
	General Notes SHIPMENT MONETARY AMOUNTS Examples <MonetaryAmounts> <MonetaryAmount Type="InvoiceValue"> <Amount>100.01</Amount> <Currency>DKK</Currency> </MonetaryAmount> </MonetaryAmounts>				
xs:sequence MonetaryAmount Type	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type MonetaryAmount Type xs:string Use required General Notes MONETARY AMOUNT TYPE Applicable Codes <table> <tr> <td>COD</td><td>Cash On Delivery Amount</td></tr> <tr> <td>InvoiceValue</td><td>Invoice Value</td></tr> </table>	COD	Cash On Delivery Amount	InvoiceValue	Invoice Value
COD	Cash On Delivery Amount				
InvoiceValue	Invoice Value				
xs:sequence Amount Currency	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT				
	Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT ISO CURRENCY				
FreeTextData	Occurrence 0 .. 1 Type FreeTextList General Notes SHIPMENT FREE TEXT Examples <FreeTextData> <FreeText Type="DeliveryInstructions"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> <TextLine2>DeliveryInstructions Text Line 2</TextLine2> <TextLine3>DeliveryInstructions Text Line 3</TextLine3> <TextLine4>DeliveryInstructions Text Line 4</TextLine4> <TextLine5>DeliveryInstructions Text Line 5</TextLine5> </FreeText> <FreeText Type="HandlingInstructions"> <TextLine1>Handling Instructions Text Line 1</TextLine1> </FreeText> <FreeText Type="PickupInstructions"> <TextLine1>Pickup Instructions Text Line 1</TextLine1> </FreeText> </FreeTextData>				
xs:sequence FreeText Type	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type FreeText Type xs:string Use required General Notes FREE TEXT TYPE Predefined Types listed, additional FreeText types to be agreed				
	Applicable Codes <table> <tr> <td>AdditionalDetails</td><td>Additional Details</td></tr> </table>	AdditionalDetails	Additional Details		
AdditionalDetails	Additional Details				



Element/Attribute	Annotation
	Applicable Codes
	ConsignmentDetails Consignment Details (Status, RegDate, Remarks, Originater) DeliveryInstructions Delivery Instructions DeliveryRemarks Delivery Remarks GeneralInformation General information GoodsDescription Goods Description MarinePollutant DG Marine Pollutant NatureOfCargo Nature Of Cargo PickupInstructions Pickup Instructions ProperShippingName DG Proper Shipping Name ReportInformation Report Information SpecialHandling Special Handling SpecialInstructions Special Instructions StatusRemarks Status Remarks WarehouseInstructionsExport Warehouse Instructions Export
xs:sequence	Occurrence 1 .. 1
DescriptionCode	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT DESCRIPTION CODE Use to be agreed
TextLine1	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 1
TextLine2	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 2
TextLine3	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 3
TextLine4	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 4
TextLine5	Occurrence 0 .. 1 Type xs:string General Notes FREE TEXT LINE 5
ControlTotals	Occurrence 0 .. 1 Type ControlTotalList General Notes SHIPMENT CONTROL TOTALS Examples <ControlTotals> <ControlTotal Type="NumberOfPackages"> <Quantity>20</Quantity> </ControlTotal> <ControlTotal Type="GrossWeight" Uom="KGM"> <Quantity>101.01</Quantity> </ControlTotal> <ControlTotal Type="Volume" Uom="MTQ"> <Quantity>2</Quantity> </ControlTotal> <ControlTotal Type="LoadingMeters" Uom="MTR"> <Quantity>12</Quantity> </ControlTotal> <ControlTotal Type="PalletSpaces" Uom="PLL">

Element/Attribute	Annotation
	Examples <Quantity>10</Quantity> </ControlTotal> </ControlTotals>
xs:sequence	Occurrence 1 .. 1
ControlTotal	Occurrence 0 .. unbounded
	Type ControlTotal
Type	Type xs:string
	Use required
	General Notes CONTROL TOTAL TYPE
	Applicable Codes ChargableWeight Chargable Weight GrossWeight Gross Weight LoadingMeters Loading Meters NumberOfInnerPackages Number Of Inner Packages NumberOfPackages Number Of Packages PalletSpaces Pallet Spaces TotalNetWeightOfShipment Total net weight of shipment TotalNumberOfShipments Total number of shipments Volume Volume
Uom	Type xs:string
	General Notes QUANTITY UNIT OF MEASURE
	Applicable Codes CTN Cartons KGM Kilograms MTQ Cubic meters MTR Linear meters PCE Pieces PKG Packages UNT Units
xs:sequence	Occurrence 1 .. 1
Quantity	Occurrence 0 .. 1
	Type xs:string
	General Notes CONTROL TOTAL QUANTITY
Documents	Occurrence 0 .. 1
	Type DocumentList
	General Notes SHIPMENT DOCUMENTS
	Examples <Documents> <Document> <DocumentCode>EBL</DocumentCode> <DocumentCopies>1</DocumentCopies> <DocumentOriginals>0</DocumentOriginals> </Document> </Documents>
xs:sequence	Occurrence 1 .. 1
Document	Occurrence 0 .. unbounded
	Type Document
xs:sequence	Occurrence 1 .. 1
DocumentCode	Occurrence 0 .. 1
	Type xs:string
	General Notes DOCUMENT CODE
	Applicable Codes EBL Non-negotiable maritime transport

Element/Attribute	Annotation
	Applicable Codes document OBO Original Bill - Surrendered at origin OBP Original BL - Print at destination OBR Bill of lading original T1 Despatch note model T1 T2 Despatch note model T2 T2L Despatch note model T2L T5 Control Document T5
DocumentCopies	Occurrence 0 .. 1 Type xs:string General Notes NUMBER OF COPIES
DocumentOriginals	Occurrence 0 .. 1 Type xs:string General Notes NUMBER OF ORIGINALS
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes SHIPMENT LOCATIONS Examples <Locations> <LocationGroup> <Location Type="BranchLocation"> <LocationIdentification Type="DSVBranch"> <LocationIdentifier>HOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type Location
Type	Type xs:string Use required General Notes LOCATION TYPE
	Applicable Codes DSVOrigin DSV Origin
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
Type	Type xs:string General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes DSVBookingOffice DSV Booking Office (Only to be used for CargoLink Road Freight) DSVBranch DSV Branch (Only to be used for Air, Sea & Rail) DSVDepartment DSV Department (Only to be used for Air, Sea & Rail) ISOCountry Originating Country ISO Code (Only used for Air, Sea & Rail)
xs:sequence	Occurrence 1 .. 1

Element/Attribute	Annotation
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER
TermsOfDelivery	Occurrence 0 .. 1 Type TermsGroup Examples <TermsOfDelivery> <Terms> <TermsCode>CIP</TermsCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>
xs:sequence	Occurrence 1 .. 1
Terms	Occurrence 0 .. 1 Type Terms
xs:sequence	Occurrence 1 .. 1
TermsCode	Occurrence 0 .. 1 Type xs:string General Notes TERM CODE
CodeId	Occurrence 0 .. 1 Type xs:string General Notes TYPE OF TERM CODE Applicable Codes CombiTerm Combi Term Incoterm INCO Term
Location	Occurrence 0 .. unbounded Type Location
<i>Type</i>	Type xs:string Use required Applicable Codes NamedPlace Term Named Place
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
<i>Type</i>	Type xs:string Applicable Codes Name Only Location Name provided UN UN Location Code
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
LocationName	Type xs:string Occurrence 0 .. 1 Type xs:string
References	Occurrence 0 .. 1 Type ReferenceGroupList Examples <References> <ReferenceGroup> <Reference Type="ShipperReference">ShpRef1</Reference> <Date Type="ReferenceDate" Format="Date">



Element/Attribute	Annotation
	Examples <DateTime>20250803</DateTime> </Date> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">ConsRef1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="RoadWaybill">Waybill1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>2025081309000000</DateTime> </Date> </Dates> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes SHIPMENT REFERENCE
Type	Type xs:string Use required General Notes SHIPMENT REFERENCE TYPE Predefined Types listed, additional reference types to be agreed
Applicable Codes	
ASMShipmentId	Assembly Master Shipment Id
AgentsReference	Agent's reference
AviationSecurity	Aviation Security
CLPartnerCode	CargoLink Partner Code
CargoManifestNo	Cargo manifest number, Transport Id
ConsigneeOrderNumber	Consignee's order number
ConsigneeReference	Consignee Reference
ConsignmentId	Consignment id, carrier assigned
CustomField	Custom Field
CustomerAccountCode	Customer Account Code
CustomerReferenceNumber	Customer reference number
DeliveryAgreement	Delivery Agreement
DocumentReference	Document Reference
EventCode	DSV specific value for Event Code
ExternalReference	DSV specific value for External reference customer reference number
GINCNumber	Waybill number, GINC
HazardousReference	Hazardous Reference
HouseBill	House bill of lading number
IDSReference	DSV specific value for IDS reference
InspectionType	Inspection Type
MasterBill	Master bill of lading number
OnSightAuthorizationCode	DSV specific value for On sight authorization code
OrderReference	Order Reference
PackageNumber	Package Number
ProofOfDeliveryNumber	Proof of delivery reference number
QualityCode	Quality Code



Element/Attribute	Annotation
	Applicable Codes QualitySource Quality Source RoadWaybill Road Waybill number, SIS ShipmentReference Shipment reference number ShipperReference Shipper Reference TrafficFrom Traffic From TransportInstructionNumber Transport instruction number VehicleId Vehicle identification number (VIN) VesselCountryOfRegistration DSV specific value for Vessel Country of Registration VesselId Vessel identifier
<i>CustomFieldType</i>	Type xs:string Use optional General Notes CUSTOM FIELD TYPE Use to be agreed
Date	Occurrence 0 .. 1 Type Date General Notes REFERENCE DATE
<i>Type</i>	Type xs:string Use required General Notes REFERENCE DATE
<i>Format</i>	Applicable Codes ReferenceDate Reference Date Type xs:string Use required General Notes REFERENCE DATE FORMAT
<i>xs:sequence</i>	Applicable Codes DateTime CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS
DateTime	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes REFERENCE DATE/TIME
Requirements	Occurrence 0 .. 1 Type RequirementList General Notes GOVERNMENT AND DOCUMENT REQUIREMENTS Examples <Requirements> <Requirement> <GovernmentalRequirements> <TransportMovementCode>Export</TransportMovementCode> <InvolvementCode>NotApplicable</InvolvementCode> </GovernmentalRequirements> <Documents> <Document> <DocumentCode>EBL</DocumentCode> </Document> </Documents> </Requirement> </Requirements>
<i>xs:sequence</i>	Occurrence 1 .. 1
Requirement	Occurrence 0 .. unbounded Type Requirement
<i>xs:sequence</i>	Occurrence 1 .. 1

Element/Attribute	Annotation
GovernmentalRequirements	Occurrence 0 .. 1 Type GovernmentalRequirements
xs:sequence	Occurrence 1 .. 1
TransportMovementCode	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MOVEMENT TYPE
	Applicable Codes Export Import Transit
InvolvementCode	Occurrence 0 .. 1 Type xs:string General Notes INVOLVEMENT CODE
	Applicable Codes Completed NotApplicable
Documents	Occurrence 0 .. 1 Type DocumentList
xs:sequence	Occurrence 1 .. 1
Document	Occurrence 0 .. unbounded Type Document
xs:sequence	Occurrence 1 .. 1
DocumentCode	Occurrence 0 .. 1 Type xs:string General Notes ROAD TRANSPORTATION DOCUMENT TYPE
	Applicable Codes EBL Non-negotiable maritime transport document OBO Original Bill - Surrendered at origin OBP Original BL - Print at destination OBR Bill of lading original T1 Despatch note model T1 T2 Despatch note model T2 T2L Despatch note model T2L T5 Control document T5
ChargeMethodology	Occurrence 0 .. 1 Type ChargeMethodologyList General Notes CHARGE METHODOLOGY
	Examples <ChargeMethodology> <PaymentInstructions> <PaymentInstruction> <PaymentCode>Prepaid</PaymentCode> </PaymentInstruction> </PaymentInstructions> </ChargeMethodology>
xs:sequence	Occurrence 1 .. 1
PaymentInstructions	Occurrence 0 .. unbounded Type PaymentInstructions
xs:sequence	Occurrence 1 .. 1
PaymentInstruction	Occurrence 0 .. 1 Type PaymentInstruction
xs:sequence	Occurrence 1 .. 1
PaymentCode	Occurrence 0 .. 1 Type xs:string

Element/Attribute	Annotation
	General Notes PAYMENT TYPE Applicable Codes Collect Collect Shipment Prepaid Prepaid Shipment ThirdParty Third Party Shipment
TransportStages	Occurrence 0 .. 1 Type TransportStageList General Notes TRANSPORT STAGES
xs:sequence	
TransportStage	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type TransportStage
xs:sequence	
Stage	Occurrence 1 .. 1 Occurrence 0 .. 1 Type Stage General Notes TRANSPORTATION STAGE Examples <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> <TransportId>12345X</TransportId> <CarrierId>12345678</CarrierId> <CarrierName>Carrier Name</CarrierName> <TransportType>Main</TransportType> <TransportMeansName>Vessel name</TransportMeansName> <TransportMeansNationality>PA</TransportMeansNationality> </Stage>
Type	Type xs:string Use required General Notes TRANSPORTATION STAGE TYPE Applicable Codes MainCarriage Main Carriage PlannedLeg Planned Leg PlannedLeg1 Main carriage - first carrier PlannedLeg2 Main carriage - second carrier PlannedLeg3 Main carriage - third carrier PlannedLeg4 Main carriage - fourth carrier PlannedLeg5 Main carriage - fifth carrier
xs:sequence	
ModeOfTransport	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes MODE OF TRANSPORTATION Applicable Codes Air Air transportation Rail Rail transportation Road Road transportation Sea Sea transportation
TransportId	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT IDENTIFICATION Air: Flight number Sea: Voyage number Road: Not used
CarrierId	Occurrence 0 .. 1 Type xs:string General Notes CARRIER IDENTIFICATION Air & Sea: DSV carrier identifier



Element/Attribute	Annotation												
	Road: Not used												
CarrierName	Occurrence 0 .. 1 Type xs:string General Notes CARRIER NAME Road: Not used												
TransportType	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT TYPE Road: Not used Applicable Codes <table> <tr><td>Flight1</td><td>First Flight</td></tr> <tr><td>Flight2</td><td>Second Flight</td></tr> <tr><td>Flight3</td><td>Third Flight</td></tr> <tr><td>Flight4</td><td>Fourth Flight</td></tr> <tr><td>Main</td><td>Main Carriage</td></tr> <tr><td>Other</td><td>Other</td></tr> </table>	Flight1	First Flight	Flight2	Second Flight	Flight3	Third Flight	Flight4	Fourth Flight	Main	Main Carriage	Other	Other
Flight1	First Flight												
Flight2	Second Flight												
Flight3	Third Flight												
Flight4	Fourth Flight												
Main	Main Carriage												
Other	Other												
TransportMeansName	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NAME Sea: Vessel Name Air & Road: Not used												
TransportMeansNationality	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS NATIONALITY Sea: Vessel flag Air & Road: Not used												
Dates	Occurrence 0 .. 1 Type DateList General Notes TRANSPORTATION DATES Examples <Dates> <Date Format="DateTimeSec" Type="ScheduledDeparture"> <DateTime>20250821093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentDeparture"> <DateTime>20250821093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledArrival"> <DateTime>20250819000100</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentArrival"> <DateTime>20250819000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDeparture"> <DateTime>20250821093500</DateTime> </Date> </Dates>												
xs:sequence	Occurrence 1 .. 1												
Date	Occurrence 0 .. unbounded Type Date												
Type	Type xs:string Use required General Notes TRANSPORTATION DATE TYPE												

Element/Attribute	Annotation
	Applicable Codes ActualArrival Actual Time of Arrival ActualDelivery Actual Delivery date/time ActualDeparture Actual Time of Departure EstimatedArrival Estimated Time of Arrival EstimatedDelivery Delivery date/time, estimated EstimatedDeparture Estimated Time of Departure ScheduledArrival Scheduled Time of Arrival ScheduledDeparture Scheduled Time of Departure ScheduledShipmentArrival Scheduled Shipment Time of Arrival ScheduledShipmentDeparture Scheduled Shipment Time of Departure
<i>Format</i>	Type xs:string Use required General Notes TRANSPORTATION DATE FORMAT Applicable Codes DateTime CCYYMMDDHHMM DateTimeInterval CCYYMMDDHHMM- CCYYMMDDHHMM DateTimeSec CCYYMMDDHHMMSS
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORTATION DATE/TIME
TransportServices	Occurrence 0 .. 1 Type ServiceGroupList General Notes TRANSPORT STAGES TRANSPORT SERVICE
xs:sequence	Occurrence 1 .. 1
ServiceGroup	Occurrence 0 .. unbounded Type ServiceGroup Examples <ServiceGroup> <TransportService> <ServiceCode>AIR_LSE</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService> </ServiceGroup>
xs:sequence	Occurrence 1 .. 1
TransportService	Occurrence 0 .. 1 Type TransportService
xs:sequence	Occurrence 1 .. 1
ServiceCode	Occurrence 0 .. 1 Type xs:string Applicable Codes Air_IATA Air - IATA Air_LSE Air - LSE Before10 DSV specific value for Express 10: 00 Before12 DSV specific value for Express 12: 00 Before16 DSV specific value for Express 16: 00 Before7 DSV specific value for Express 07: 00 Crane DSV specific value for Crane required loading or unloading or both



Element/Attribute	Annotation
	Applicable Codes
HAZ	DSV specific value for Hazardous goods
InNightproduct	DSV specific value for INGT - InNight product
Lift	DSV specific value for LIFT-Tail lift
Notification	DSV specific value for NTFY - Notify
OMEX	DSV specific value for Omex service goods
PersonalDeliveryService	DSV specific value for PDS - Personal delivery service
PreAdvice	DSV specific value for PADV - Pre-advice
Rail_FCL	Rail - Full Container Load
Rail_LCL	Road - Less Than Truckload
Road_FTL	Road - Full Truckload
Road_LTL	Road - Less Than Truckload
Sea_FCL	Sea - Full Container Load
Sea_LCL	Sea - Less Than Container Load
ePallet	DSV specific value for EPLT - E-service pallet
eParcel	DSV specific value for EPRC- E-service collie
PriorityCode	Occurrence 0 .. 1 Type xs:string Applicable Codes Express Express Service HighSpeed High Speed Service Normal Normal Service
ServiceGroup <Services>	Occurrence 0 .. unbounded Type ServiceGroup Examples <ServiceGroup> <TransportService> <ServiceCode>PreAdvice</ServiceCode> <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData> <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date> </Dates> <Parties> <Party> <PartyDetails Role="Contractor"> <Id>123456789XYZ</Id> <Assignor>DSV</Assignor> <PartyName>ABCDEF</PartyName> <AddressLine1>ASDF</AddressLine1> <AddressLine2>XYZ</AddressLine2> <CityName>CITY</CityName> <PostCode>POCODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>ASDFGRT</Name> <Phone>123456789</Phone>

Element/Attribute	Annotation
	Examples </Contact> </Party> </Parties> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References> </TransportService> </ServiceGroup>
xs:sequence	Occurrence 1 .. 1
TransportService	Occurrence 0 .. 1
	Type TransportService
xs:sequence	Occurrence 1 .. 1
ServiceCode	Occurrence 0 .. 1
	Type xs:string
	Applicable Codes
	Air_IATA Air - IATA
	Air_LSE Air - LSE
	Before10 DSV specific value for Express 10: 00
	Before12 DSV specific value for Express 12: 00
	Before16 DSV specific value for Express 16: 00
	Before7 DSV specific value for Express 07: 00
	Crane DSV specific value for Crane required loading or unloading or both
	HAZ DSV specific value for Hazardous goods
	InNightproduct DSV specific value for INGT - InNight product
	Lift DSV specific value for LIFT-Tail lift
	Notification DSV specific value for NTFY - Notify
	OMEX DSV specific value for Omex service goods
	PersonalDeliveryService DSV specific value for PDS - Personal delivery service
	PreAdvice DSV specific value for PADV - Pre- advice
	Rail_FCL Rail - Full Container Load
	Rail_LCL Road - Less Than Truckload
	Road_FTL Road - Full Truckload
	Road_LTL Road - Less Than Truckload
	Sea_FCL Sea - Full Container Load
	Sea_LCL Sea - Less Than Container Load
	ePallet DSV specific value for EPLT - E- service pallet
	eParcel DSV specific value for EPRC- E- service collie
FreeTextData	Occurrence 0 .. 1
	Type FreeTextList
xs:sequence	Occurrence 1 .. 1

Element/Attribute	Annotation														
FreeText	Occurrence 0 .. unbounded Type FreeText														
<i>Type</i>	Type xs:string Use required														
<i>xs:sequence</i>	Occurrence 1 .. 1														
TextLine1	Occurrence 0 .. 1 Type xs:string														
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes TRANSPORTATION LOCATIONS Examples <Locations> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="UN"> <LocationIdentifier>ZAJNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> <LocationIdentification Type="IATA"> <LocationIdentifier>JNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations>														
<i>xs:sequence</i>	Occurrence 1 .. 1														
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup														
<i>xs:sequence</i>	Occurrence 1 .. 1														
Location	Occurrence 0 .. 1 Type Location														
<i>Type</i>	Type xs:string Use required General Notes TRANSPORTATION LOCATION TYPE														
Applicable Codes <table> <tr> <td>Departure</td><td>Place of Departure</td></tr> <tr> <td>Destination</td><td>Place of Destination</td></tr> <tr> <td>GoodsItemLocation</td><td>Goods Item Storage Location</td></tr> <tr> <td>PlaceOfConsolidation</td><td>Place of Consolidation</td></tr> <tr> <td>PlaceOfDeconsolidation</td><td>Place of Deconsolidation</td></tr> <tr> <td>PlaceOfLoading</td><td>Place of Loading</td></tr> <tr> <td>PlaceOfUnloading</td><td>Place of Unloading</td></tr> </table>		Departure	Place of Departure	Destination	Place of Destination	GoodsItemLocation	Goods Item Storage Location	PlaceOfConsolidation	Place of Consolidation	PlaceOfDeconsolidation	Place of Deconsolidation	PlaceOfLoading	Place of Loading	PlaceOfUnloading	Place of Unloading
Departure	Place of Departure														
Destination	Place of Destination														
GoodsItemLocation	Goods Item Storage Location														
PlaceOfConsolidation	Place of Consolidation														
PlaceOfDeconsolidation	Place of Deconsolidation														
PlaceOfLoading	Place of Loading														
PlaceOfUnloading	Place of Unloading														
<i>xs:sequence</i>	Occurrence 1 .. 1														
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification General Notes One Location can result in up to three LocationIdentification elements.														
<i>Type</i>	Type xs:string General Notes LOCATION IDENTIFIER TYPE														

Bold = Element, Italic = Attribute, Grey = Group
DSV public

DSV SHIPMENT XML OUT; v2.0
Issue date: 2026-08-28
Print date: 2026-08-28

Generated by GEFEG.FX
 Page: 40 / 73

Element/Attribute	Annotation
	Applicable Codes QualityCode Quality Code QualitySource Quality Source RoadWaybill Road Waybill number, SIS ShipmentReference Shipment reference number ShipperReference Shipper Reference TrafficFrom Traffic From TransportInstructionNumber Transport instruction number TypeOfService Type of Service VehicleId Vehicle identification number (VIN) VesselCountryOfRegistration DSV specific value for Vessel Country of Registration VesselId Vessel identifier
Identifier	Type xs:string Use optional
CustomFieldType	Type xs:string Use optional
Parties	Occurrence 0 .. 1 Type PartiesList General Notes SHIPMENT PARTY INFORMATION
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded Type Party
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1 Type PartyDetails General Notes PARTY DETAILS Examples <PartyDetails Role="Consignor"> <Id>ConsignorID</Id> <Assignor>Consignor</Assignor> <PartyName>Consignor Name</PartyName> <AddressLine1>Consignor Addr Line 1</AddressLine1> <AddressLine2>Consignor Addr Line 2</AddressLine2> <AddressLine3>Consignor Addr Line 3</AddressLine3> <CityName>Consignor City</CityName> <State>Consignor State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails>
Role	Type xs:string Use required General Notes PARTY ROLE
	Applicable Codes AcceptingParty Agent Buyer Carrier Carrier Party Consignee Consignee Party Consignor Consignor Party Consolidator Consolidator Deconsolidator Deconsolidator Delivery Delivery Party DeliveryAgent Delivery Agent DeliveryLocalCartage Delivery Local Cartage Despatch Despatch Party Forwarder Forwarder



Element/Attribute	Annotation
Applicable Codes	
FreightForwarder	Freight Forwarder
FreightPayer	Freight/charges Payer
Notify	Notify Party
OrderingCustomer	Ordering Customer
PickupAgent	Pickup Agent
PickupLocalCartage	Pickup Local Cartage
ShipFrom	Ship From
ShipTo	Ship To
Supplier	Supplier
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY IDENTIFIER
Assignor	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY IDENTIFIER ASSIGNOR
Applicable Codes	
Consignor	Consignor Assigned
DSV	DSV Assigned
GS1	GS1 Assigned
PartyName	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY NAME
AddressLine1	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY CITY NAME
State	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY STATE OR PROVINCE
PostCode	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY LOCATION ISO COUNTRY CODE
Locations	Occurrence 0 .. 1
	Type LocationGroupList
	General Notes PHYSICAL LOCATION
Examples	
<Locations>	
<LocationGroup>	

Element/Attribute	Annotation
	Examples <Location Type="PhysicalLocation"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type Location
Type	Type xs:string
	Use required
	General Notes PHYSICAL LOCATION TYPE
	Applicable Codes
	Physicallocation Party Location
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type LocationIdentification
Type	Type xs:string
	General Notes PHYSICAL LOCATION IDENTIFIER TYPE
	Applicable Codes
	UN UN Location Code
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
	General Notes PHYSICAL LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1
	Type xs:string
	General Notes PHYSICAL LOCATION NAME
Contact	Occurrence 0 .. unbounded
	Type Contact
	General Notes PARTY CONTACT DETAILS
	Examples <Contact Type="InformationContact"> <ContactId>Contact ID</ContactId> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
Type	Type xs:string
	Use required
	General Notes PARTY CONTACT TYPE
	Applicable Codes
	GoodsReceivingContact Goods Receiving Contact
	InformationContact Party Information Contact
xs:sequence	Occurrence 1 .. 1



Element/Attribute	Annotation
ContactId	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT ID
Name	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT PHONE NUMBER
Mobile	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT MOBILE NUMBER
Fax	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT FAX NUMBER
Email	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT E-MAIL ADDRESS
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes PARTY REFERENCES Examples <References> <ReferenceGroup> <Reference Type="VAT" Identifier="DK">VatNo</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference General Notes PARTY REFERENCE
Type	Type xs:string Use required General Notes PARTY REFERENCE TYPE Predefined Types listed, additional reference types to be agreed
Applicable Codes	
VAT	VAT Number
Identifier	Type xs:string Use optional General Notes PARTY REFERENCE IDENTIFIER
CustomFieldType	Type xs:string Use optional General Notes PARTY REFERENCE CUSTOM FIELD TYPE Use to be agreed

Element/Attribute	Annotation
Party <DSVOperator>	Occurrence 0 .. unbounded Type Party Examples <Party> <PartyDetails Role="Consignor"> <Id>1234567890</Id> <Assignor>DSV</Assignor> <PartyName>ABCDEF</PartyName> <AddressLine1>XYZSD</AddressLine1> <AddressLine2>ASDFTG</AddressLine2> <CityName>CITY</CityName> <PostCode>POCODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>CONTACT NAME</Name> <Phone>123456789</Phone> </Contact> </Party>
xs:sequence PartyDetails	Occurrence 1 .. 1 Occurrence 0 .. 1 Type PartyDetails General Notes PARTY DETAILS Examples <PartyDetails Role="Consignor"> </PartyDetails>
Role	Type xs:string Use required General Notes PARTY ROLE Applicable Codes DSVOperator DSV Operator
Contact	Occurrence 0 .. unbounded Type Contact General Notes PARTY CONTACT DETAILS Examples <Contact Type="InformationContact"> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Email>Contact Email</Email> </Contact>
Type	Type xs:string Use required General Notes PARTY CONTACT TYPE Applicable Codes InformationContact Party Information Contact
xs:sequence Name	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT PHONE NUMBER



Element/Attribute	Annotation
Email	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT E-MAIL ADDRESS
GoodsItems	Occurrence 0 .. 1 Type GoodsItemList General Notes SHIPMENT LINE ITEMS
xs:sequence GoodsItem	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type GoodsItem
xs:sequence Item	Occurrence 1 .. 1 Occurrence 0 .. 1 Type Item General Notes GOODS ITEM DETAILS Examples <Item> <ItemNumber>1</ItemNumber> <PackageQty>20</PackageQty> <PackageType>PKG</PackageType> </Item>
xs:sequence Sequence	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes LINE SEQUENCE NUMBER
ItemNumber	Occurrence 0 .. 1 Type xs:string General Notes LINE ITEM NUMBER
PackageQty	Occurrence 0 .. 1 Type xs:string General Notes LINE ITEM PACKAGE QUANTITY
PackageType	Occurrence 0 .. 1 Type xs:string General Notes LINE ITEM PACKAGE TYPE Applicable Codes UNT Units
HandlingInstructions	Occurrence 0 .. 1 Type HandlingInstructions General Notes LINE ITEM HANDLING INSTRUCTION Only used for Road Freight Stacked Cargo Examples <HandlingInstructions> <HandlingInstruction> <Code>Stacked</Code> <Description>10</Description> </HandlingInstruction> </HandlingInstructions>
xs:sequence HandlingInstruction	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type CodeDescription General Notes LINE ITEM HANDLING INSTRUCTION

Element/Attribute	Annotation
	Examples <HandlingInstructions> <HandlingInstruction> <Code>Stacked</Code> <Description>10</Description> </HandlingInstruction> </HandlingInstructions>
xs:sequence	Occurrence 1 .. 1
Code	Occurrence 0 .. 1 Type xs:string General Notes HANDLING DESCRIPTION CODE
	Applicable Codes NotStacked Cargo Not Stacked Stacked Stacked Cargo
Description	Occurrence 0 .. 1 Type xs:string General Notes HANDLING DESCRIPTION Number of stacked units
TemperatureControl	Occurrence 0 .. 1 Type TemperatureControl General Notes LINE ITEM TEMPERATURE CONTROL
	Examples <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> </TemperatureControl>
Type	Type xs:string
Use	Use required
Uom	Type xs:string
xs:sequence	Occurrence 1 .. 1
Fixed	Occurrence 0 .. 1 Type xs:string
RangeDetails	Occurrence 0 .. 1 Type RangeDetails General Notes LINE ITEM TEMPERATURE RANGE
	Examples <RangeDetails Type="Allowance" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>
Type	Type xs:string Use required General Notes TEMPERATURE RANGE TYPE
	Applicable Codes Allowance Temperature Range Allowance
Uom	Type xs:string General Notes TEMPERATURE RANGE UNIT OF MEASURE
	Applicable Codes CEL Celsius FAH Fahrenheit
xs:sequence	Occurrence 1 .. 1
Minimum	Occurrence 0 .. 1 Type xs:string

Element/Attribute	Annotation
	General Notes MINIMUM TEMPERATAURE
Maximum	Occurrence 0 .. 1 Type xs:string General Notes MAXIMUM TEMPERATAURE
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes LINE ITEM COUNTRY OF ORIGIN Examples <Locations> <LocationGroup> <Location Type="CountryOfOrigin"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DK</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type Location
<i>Type</i>	Type xs:string Use required General Notes LOCATION TYPE
	Applicable Codes
	CountryOfOrigin Line item Country of Origin
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type LocationIdentification
<i>Type</i>	Type xs:string General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes
	ISOCountry ISO Country Code
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER ISO Country Code for Country of Origin
MonetaryAmounts	Occurrence 0 .. 1 Type MonetaryAmountList General Notes LINE ITEM MONETARY AMOUNTS Examples <MonetaryAmounts> <MonetaryAmount Type="LineInvoiceValue"> <Amount>100.01</Amount> <Currency>DKK</Currency> </MonetaryAmount> </MonetaryAmounts>
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded Type MonetaryAmount

Element/Attribute	Annotation
Type	Type xs:string Use required General Notes MONETARY AMOUNT TYPE
xs:sequence	Applicable Codes LineInvoiceValue Line Item Invoice Value
Amount	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type xs:string General Notes MONETARY AMOUNT ISO CURRENCY CODE
ProductIds	Applicable Codes InvoiceValue Occurrence 0 .. 1 Type ProductIdsList General Notes LINE ITEM PRODUCT IDENTIFICATION Examples <ProductIds> <ProductId Type="ProductId"> <ItemId>ITEM ID</ItemId> <ItemType>HarmonizedCode</ItemType> </ProductId> </ProductIds>
xs:sequence	Occurrence 1 .. 1
ProductId	Occurrence 0 .. unbounded Type ProductId
Type	Type xs:string Use required General Notes PRODUCT IDENTIFICATION TYPE
xs:sequence	Applicable Codes ProductId Product Identification
ItemId	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes PRODUCT IDENTIFICATION
ItemType	Occurrence 0 .. 1 Type xs:string General Notes PRODUCT IDENTIFIER TYPE
FreeTextData	Applicable Codes CommodityCode Commodity Code HarmonizedCode Harmonized Tariff Code Occurrence 0 .. 1 Type FreeTextList General Notes LINE ITEM FREE TEXT Examples <FreeTextData> <FreeText Type="GoodsDescription"> <TextLine1>Goods Description Line</TextLine1> </FreeText> <FreeText Type="AdditionalDetails"> <TextLine1>Additional Details Line</TextLine1> </FreeText>



Element/Attribute	Annotation
	Examples </FreeTextData>
xs:sequence	Occurrence 1 .. 1
FreeText	Occurrence 0 .. unbounded
	Type FreeText
Type	Type xs:string
	Use required
	General Notes FREE TEXT TYPE
	Applicable Codes AdditionalDetails Additional Details ConsignmentDetails Consignment Details (Status, RegDate, Remarks, Originater) DeliveryInstructions Delivery Instructions DeliveryRemarks Delivery Remarks GeneralInformation General information GoodsDescription Goods Description MarinePollutant DG Marine Pollutant NatureOfGoods Nature Of Goods PickupInstructions Pickup Instructions ProperShippingName DG Proper Shipping Name ReportInformation Report Information SpecialHandling Special Handling SpecialInstructions Special Instructions StatusRemarks Status Remarks
xs:sequence	Occurrence 1 .. 1
DescriptionCode	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT DESCRIPTION CODE
TextLine1	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 1
TextLine2	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 2
TextLine3	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 3
TextLine4	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 4
TextLine5	Occurrence 0 .. 1
	Type xs:string
	General Notes FREE TEXT LINE 5
Measurements	Occurrence 0 .. 1
	Type MeasurementList
	General Notes LINE ITEM MEASUREMENTS
	Examples <Measurements> <Measurement Type="GrossWeight" Uom="KGM"> <Measure>10.03</Measure> </Measurement> <Measurement Type="NetWeight" Uom="KGM"> <Measure>8.03</Measure> </Measurement> </Measurements>



Element/Attribute	Annotation
	Examples </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.03</Measure> </Measurement> <Measurement Type="LoadingMeters" Uom="MTR"> <Measure>2.05</Measure> </Measurement> <Measurement Type="PalletSpaces" Uom="PLL"> <Measure>5</Measure> </Measurement> </Measurements>
xs:sequence	Occurrence 1 .. 1
Measurement	Occurrence 0 .. unbounded
	Type Measurement
Type	Type xs:string
	Use required
	General Notes MEASUREMENT TYPE
	Applicable Codes GrossWeight Line Item Gross Weight LoadingMeters Line Item Loading Meters NetWeight Line Item Net Weight PalletSpaces Line Item Pallet Spaces Volume Line Item Volume
Uom	Type xs:string
	General Notes MEASUREMENT UNIT OF MEASURE
	Applicable Codes KGM Kilograms MTQ Cubic Meters MTR Linear Meters PLL Pallets
xs:sequence	Occurrence 1 .. 1
Measure	Occurrence 0 .. 1
	Type xs:string
	General Notes MEASUREMENT VALUE
Dimensions	Occurrence 0 .. 1
	Type DimensionsList
	General Notes LINE ITEM DIMENSIONS
	Examples <Dimensions> <Dimension Type="Gross" Uom="MTR"> <Length>0.6</Length> <Width>0.2</Width> <Height>0.8</Height> </Dimension> </Dimensions>
xs:sequence	Occurrence 1 .. 1
Dimension	Occurrence 0 .. unbounded
	Type Dimension
Type	Type xs:string
	Use required
	General Notes DIMENSION TYPE
	Applicable Codes Consignment Consignment Dimensions

Element/Attribute	Annotation
	Applicable Codes GoodsItem Goods Item Dimensions Gross Line Item Gross Dimensions
<i>Uom</i>	Type xs:string General Notes DIMENSIONS UNIT OF MEASURE Applicable Codes CMT Centimeters MTR Meters
xs:sequence	Occurrence 1 .. 1
Length	Occurrence 0 .. 1 Type xs:string General Notes DIMENSION - LENGTH
Width	Occurrence 0 .. 1 Type xs:string General Notes DIMENSION - WIDTH
Height	Occurrence 0 .. 1 Type xs:string General Notes DIMENSION - HEIGHT
NumberOfUnits	Occurrence 0 .. 1 Type xs:string General Notes DIMENSION - NUMBER OF UNITS
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes GOODS ITEM REFERENCES Examples <References> <ReferenceGroup> <Reference Type="OrderLineNumber">10</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="Agreed" CustomFieldType="String">ABCDEFG</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required General Notes GOODS ITEM REFERENCE Applicable Codes PackListLineId Pack List Line Identifier PackageNumber Package Number
Packagelds	Occurrence 0 .. 1 Type Packagelds General Notes PACKAGE IDENTIFICATION AND MARKINGS Examples <Packagelds> <Packageld> <InstructionCode>PackageMarks</InstructionCode>

Element/Attribute	Annotation
Examples <Marks> <ShippingMark>Package1</ShippingMark> <ShippingMark>Package2</ShippingMark> <ShippingMark>Package3</ShippingMark> </Marks> </Packageld> <GoodsIdentities Type="SerialNumber"> <GoodsIdentifier>12345678912345678900</GoodsIdentifier> <GoodsIdentifier>78945612332145698712</GoodsIdentifier> <GoodsIdentifier>85296374125814736979</GoodsIdentifier> </GoodsIdentities> <GoodsIdentities Type="SSCC"> <GoodsIdentifier>SSCC Code</GoodsIdentifier> <GoodsIdentifier>SSCC Code</GoodsIdentifier> <GoodsIdentifier>SSCC Code</GoodsIdentifier> </GoodsIdentities> </Packagelds>	
xs:sequence	Occurrence 1 .. 1
Packageld	Occurrence 0 .. unbounded Type Packageld General Notes PACKAGE MARKS & NUMBERS
xs:sequence	Occurrence 1 .. 1
InstructionCode	Occurrence 1 .. 1 Type xs:string General Notes PACKAGE MARKS TYPE
Applicable Codes PackageMarks Package Marks and Numbers	
Marks	Occurrence 0 .. 1 Type Marks
xs:sequence	Occurrence 1 .. 1
ShippingMark	Occurrence 1 .. unbounded Type xs:string General Notes PACKAGE MARK
GoodsIdentities	Occurrence 0 .. unbounded Type GoodsIdentity General Notes PACKAGE BAR CODES
Type	Type xs:string Use required General Notes TYPE OF IDENTIFIER
Applicable Codes SSCC Serial Shipping Container Code SerialNumber Package/Pallet Serial Number	
xs:sequence	Occurrence 1 .. 1
GoodsIdentifier	Occurrence 1 .. unbounded Type xs:string General Notes GOODS IDENTIFIER SSCC codes should not include the leading "00" qualifier, length of value should be 18 characters
GoodsPlacementIds	Occurrence 0 .. 1 Type GoodsPlacementIds General Notes GOODS PLACEMENT For containerized Sea Freight, container number the line



Element/Attribute	Annotation
	item is packed in
	Examples <GoodsPlacementIds> <GoodsPlacementId>123456789</GoodsPlacementId> </GoodsPlacementIds>
xs:sequence	Occurrence 1 .. 1
GoodsPlacementId	Occurrence 1 .. unbounded Type xs:string General Notes SHIPPING CONTAINER NUMBER
DangerousGoodsDetails	Occurrence 0 .. 1 Type DangerousGoodsDetailList General Notes DANGEROUS / HAZARDOUS GOODS DETAILS Only included if line item contains dangerous/hazardous cargo Examples <DangerousGoodsDetails> <DangerousGoodsDetail> <DangerousGoods> <Regulation>ADR</Regulation> <HazardClass>9</HazardClass> <AdditionalHazardClass>3</AdditionalHazardClass> <HazardVersionId>5</HazardVersionId> <UNDGNumber>3082</UNDGNumber> <FlashPointDescription>FlashDesc</FlashPointDescription> <FlashPointTemperature FlashpointUom="CEL">10</FlashPointTemperature> <DangerLevelCode>III</DangerLevelCode> <EMSNumber>EMS No</EMSNumber> <MFAGNumber>MFAG No</MFAGNumber> <TremCardNumber>Trem No</TremCardNumber> <UpperPlate>Upper</UpperPlate> <LowerPlate>Lower</LowerPlate> <Labels> <Label>Lab1</Label> </Labels> <TunnelCode>E</TunnelCode> <FreeTextData> <FreeText Type="MarinePollutant"> <TextLine>MP</TextLine> </FreeText> <FreeText Type="ProperShippingName"> <TextLine>Proper Shipping Name</TextLine> </FreeText> <FreeText Type="TechnicalName"> <TextLine>Technical Name</TextLine> </FreeText> <FreeText Type="IntTechnicalName"> <TextLine>Int Technical Name</TextLine> </FreeText> <FreeText Type="DGAdditionalInfo"> <TextLine>DG Additional Info Line</TextLine> </FreeText> </FreeTextData> <Measurements> <Measurement Type="NetWeight" Uom="KGM"> <Measure>5.01</Measure> </Measurement>

Element/Attribute	Annotation
	Examples <Measurement Type="ExplosiveWeight" Uom="KGM"> <Measure>2.02</Measure> </Measurement> <Measurement Type="NumberOfPackages" Uom="PKG"> <Measure>3</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.002</Measure> </Measurement> </Measurements> <Quantities> <Quantity Type="NetWeight" Uom="KGM"> <Quantity>5.01</Quantity> </Quantity> </Quantities> </DangerousGoods> </DangerousGoodsDetail> </DangerousGoodsDetails>
xs:sequence	Occurrence 1 .. 1
DangerousGoodsDetail	Occurrence 0 .. unbounded
	Type DangerousGoodsDetail
xs:sequence	Occurrence 1 .. 1
DangerousGoods	Occurrence 0 .. 1
	Type DangerousGoods
	General Notes DANGEROUS GOODS INFORMATION
	Examples <DangerousGoods> <Regulation>ADR</Regulation> <HazardClass>9</HazardClass> <AdditionalHazardClass>3</AdditionalHazardClass> <HazardVersionId>5</HazardVersionId> <UNDGNumber>3082</UNDGNumber> <FlashPointDescription>FlashDesc</FlashPointDescription> <FlashPointTemperature FlashpointUom="CEL">10</FlashPointTemperature> FlashPointTemperature <DangerLevelCode>III</DangerLevelCode> <EMSNumber>EMS No</EMSNumber> <MFAGNumber>MFAG No</MFAGNumber> <TremCardNumber>Trem No</TremCardNumber> <UpperPlate>Upper</UpperPlate> <LowerPlate>Lower</LowerPlate> <Labels> <Label>Lab1</Label> </Labels> <TunnelCode>E</TunnelCode> </DangerousGoods>
xs:sequence	Occurrence 1 .. 1
Regulation	Occurrence 0 .. 1
	Type xs:string
	General Notes DANGEROUS GOODS REGULATION TYPE
	Applicable Codes
	ADR European Road Agreement
	IMO IMO IMDG
HazardClass	Occurrence 0 .. 1
	Type xs:string
	General Notes HAZARDOUS CLASS

Element/Attribute		Annotation
	AdditionalHazardClass	Occurrence 0 .. 1 Type xs:string General Notes ADDITIONAL HAZARDOUS CLASS / SUBRISK
	HazardVersionId	Occurrence 0 .. 1 Type xs:string General Notes HAZARDOUS VERSION ID
	UNDGNumber	Occurrence 0 .. 1 Type xs:string General Notes UNDG NUMBER
	FlashPointDescription	Occurrence 0 .. 1 Type xs:string General Notes FLASH POINT DESCRIPTION
	FlashPointTemperature	Occurrence 0 .. 1 Type extension (xs:string) General Notes FLASHPOINT TEMPERATURE Integer value only
	<i>FlashpointUom</i>	Type xs:string General Notes FLASHPOINT TEMPERATURE UNIT OF MEASURE
		Applicable Codes
		CEL Celsius
		FAH Fahrenheit
	DangerLevelCode	Occurrence 0 .. 1 Type xs:string General Notes DANGER LEVEL CODE / PACKING GROUP
		Applicable Codes
		I Packing Group I - Great danger
		II Packing Group II - Medium danger
		III Packing Group III - Minor danger
	EMSNumber	Occurrence 0 .. 1 Type xs:string General Notes EMERGENCY SCHEDULE NUMBER
	MFAGNumber	Occurrence 0 .. 1 Type xs:string General Notes MEDICAL FIRST AID GUIDE
	TremCardNumber	Occurrence 0 .. 1 Type xs:string General Notes TREMCARD NUMBER
	UpperPlate	Occurrence 0 .. 1 Type xs:string General Notes ORANGE HAZARD PLACARD UPPER PLATE
	LowerPlate	Occurrence 0 .. 1 Type xs:string General Notes ORANGE HAZARD PLACARD LOWER PLATE
	Labels	Occurrence 0 .. 1 General Notes HAZARDOUS LABELS
	<i>xs:sequence</i>	Occurrence 1 .. 1
	Label	Occurrence 1 .. 4 Type xs:string General Notes HAZARDOUS LABEL



Element/Attribute	Annotation										
PackingInstruction	Occurrence 0 .. 1 Type xs:string General Notes PACKING INSTRUCTION										
TransportMeansCode	Occurrence 0 .. 1 Type xs:string General Notes TRANSPORT MEANS CODE										
TunnelCode	Occurrence 0 .. 1 Type xs:string General Notes TUNNEL CODE										
FreeTextData	Occurrence 0 .. 1 Type FreeTextList General Notes DANGEROUS GOODS FREE TEXT Examples <FreeTextData> <FreeText Type="MarinePollutant"> <TextLine>MP</TextLine> </FreeText> <FreeText Type="ProperShippingName"> <TextLine>Proper Shipping Name</TextLine> </FreeText> <FreeText Type="TechnicalName"> <TextLine>Technical Name</TextLine> </FreeText> <FreeText Type="IntTechnicalName"> <TextLine>Int Technical Name</TextLine> </FreeText> <FreeText Type="DGAdditionalInfo"> <TextLine>DG Additional Info Line</TextLine> </FreeText> </FreeTextData>										
xs:sequence	Occurrence 1 .. 1										
FreeText	Occurrence 0 .. unbounded Type FreeText										
Type	Type xs:string Use required General Notes FREE TEXT TYPE Applicable Codes <table> <tr> <td>DGAdditionalInfo</td><td>Additional Dangerous Goods Information</td></tr> <tr> <td>IntTechnicalName</td><td>Dangerous Goods Int. Technical Name</td></tr> <tr> <td>MarinePollutant</td><td>Marine Pollutant</td></tr> <tr> <td>ProperShippingName</td><td>Dangerous Goods Proper Shipping Name</td></tr> <tr> <td>TechnicalName</td><td>Dangerous Goods Technical Name</td></tr> </table>	DGAdditionalInfo	Additional Dangerous Goods Information	IntTechnicalName	Dangerous Goods Int. Technical Name	MarinePollutant	Marine Pollutant	ProperShippingName	Dangerous Goods Proper Shipping Name	TechnicalName	Dangerous Goods Technical Name
DGAdditionalInfo	Additional Dangerous Goods Information										
IntTechnicalName	Dangerous Goods Int. Technical Name										
MarinePollutant	Marine Pollutant										
ProperShippingName	Dangerous Goods Proper Shipping Name										
TechnicalName	Dangerous Goods Technical Name										
xs:sequence	Occurrence 1 .. 1										
DescriptionCode	Occurrence 0 .. 1 Type xs:string General Notes DG FREE TEXT DESCRIPTION CODE										
TextLine1	Occurrence 0 .. 1 Type xs:string General Notes DG FREE TEXT LINE 1										
TextLine2	Occurrence 0 .. 1 Type xs:string										

Element/Attribute	Annotation						
	General Notes DG FREE TEXT LINE 2						
TextLine3	Occurrence 0 .. 1 Type xs:string General Notes DG FREE TEXT LINE 3						
TextLine4	Occurrence 0 .. 1 Type xs:string General Notes DG FREE TEXT LINE 4						
TextLine5	Occurrence 0 .. 1 Type xs:string General Notes DG FREE TEXT LINE 5						
Measurements	Occurrence 0 .. 1 Type MeasurementList General Notes DANGEROUS GOODS MEASUREMENTS Examples <Measurements> <Measurement Type="NetWeight" Uom="KGM"> <Measure>5.01</Measure> </Measurement> <Measurement Type="ExplosiveWeight" Uom="KGM"> <Measure>2.02</Measure> </Measurement> <Measurement Type="NumberOfPackages" Uom="PKG"> <Measure>3</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.002</Measure> </Measurement> </Measurements>						
xs:sequence	Occurrence 1 .. 1						
Measurement	Occurrence 0 .. unbounded Type Measurement						
Type	Type xs:string Use required General Notes MEASUREMENT TYPE Applicable Codes <table> <tr> <td>ExplosiveWeight</td><td>Dangerous Goods Explosive Weight</td></tr> <tr> <td>LoadingMeters</td><td>Loading Meters</td></tr> <tr> <td>NetNetWeight</td><td>Dangerous Goods Net Weight</td></tr> </table>	ExplosiveWeight	Dangerous Goods Explosive Weight	LoadingMeters	Loading Meters	NetNetWeight	Dangerous Goods Net Weight
ExplosiveWeight	Dangerous Goods Explosive Weight						
LoadingMeters	Loading Meters						
NetNetWeight	Dangerous Goods Net Weight						
Uom	Type xs:string General Notes MEASUREMENT UNIT OF MEASURE Applicable Codes <table> <tr> <td>KGM</td><td>Kilograms</td></tr> <tr> <td>PCE</td><td>Pieces</td></tr> </table>	KGM	Kilograms	PCE	Pieces		
KGM	Kilograms						
PCE	Pieces						
xs:sequence	Occurrence 1 .. 1						
Measure	Occurrence 0 .. 1 Type xs:string General Notes MEASURE						
Quantities	Occurrence 0 .. 1 Type QuantitiesList General Notes DANGEROUS GOODS QUANTITIES Examples <Quantities>						



Element/Attribute	Annotation
	Examples <Quantity Type="NetWeight" Uom="KGM"> <Quantity>5.01</Quantity> </Quantities>
xs:sequence	Occurrence 1 .. 1
Quantity	Occurrence 0 .. unbounded
Type	Quantity
Type	xs:string
Use	required
General Notes	QUANTITY TYPE
	Applicable Codes
	NumberOfPackages Number of Dangerous Goods Packages
Uom	Type xs:string
General Notes	QUANTITY UNIT OF MEASURE
xs:sequence	Occurrence 1 .. 1
Quantity	Occurrence 0 .. 1
Type	xs:string
General Notes	QUANTITY
ContainerNumber	Occurrence 0 .. 1
Type	xs:string
General Notes	SHIPPING CONTAINER NUMBER
	Examples <ContainerNumber>ADFC5689</ContainerNumber>
EquipmentUnits	Occurrence 0 .. 1
Type	EquipmentUnitList
General Notes	EQUIPMENT INFORMATION
xs:sequence	Occurrence 1 .. 1
EquipmentUnit	Occurrence 0 .. unbounded
Type	EquipmentUnit
General Notes	EQUIPMENT UNIT DETAILS
	Examples For containerized sea freight: <EquipmentUnit> <EquipmentType> <Type>Container</Type> <UnitId>MSCU1234567</UnitId> <SizeTypeCode>40GP</SizeTypeCode> </EquipmentType> <SealIds> <Seal> <SealId>Seal1</SealId> <SealParty>Shipper</SealParty> </Seal> </SealIds> </EquipmentUnit> For EUR pallet road freight: <EquipmentUnit> <EquipmentType> <Type>EFP</Type> </EquipmentType>



Element/Attribute	Annotation														
	Examples <NumberOfUnits>3</NumberOfUnits> </EquipmentUnit>														
xs:sequence	Occurrence 1 .. 1														
EquipmentType	Occurrence 0 .. 1 Type EquipmentType General Notes EQUIPMENT TYPE INFORMATION Examples <EquipmentType> <Type>Container</Type> <UnitId>UNIT ID</UnitId> <SizeTypeCode>12AB</SizeTypeCode> <ISOCODE>13B1</ISOCODE> <PackingMode>FCL</PackingMode> <FullOrEmptyIndicator>Full</FullOrEmptyIndicator> </EquipmentType>														
xs:sequence	Occurrence 1 .. 1														
Type	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT TYPE Applicable Codes <table> <tr> <td>Container</td><td>Shipping Container</td></tr> <tr> <td>EFF</td><td>Euro Flat Pallet</td></tr> <tr> <td>EUR</td><td>Euro Pallet</td></tr> </table>	Container	Shipping Container	EFF	Euro Flat Pallet	EUR	Euro Pallet								
Container	Shipping Container														
EFF	Euro Flat Pallet														
EUR	Euro Pallet														
UnitId	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER NUMBER														
SizeTypeCode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER SIZE AND TYPE DSV specified Container Type for Shipping Container Applicable Codes <table> <tr> <td>20GP</td><td>20 ft General Purpose</td></tr> <tr> <td>20RE</td><td>20 ft Reefer</td></tr> <tr> <td>40GP</td><td>40 ft General Purpose</td></tr> <tr> <td>40HC</td><td>40 ft High Cube</td></tr> <tr> <td>40NOR</td><td>40 ft high Cube, self powered Reefer</td></tr> <tr> <td>40RE</td><td>40 ft Reefer</td></tr> <tr> <td>40REHC</td><td>40 ft High Cube Reefer</td></tr> </table>	20GP	20 ft General Purpose	20RE	20 ft Reefer	40GP	40 ft General Purpose	40HC	40 ft High Cube	40NOR	40 ft high Cube, self powered Reefer	40RE	40 ft Reefer	40REHC	40 ft High Cube Reefer
20GP	20 ft General Purpose														
20RE	20 ft Reefer														
40GP	40 ft General Purpose														
40HC	40 ft High Cube														
40NOR	40 ft high Cube, self powered Reefer														
40RE	40 ft Reefer														
40REHC	40 ft High Cube Reefer														
ISOCODE	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER ISO CODE														
PackingMode	Occurrence 0 .. 1 Type xs:string Applicable Codes <table> <tr> <td>FCL</td><td>Full Container Load</td></tr> <tr> <td>LCL</td><td>Less than full Container Load</td></tr> </table>	FCL	Full Container Load	LCL	Less than full Container Load										
FCL	Full Container Load														
LCL	Less than full Container Load														
EquipmentSizeDescription	Occurrence 0 .. 1 Type xs:string														
FullOrEmptyIndicator	Occurrence 0 .. 1 Type xs:string General Notes FULL OR EMPTY INDICATOR														



Element/Attribute	Annotation
	Applicable Codes Empty Empty Full Full
NumberOfUnits	Occurrence 0 .. 1 Type xs:decimal General Notes NUMBER OF UNITS For Road freight pallets Only used for Returnable items. Examples <NumberOfUnits>1</NumberOfUnits>
Measurements	Occurrence 0 .. 1 Type MeasurementList General Notes EQUIPMENT MEASUREMENTS Examples <Measurements> <Measurement Type="Volume" Uom="KGM"> <Measure>12.5</Measure> </Measurement> </Measurements>
xs:sequence	Occurrence 1 .. 1
Measurement	Occurrence 0 .. unbounded Type Measurement
Type	Type xs:string Use required General Notes EQUIPMENT MEASUREMENT TYPE
	Applicable Codes TareWeight Volume Weight
Uom	Type xs:string General Notes EQUIPMENT MEASUREMENT UNIT OF MEASURE
	Applicable Codes KGM Kilograms MTQ Cubic metres
xs:sequence	Occurrence 1 .. 1
Measure	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MEASUREMENT
Dimensions	Occurrence 0 .. 1 Type DimensionsList General Notes EQUIPMENT DIMENSIONS Examples <Dimensions Type="Container" Uom="MTR"> <Length>2.5</Length> <Width>5</Width> <Height>3</Height> <Dimension> </Dimension> </Dimensions>
xs:sequence	Occurrence 1 .. 1
Dimension	Occurrence 0 .. unbounded Type Dimension

Element/Attribute	Annotation
<i>Type</i>	Type xs:string Use required General Notes EQUIPMENT DIMENSION TYPE
	Applicable Codes Container
<i>Uom</i>	Type xs:string General Notes EQUIPMENT DIMENSION UNIT OF MEASURE
	Applicable Codes MTR
xs:sequence	Occurrence 1 .. 1
Length	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION LENGTH
Width	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION WIDTH
Height	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT DIMENSION HEIGHT
SealIds	Occurrence 0 .. 1 Type SealList General Notes SEAL INFORMATION FOR SHIPPING CONTAINERS Examples <SealIds> <Seal> <SealId>XX-12345678</SealId> </Seal> </SealIds>
xs:sequence	Occurrence 1 .. 1
Seal	Occurrence 0 .. unbounded Type Seal
xs:sequence	Occurrence 1 .. 1
SealId	Occurrence 0 .. 1 Type xs:string General Notes SEAL NUMBER
SealParty	Occurrence 0 .. 1 Type xs:string General Notes SEALING PARTY
	Applicable Codes Shipper Shipper Sealing Party
References	Occurrence 0 .. 1 Type ReferenceGroupList General Notes EQUIPMENT REFERENCES Examples <References> <ReferenceGroup> <Reference Type="PackingMode">FCL</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="DeliveryMode">FCL</Reference> </ReferenceGroup>

Element/Attribute	Annotation
	Examples </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded
	Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1
	Type Reference
	General Notes EQUIPMENT REFERENCE
Type	Type xs:string Use required General Notes EQUIPMENT REFERENCE TYPE
Applicable Codes	
DeliveryMode	Container Delivery Mode
InterimUnitId	
PackingMode	Container Packing Mode
VerificationMethod	
VerificationStatus	
Dates	Occurrence 0 .. 1 Type DateList General Notes CONTAINER DATES
	Examples <Dates> <Date Format="DateTimeSec" Type="EstimatedCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="RequestedCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledCollection"> <DateTime>20250818120500</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedDelivery"> <DateTime>20250802124800</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDelivery"> <DateTime>20250823090200</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedFullPickup"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLOnBoardVessel"> <DateTime>20250806013500</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLUnloadFromVessel"> <DateTime>20250815135900</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateIn"> <DateTime>20250801085600</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateOut"> <DateTime>20250818101000</DateTime> </Date> <Date Format="DateTimeSec"

Element/Attribute	Annotation
	Examples Type="ContainerParkEmptyPickupGateOut"> <DateTime>20250830121700</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
<i>Type</i>	Type Date
	Type xs:string
	Use required
	General Notes CONTAINER DATE TYPE
	Applicable Codes
<i>Format</i>	VerifiedDate
	Type xs:string
	Use required
	General Notes CONTAINER DATE FORMAT
	Applicable Codes
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes CONTAINER DATE/TIME
TransportMovements	Occurrence 0 .. 1
	Type TransportMovementList
	General Notes EQUIPMENT TRANSPORT MOVEMENTS
	Examples <TransportMovements> <TransportMovement Type="DeliveryMode"> <Code>CFS</Code> <Description>DSC</Description> </TransportMovement> </TransportMovements>
xs:sequence	Occurrence 1 .. 1
TransportMovement	Occurrence 0 .. unbounded
<i>Type</i>	Type CodeDescription
	Type xs:string
	Use optional
	Applicable Codes
	DeliveryMode
xs:sequence	Occurrence 1 .. 1
Code	Occurrence 0 .. 1
	Type xs:string
	General Notes EQUIPMENT MOVEMENT CODE
	Applicable Codes
	CFS/CFS
	CFS/CY
	CFS/DR
	CY/CFS
	CY/CY
	CY/DR
	DR/CFS
	DR/CY
	DR/DR



Element/Attribute	Annotation
	Applicable Codes FCL/FCL FCL/LCL LCL/FCL LCL/LCL RO/RO
Description	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT MOVEMENT DESCRIPTION
TransportServices	Occurrence 0 .. 1 Type ServiceGroupList General Notes EQUIPMENT UNIT TRANSPORT SERVICES Examples <pre> <TransportServices> <ServiceGroup> <TransportService> <ServiceCode>FCL</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService> </ServiceGroup> <ServiceGroup> <TransportService> <ServiceCode>STD</ServiceCode> <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData> <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date> </Dates> <Parties> <Party> <PartyDetails Role="Contractor"> <Id>123456789</Id> <Assignor>DSV</Assignor> <PartyName>AXDFR</PartyName> <AddressLine1>XYZ</AddressLine1> <AddressLine2>ABC</AddressLine2> <CityName>CITY NAME</CityName> <PostCode>PO CODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>CONTACT NAME</Name> <Phone>123456789</Phone> </Contact> </Party> </Parties> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References> </TransportService> </pre>

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation
	Examples </ServiceGroup> </TransportServices>
xs:sequence	Occurrence 1 .. 1
ServiceGroup	Occurrence 0 .. unbounded Type ServiceGroup
xs:sequence	Occurrence 1 .. 1
TransportService	Occurrence 0 .. 1 Type TransportService Examples <TransportService> <ServiceCode>LTL</ServiceCode> </TransportService>
xs:sequence	Occurrence 1 .. 1
ServiceCode	Occurrence 0 .. 1 Type xs:string
FreeTextData	Occurrence 0 .. 1 Type FreeTextList Examples <FreeTextData> <FreeText Type="ServiceDescription"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
xs:sequence	Occurrence 1 .. 1
FreeText	Occurrence 0 .. unbounded Type FreeText Type xs:string Use required
<i>Type</i>	
xs:sequence	Occurrence 1 .. 1
TextLine1	Occurrence 0 .. 1 Type xs:string
FreeText <Notes>	Occurrence 0 .. unbounded Type FreeText Examples <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
<i>Type</i>	Type xs:string Use required
xs:sequence	Occurrence 1 .. 1
TextLine1	Occurrence 0 .. 1 Type xs:string
Dates	Occurrence 0 .. 1 Type DateList Examples <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date>

Element/Attribute	Annotation
	Examples </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
<i>Type</i>	Type xs:string
<i>Format</i>	Use required
xs:sequence	Type xs:string
DateTime	Use required
Parties	Occurrence 1 .. 1
	Occurrence 0 .. 1
	Type xs:string
	Occurrence 0 .. 1
	Type PartiesList
	Examples <Parties> <Party> <PartyDetails Role="Contractor"> <Id>123456789</Id> <Assignor>DSV</Assignor> <PartyName>AXDFR</PartyName> <AddressLine1>XYZ</AddressLine1> <AddressLine2>ABC</AddressLine2> <CityName>CITY NAME</CityName> <PostCode>PO CODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>CONTACT NAME</Name> <Phone>123456789</Phone> </Contact> </Party> </Parties>
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded
	Type Party
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1
	Type PartyDetails
<i>Role</i>	Type xs:string
	Use required
<i>AddressOverride</i>	Type xs:boolean
	Default false
	Use optional
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1
	Type xs:string
Assignor	Occurrence 0 .. 1
	Type xs:string
PartyName	Occurrence 0 .. 1
	Type xs:string
AddressLine1	Occurrence 0 .. 1
	Type xs:string
AddressLine2	Occurrence 0 .. 1
	Type xs:string
AddressLine3	Occurrence 0 .. 1
	Type xs:string

Element/Attribute		Annotation	
CityName	Occurrence	0 .. 1	
	Type	xs:string	
State	Occurrence	0 .. 1	
	Type	xs:string	
PostCode	Occurrence	0 .. 1	
	Type	xs:string	
CountryCode	Occurrence	0 .. 1	
	Type	xs:string	
Locations	Occurrence	0 .. 1	
	Type	LocationGroupList	
xs:sequence	Occurrence	1 .. 1	
LocationGroup	Occurrence	0 .. unbounded	
	Type	LocationGroup	
xs:sequence	Occurrence	1 .. 1	
Location	Occurrence	0 .. 1	
	Type	Location	
Type	Type	xs:string	
Use	Use	required	
xs:sequence	Occurrence	1 .. 1	
LocationIdentification	Occurrence	1 .. unbounded	
	Type	LocationIdentification	
Type	Type	xs:string	
xs:sequence	Occurrence	1 .. 1	
LocationIdentifier	Occurrence	0 .. 1	
	Type	xs:string	
LocationName	Occurrence	0 .. 1	
	Type	xs:string	
Contact	Occurrence	0 .. unbounded	
	Type	Contact	
Type	Type	xs:string	
Use	Use	required	
xs:sequence	Occurrence	1 .. 1	
ContactId	Occurrence	0 .. 1	
	Type	xs:string	
Name	Occurrence	0 .. 1	
	Type	xs:string	
Phone	Occurrence	0 .. 1	
	Type	xs:string	
Mobile	Occurrence	0 .. 1	
	Type	xs:string	
Fax	Occurrence	0 .. 1	
	Type	xs:string	
Email	Occurrence	0 .. 1	
	Type	xs:string	
References	Occurrence	0 .. 1	
	Type	ReferenceGroupList	
xs:sequence	Occurrence	1 .. 1	
ReferenceGroup	Occurrence	0 .. unbounded	
	Type	ReferenceGroup	
xs:sequence	Occurrence	1 .. 1	
Reference	Occurrence	0 .. 1	
	Type	Reference	
Type	Type	xs:string	
Use	Use	required	
Identifier	Type	xs:string	
	Use	optional	

Bold = Element, Italic = Attribute, Grey = Group

DSV public

DSV SHIPMENT XML OUT; v2.0

Issue date: 2026-08-28

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 68 / 73

Element/Attribute	Annotation
<i>CustomFieldType</i>	Type xs:string Use optional
References	Occurrence 0 .. 1 Type ReferenceGroupList Examples <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference
Type	Type xs:string Use required
Identifier	Type xs:string Use optional
CustomFieldType	Type xs:string Use optional
Date	Occurrence 0 .. 1 Type Date
Type	Type xs:string Use required
Format	Type xs:string Use required
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type xs:string
TemperatureControl	Occurrence 0 .. 1 Type TemperatureControl General Notes CONTAINER TEMPERATURE Examples <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> <HumidityPercentage>25</HumidityPercentage> </TemperatureControl>
Type	Type xs:string Use required General Notes TEMPERATURE CONTROL TYPE
Uom	Applicable Codes Container Type xs:string General Notes TEMPERATURE UNIT OF MEASURE Applicable Codes CEL Celsius FAH Fahrenheit
xs:sequence	Occurrence 1 .. 1
Fixed	Occurrence 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

DSV public

Element/Attribute	Annotation
	General Notes TEMPERATURE
HumidityPercentage	Occurrence 0 .. 1 Type xs:string General Notes HUMIDITY PERCENTAGE
RangeDetails	Occurrence 0 .. 1 Type RangeDetails General Notes RANGE DETAILS Examples <RangeDetails Type="Container" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>
<i>Type</i>	Type xs:string Use required General Notes RANGE DETAILS TYPE
	Applicable Codes
	Container
<i>Uom</i>	Type xs:string General Notes TEMPERATURE UNIT OF MEASURE
xs:sequence	Occurrence 1 .. 1
Minimum	Occurrence 0 .. 1 Type xs:string
Maximum	Occurrence 0 .. 1 Type xs:string
Parties	Occurrence 0 .. 1 Type PartiesList General Notes EQUIPMENT PARTY INFORMATION
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded Type Party
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1 Type PartyDetails General Notes PARTY DETAILS Examples <PartyDetails Role="VGM"> <Id>VGMID</Id> <Assignor>DSV</Assignor> <PartyName>VGM Name</PartyName> <AddressLine1>VGM Addr Line 1</AddressLine1> <AddressLine2>VGM Addr Line 2</AddressLine2> <AddressLine3>VGM Addr Line 3</AddressLine3> <CityName>VGM City</CityName> <State>VGM State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails>
<i>Role</i>	Type xs:string Use required General Notes PARTY ROLE
xs:sequence	Occurrence 1 .. 1



Element/Attribute		Annotation	
- Id - Assignor - PartyName - AddressLine1 - AddressLine2 - AddressLine3 - CityName - State - PostCode - CountryCode		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
		Occurrence	0 .. 1
		Type	xs:string
- Locations - xs:sequence - LocationGroup - xs:sequence - Location - Type - xs:sequence - LocationIdentification - Type - xs:sequence - LocationIdentifier		Occurrence	0 .. 1
		Type	LocationGroupList
		General Notes PARTY LOCATION	
		Examples	
		<Locations>	
		<LocationGroup>	
		<Location Type="VerifiedBy">	
		<LocationIdentification Type="UN">	
		<LocationIdentifier>DKHOR</LocationIdentifier>	
		</LocationIdentification>	
		</Location>	
		</LocationGroup>	
		</Locations>	
		Occurrence	1 .. 1
		Occurrence	0 .. unbounded
		Type	LocationGroup
		Occurrence	1 .. 1
		Occurrence	0 .. 1
		Type	Location
		Type	xs:string
		Use	required
		General Notes PARTY LOCATION TYPE	
		Applicable Codes	
		PhysicalLocation	
		VerifiedBy	
		Occurrence	1 .. 1
		Occurrence	1 .. unbounded
		Type	LocationIdentification
		Type	xs:string
		General Notes PARTY LOCATION IDENTIFIER TYPE	
		Applicable Codes	
		UN UN location code	
		Occurrence	1 .. 1
		Occurrence	0 .. 1
		Type	xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

DSV public

DSV SHIPMENT XML OUT; v2.0

Issue date: 2026-08-28

Print date: 2026-08-28

Generated by GEFEG.FX

Page: 71 / 73



Element/Attribute	Annotation
	General Notes PARTY LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1 Type xs:string General Notes PARTY LOCATION NAME
Contact	Occurrence 0 .. unbounded Type Contact General Notes PARTY CONTACT DETAILS Examples <Contact Type="VerifiedBy"> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
Type	Type xs:string Use required General Notes PARTY CONTACT TYPE
xs:sequence	Occurrence 1 .. 1
ContactId	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT ID
Name	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT PHONE NUMBER
Mobile	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT MOBILE NUMBER
Fax	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT FAX NUMBER
Email	Occurrence 0 .. 1 Type xs:string General Notes PARTY CONTACT E-MAIL ADDRESS
References	Occurrence 0 .. 1 Type ReferenceGroupList Examples <References> <ReferenceGroup> <Reference Type="VAT">VatNo</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type Reference

Bold = Element, Italic = Attribute, Grey = Group

DSV public



Element/Attribute	Annotation
Type	Typexs:string Userequired
	Applicable Codes
	VATVAT Number
Flags	Occurence0 .. 1 TypeFlagList Examples <Flags> <Flag Type="IsSealOk">OK</Flag> </Flags>
xs:sequence	Occurence1 .. 1
Flag	Occurence0 .. unbounded TypeFlag
Type	Typexs:string Applicable Codes IsDamaged IsSealOk IsShipperOwned