



Message Implementation Guideline

## **DSV\_ShipmentMessage**

Model: DSV\_STD\_XML\_SHIPMENTMESSAGE\_V2\_OUT  
Version: v2.0  
Issue date: 2025-08-29  
Author: DSV A/S, EDI

## Structure

Occurrence	Element/Attribute
	<b>DSV_ShipmentMessage</b>
1 .. 1	xs:sequence
<b>1 .. 1</b>	<b>Header</b>
1 .. 1	xs:sequence
1 .. 1	<b>MessageId</b>
1 .. 1	<b>SenderId</b>
1 .. 1	<b>ReceiverId</b>
<b>1 .. 1</b>	<b>DocumentDate</b>
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
1 .. 1	<b>DocumentCode</b>
1 .. 1	<b>Function</b>
1 .. 1	<b>Version</b>
<b>1 .. 1</b>	<b>Shipment</b>
1 .. 1	xs:sequence
0 .. 1	<b>ShipmentId</b>
optional	Type
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Date</b>
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>TransportServices</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ServiceGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>TransportService</b>
1 .. 1	xs:sequence
0 .. 1	<b>ServiceCode</b>
0 .. 1	<b>PriorityCode</b>
<b>0 .. unbounded</b>	<b>ServiceGroup &lt;Services&gt;</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>TransportService</b>
1 .. 1	xs:sequence
0 .. 1	<b>ServiceCode</b>
<b>0 .. 1</b>	<b>FreeTextData</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>FreeText</b>
required	Type
1 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Date</b>
required	Type

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
required	<i>Format</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. 1</b>	<b>PartyDetails</b>
required	<i>Role</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	<b>Id</b>
0 .. 1	<b>Assignor</b>
0 .. 1	<b>PartyName</b>
0 .. 1	<b>AddressLine1</b>
0 .. 1	<b>AddressLine2</b>
0 .. 1	<b>AddressLine3</b>
0 .. 1	<b>CityName</b>
0 .. 1	<b>State</b>
0 .. 1	<b>PostCode</b>
0 .. 1	<b>CountryCode</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. 1</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	<i>xs:sequence</i>
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	<i>Type</i>
0 .. 1	<i>xs:sequence</i>
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. unbounded</b>	<b>Contact</b>
required	<i>Type</i>
1 .. 1	<i>xs:sequence</i>
0 .. 1	<b>ContactId</b>
0 .. 1	<b>Name</b>
0 .. 1	<b>Phone</b>
0 .. 1	<b>Mobile</b>
0 .. 1	<b>Fax</b>
0 .. 1	<b>Email</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	<i>xs:sequence</i>
0 .. 1	<b>Reference</b>
required	<i>Type</i>
optional	<i>Identifier</i>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	<i>xs:sequence</i>
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
optional	<i>Identifier</i>
<b>0 .. 1</b>	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>MonetaryAmounts</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>MonetaryAmount</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>Amount</b>
0 .. 1	<b>Currency</b>
<b>0 .. 1</b>	<b>FreeTextData</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>FreeText</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>DescriptionCode</b>
0 .. 1	<b>TextLine1</b>
0 .. 1	<b>TextLine2</b>
0 .. 1	<b>TextLine3</b>
0 .. 1	<b>TextLine4</b>
0 .. 1	<b>TextLine5</b>
<b>0 .. 1</b>	<b>ControlTotals</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ControlTotal</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Quantity</b>
<b>0 .. 1</b>	<b>Documents</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Document</b>
1 .. 1	xs:sequence
0 .. 1	<b>DocumentCode</b>
0 .. 1	<b>DocumentCopies</b>
0 .. 1	<b>DocumentOriginals</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
	<i>Type</i>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	└ LocationIdentifier
<b>0 .. 1</b>	<b>TermsOfDelivery</b>
1 .. 1	└ xs:sequence
<b>0 .. 1</b>	<b>Terms</b>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>TermsCode</b>
0 .. 1	└ <b>Codeld</b>
<b>0 .. unbounded</b> required	<b>Location</b>
1 .. 1	└ <i>Type</i>
1 .. 1	└ xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	└ <i>Type</i>
0 .. 1	└ xs:sequence
0 .. 1	└ <b>LocationIdentifier</b>
0 .. 1	└ <b>LocationName</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	└ xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>Reference</b>
required	└ <i>Type</i>
optional	└ <i>CustomFieldType</i>
<b>0 .. 1</b>	<b>Date</b>
required	└ <i>Type</i>
required	└ <i>Format</i>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>DateTime</b>
<b>0 .. 1</b>	<b>Requirements</b>
1 .. 1	└ xs:sequence
<b>0 .. unbounded</b>	<b>Requirement</b>
1 .. 1	└ xs:sequence
<b>0 .. 1</b>	<b>GovernmentalRequirements</b>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>TransportMovementCode</b>
0 .. 1	└ <b>InvolvementCode</b>
<b>0 .. 1</b>	<b>Documents</b>
1 .. 1	└ xs:sequence
<b>0 .. unbounded</b>	<b>Document</b>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>DocumentCode</b>
<b>0 .. 1</b>	<b>ChargeMethodology</b>
1 .. 1	└ xs:sequence
<b>0 .. unbounded</b>	<b>PaymentInstructions</b>
1 .. 1	└ xs:sequence
<b>0 .. 1</b>	<b>PaymentInstruction</b>
1 .. 1	└ xs:sequence
0 .. 1	└ <b>PaymentCode</b>
<b>0 .. 1</b>	<b>TransportStages</b>
1 .. 1	└ xs:sequence
<b>0 .. unbounded</b>	<b>TransportStage</b>
1 .. 1	└ xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
<b>0 .. 1</b> required	<b>Stage</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>ModeOfTransport</b>
0 .. 1	<b>TransportId</b>
0 .. 1	<b>CarrierId</b>
0 .. 1	<b>CarrierName</b>
0 .. 1	<b>TransportType</b>
0 .. 1	<b>TransportMeansName</b>
0 .. 1	<b>TransportMeansNationality</b>
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>TransportServices</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ServiceGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>TransportService</b>
1 .. 1	xs:sequence
0 .. 1	<b>ServiceCode</b>
0 .. 1	<b>PriorityCode</b>
<b>0 .. unbounded</b>	<b>ServiceGroup &lt;Services&gt;</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>TransportService</b>
1 .. 1	xs:sequence
0 .. 1	<b>ServiceCode</b>
<b>0 .. 1</b>	<b>FreeTextData</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>FreeText</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	Type
optional	Identifier
optional	CustomFieldType
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>PartyDetails</b>
required	Role
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Location</b>
required	Type
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
<b>0 .. unbounded</b>	<b>Contact</b>
required	Type
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	Type
optional	Identifier
optional	CustomFieldType
<b>0 .. unbounded</b>	<b>Party &lt;DSVOperator&gt;</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
<b>0 .. 1</b> required	<b>PartyDetails</b>
	<i>Role</i>
<b>0 .. unbounded</b> required	<b>Contact</b>
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>Name</b>
0 .. 1	<b>Phone</b>
0 .. 1	<b>Email</b>
<b>0 .. 1</b>	<b>GoodsItems</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>GoodsItem</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Item</b>
1 .. 1	xs:sequence
0 .. 1	<b>Sequence</b>
0 .. 1	<b>ItemNumber</b>
0 .. 1	<b>PackageQty</b>
0 .. 1	<b>PackageType</b>
<b>0 .. 1</b>	<b>HandlingInstructions</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>HandlingInstruction</b>
1 .. 1	xs:sequence
0 .. 1	<b>Code</b>
0 .. 1	<b>Description</b>
<b>0 .. 1</b> required	<b>TemperatureControl</b>
	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Fixed</b>
<b>0 .. 1</b> required	<b>RangeDetails</b>
	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Minimum</b>
0 .. 1	<b>Maximum</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b> required	<b>Location</b>
1 .. 1	<i>Type</i>
	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
<b>0 .. 1</b>	<b>MonetaryAmounts</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>MonetaryAmount</b>
	<i>Type</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	<b>Amount</b>
0 .. 1	<b>Currency</b>
0 .. 1	<b>ProductIds</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>ProductId</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>ItemId</b>
0 .. 1	<b>ItemType</b>
0 .. 1	<b>FreeTextData</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>FreeText</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>DescriptionCode</b>
0 .. 1	<b>TextLine1</b>
0 .. 1	<b>TextLine2</b>
0 .. 1	<b>TextLine3</b>
0 .. 1	<b>TextLine4</b>
0 .. 1	<b>TextLine5</b>
0 .. 1	<b>Measurements</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>Measurement</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Measure</b>
0 .. 1	<b>Dimensions</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>Dimension</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Length</b>
0 .. 1	<b>Width</b>
0 .. 1	<b>Height</b>
0 .. 1	<b>NumberOfUnits</b>
0 .. 1	<b>References</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
0 .. 1	<b>Packagelds</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>Packageld</b>
1 .. 1	xs:sequence
1 .. 1	<b>InstructionCode</b>
0 .. 1	<b>Marks</b>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. unbounded	ShippingMark
0 .. unbounded required	GoodsIdentities
1 .. 1	Type
1 .. unbounded	xs:sequence
0 .. 1	GoodsIdentifier
1 .. 1	GoodsPlacementIds
1 .. 1	xs:sequence
1 .. unbounded	GoodsPlacementId
0 .. 1	DangerousGoodsDetails
1 .. 1	xs:sequence
0 .. unbounded	DangerousGoodsDetail
1 .. 1	xs:sequence
0 .. 1	DangerousGoods
1 .. 1	xs:sequence
0 .. 1	Regulation
0 .. 1	HazardClass
0 .. 1	AdditionalHazardClass
0 .. 1	HazardVersionId
0 .. 1	UNDGNumber
0 .. 1	FlashPointDescription
0 .. 1	FlashPointTemperature
	FlashpointUom
0 .. 1	DangerLevelCode
0 .. 1	EMSNumber
0 .. 1	MFAGNumber
0 .. 1	TremCardNumber
0 .. 1	UpperPlate
0 .. 1	LowerPlate
0 .. 1	Labels
1 .. 1	xs:sequence
1 .. 4	Label
0 .. 1	PackingInstruction
0 .. 1	TransportMeansCode
0 .. 1	TunnelCode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded required	FreeText
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	DescriptionCode
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded required	Measurement
	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Measure

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	<b>Quantities</b>
1 .. 1	xs:sequence
0 .. unbounded required	<b>Quantity</b>
	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	<b>Quantity</b>
0 .. 1	<b>ContainerNumber</b>
0 .. 1	<b>EquipmentUnits</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>EquipmentUnit</b>
1 .. 1	xs:sequence
0 .. 1	<b>EquipmentType</b>
1 .. 1	xs:sequence
0 .. 1	<b>Type</b>
0 .. 1	<b>UnitId</b>
0 .. 1	<b>SizeTypeCode</b>
0 .. 1	<b>ISOCODE</b>
0 .. 1	<b>PackingMode</b>
0 .. 1	<b>EquipmentSizeDescription</b>
0 .. 1	<b>FullOrEmptyIndicator</b>
0 .. 1	<b>NumberOfUnits</b>
0 .. 1	<b>Measurements</b>
1 .. 1	xs:sequence
0 .. unbounded required	<b>Measurement</b>
	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	<b>Measure</b>
0 .. 1	<b>Dimensions</b>
1 .. 1	xs:sequence
0 .. unbounded required	<b>Dimension</b>
	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	<b>Length</b>
0 .. 1	<b>Width</b>
0 .. 1	<b>Height</b>
0 .. 1	<b>SealIds</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>Seal</b>
1 .. 1	xs:sequence
0 .. 1	<b>SealId</b>
0 .. 1	<b>SealParty</b>
0 .. 1	<b>References</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1 required	<b>Reference</b>
	Type
0 .. 1	<b>Dates</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required required	<b>Date</b>
	<i>Type</i>
	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>TransportMovements</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> optional	<b>TransportMovement</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>Code</b>
0 .. 1	<b>Description</b>
<b>0 .. 1</b>	<b>TransportServices</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ServiceGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>TransportService</b>
1 .. 1	xs:sequence
0 .. 1	<b>ServiceCode</b>
<b>0 .. 1</b>	<b>FreeTextData</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>FreeText</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
<b>0 .. unbounded</b> required	<b>FreeText &lt;Notes&gt;</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required required	<b>Date</b>
1 .. 1	<i>Type</i>
0 .. 1	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	xs:sequence
<b>0 .. 1</b> required optional	<b>PartyDetails</b>
1 .. 1	<i>Role</i>
0 .. 1	<i>AddressOverride</i>
0 .. 1	xs:sequence
0 .. 1	<b>Id</b>
0 .. 1	<b>Assignor</b>
0 .. 1	<b>PartyName</b>
0 .. 1	<b>AddressLine1</b>
0 .. 1	<b>AddressLine2</b>
0 .. 1	<b>AddressLine3</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Location</b>
required	Type
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
<b>0 .. unbounded</b>	<b>Contact</b>
required	Type
1 .. 1	xs:sequence
0 .. 1	ContactId
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Mobile
0 .. 1	Fax
0 .. 1	Email
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
optional	Identifier
optional	CustomFieldType
<b>0 .. 1</b>	<b>Date</b>
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
<b>0 .. 1</b>	<b>TemperatureControl</b>
required	Type
	Uom
1 .. 1	xs:sequence
0 .. 1	Fixed
0 .. 1	HumidityPercentage

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
<b>0 .. 1</b> required	<b>RangeDetails</b>
	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Minimum</b>
0 .. 1	<b>Maximum</b>
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	xs:sequence
<b>0 .. 1</b> required	<b>PartyDetails</b>
1 .. 1	<i>Role</i>
0 .. 1	xs:sequence
0 .. 1	<b>Id</b>
0 .. 1	<b>Assignor</b>
0 .. 1	<b>PartyName</b>
0 .. 1	<b>AddressLine1</b>
0 .. 1	<b>AddressLine2</b>
0 .. 1	<b>AddressLine3</b>
0 .. 1	<b>CityName</b>
0 .. 1	<b>State</b>
0 .. 1	<b>PostCode</b>
0 .. 1	<b>CountryCode</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>LocationGroup</b>
1 .. 1	xs:sequence
<b>0 .. 1</b> required	<b>Location</b>
1 .. 1	<i>Type</i>
	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. unbounded</b> required	<b>Contact</b>
1 .. 1	<i>Type</i>
	xs:sequence
0 .. 1	<b>ContactId</b>
0 .. 1	<b>Name</b>
0 .. 1	<b>Phone</b>
0 .. 1	<b>Mobile</b>
0 .. 1	<b>Fax</b>
0 .. 1	<b>Email</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
<b>0 .. 1</b>	<b>Flags</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	<div><div></div><div>xs:sequence</div><div><div></div><div><b>Flag</b></div><div><i>Type</i></div></div></div>
0 .. unbounded	

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

## Guideline

Element/Attribute	Annotation
DSV_ShipmentMessage	<p><b>Internal IT Notes</b> To reduce verbosity in the specification, root element "DSV_GenericShipmentMessage" is omitted from instructions</p> <p><b>General Notes</b> Shipment.xsd V2</p> <p>-----</p> <p>Added:</p> <p>/Shipment/ShipmentId attributes Type and Qualifier  /Shipment/TransportServices/ServiceGroup  /Shipment/TransportServices/ServiceGroup/FreeTextData  /Shipment/TransportServices/ServiceGroup/Dates  /Shipment/TransportServices/ServiceGroup/Parties  /Shipment/TransportServices/ServiceGroup/References  /Shipment/TermsOfDelivery/Terms/DeliveryCode  /Shipment/TermsOfDelivery/Terms/TransportChargesCode  /Shipment/TransportStages/TransportStage/TransportServices  /Shipment/TransportStages/TransportStage/Parties  /Shipment/TransportStages/TransportStage/FreeTextData  /Shipment/TransportStages/TransportStage/CodeDescriptions  /Shipment/TransportStages/TransportStage/Flags  /Shipment/Parties/Party/FinancialInstitution  /Shipment/Parties/Party/Documents  /Shipment/Goodsltems/Goodsltem/Item/Sequence  /Shipment/Goodsltems/Goodsltem/Quantities  /Shipment/Goodsltems/Goodsltem/Packagelds/References  /Shipment/Goodsltems/Goodsltem/Packagelds/Dates  /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/CodeDescriptions  /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Quantities  /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Flags  /Shipment/Goodsltems/Goodsltem/DangerousGoodsDetails/DangerousGoodsDetail/Contact  /Shipment/Goodsltems/Goodsltem/ContainerNumber  /Shipment/Goodsltems/Goodsltem/Flags  /Shipment/Goodsltems/Goodsltem/CodeDescriptions  /Shipment/EquipmentUnits/EquipmentUnit/Measurements  /Shipment/EquipmentUnits/EquipmentUnit/Dimensions  /Shipment/EquipmentUnits/EquipmentUnit/TransportMovements  /Shipment/EquipmentUnits/EquipmentUnit/RangeDetails  /Shipment/EquipmentUnits/EquipmentUnit/Parties  /Shipment/EquipmentUnits/EquipmentUnit/CodeDescriptions  /Shipment/Orders  /Shipment/Milestones</p> <p>Changes:</p> <p>/Shipment/TermsOfDelivery/Terms/TermCode to /</p>

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	Shipment/TermsOfDelivery/Terms/TermsCode
xs:sequence	<b>Occurrence</b> 1 .. 1
Header	<b>Occurrence</b> 1 .. 1 <b>Type</b> Header <b>Examples</b> <Header> <MessageId>12485236</MessageId> <SenderId>SenderIdIdentification</SenderId> <ReceiverId>ReceiverIdIdentification</ReceiverId> <DocumentDate Type="DocumentDate" Format="DateTimeSec"> <DateTime>20250812000000</DateTime> </DocumentDate> <DocumentCode>ForwardingInstruction</DocumentCode> <Function>New</Function> <Version>2.0</Version> </Header>
xs:sequence	<b>Occurrence</b> 1 .. 1
MessageId	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> MESSAGE IDENTIFICATION
SenderId	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> SENDER IDENTIFICATION Mutually agreed
ReceiverId	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> RECEIVER IDENTIFICATION Mutually agreed
DocumentDate	<b>Occurrence</b> 1 .. 1 <b>Type</b> Date
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> DOCUMENT / MESSAGE DATE TYPE
Format	<b>Applicable Codes</b> <b>IssueDate</b> Document Issued Date <b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> DOCUMENT / MESSAGE DATE FORMAT
	<b>Applicable Codes</b> <b>DateTime</b> CCYYMMDDHHMM
xs:sequence	<b>Occurrence</b> 1 .. 1
DateTime	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DOCUMENT MESSAGE DATE/TIME
DocumentCode	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> DOCUMENT TYPE
	<b>Applicable Codes</b> <b>BookingRequest</b> Booking Request Message <b>ForwardingInstruction</b> Forwarding Instruction Message
Function	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>General Notes</b> DOCUMENT / MESSAGE FUNCTION <b>Applicable Codes</b> <b>Delete</b> Delete/ Cancel Shipment <b>New</b> New Shipment <b>Update</b> Update Shipment
Version	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> DOCUMENT / MESSAGE VERSION <b>Applicable Codes</b> <b>2.0</b> Version 2.0
Shipment	<b>Occurrence</b> 1 .. 1 <b>Type</b> Shipment
xs:sequence	<b>Occurrence</b> 1 .. 1
ShipmentId	<b>Occurrence</b> 0 .. 1 <b>Type</b> ShipmentId <b>General Notes</b> SHIPMENT IDENTIFIER <b>Examples</b> <ShipmentId>ABC0011222</ShipmentId>
Type	<b>Type</b> xs:string <b>Use</b> optional <b>Applicable Codes</b> <b>Booking</b> Order Management Booking <b>LoadPlan</b> Order Management Load Plan
Dates	<b>Occurrence</b> 0 .. 1 <b>Type</b> DateList <b>Examples</b> <Dates> <Date Type="IssueDate" Format="DateTime"> <DateTime>202508130900</DateTime> </Date> <Date Type="Collection" Format="Date"> <DateTime>20250820</DateTime> </Date> <Date Type="DeliveryRequested" Format="DateTimeInterval"> <DateTime>202508021200-202508021700</DateTime> </Date> </Dates>
xs:sequence	<b>Occurrence</b> 1 .. 1
Date	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Date
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> SHIPMENT DATE TYPE <b>Applicable Codes</b> <b>Collection</b> Collection date/time, earliest <b>DeliveryRequested</b> Delivery date/time, requested <b>EstimatedCollection</b> Shipment date/time, promised for <b>EstimatedDelivery</b> Delivery date/time, estimated <b>GoodsAvailable</b> Goods Available <b>GoodsStorage</b> Goods Storage <b>HouseBillIssued</b> House Bill issued <b>Receipt</b> Receipt date/time <b>RequestedCollection</b> Shipment date/time, requested <b>RequestedDelivery</b> Requested Delivery Date/ Time <b>ScheduledCollection</b> Goods collection or pick-up date/

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> time, planned <b>ScheduledDelivery</b> Delivery date/time, 1st schedule
<i>Format</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> SHIPMENT DATE FORMAT <b>Applicable Codes</b> <b>Date</b> YYYYMMDD <b>DateTime</b> YYYYMMDDHHMM <b>DateTimeInterval</b> YYYYMMDDHHMM-YYYYMMDDHHMM
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPMENT DATE/TIME
<b>TransportServices</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ServiceGroupList <b>General Notes</b> TRANSPORT SERVICES First occurrence is Main Service Additional services will be provided in subsequent occurrences
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ServiceGroup <b>Examples</b> <ServiceGroup> <TransportService> <ServiceCode>ROAD_LTL</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService> </ServiceGroup>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportService</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportService <b>General Notes</b> MAIN TRANSPORT SERVICE <b>Examples</b> <TransportService> <ServiceCode>ROAD_LTL</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TYPE OF SERVICE REQUIRED <b>Applicable Codes</b> <b>Air_IATA</b> Air - IATA <b>Air_LSE</b> Air - LSE <b>Before10</b> DSV specific value for Express 10: 00 <b>Before12</b> DSV specific value for Express 12: 00 <b>Before16</b> DSV specific value for Express 16: 00

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>Before7</b> DSV specific value for Express 07: 00 <b>Crane</b> DSV specific value for Crane required loading or unloading or both <b>HAZ</b> DSV specific value for Hazardous goods <b>InNightproduct</b> DSV specific value for INGT - InNight product <b>Lift</b> DSV specific value for LIFT-Tail lift <b>Notification</b> DSV specific value for NTFY - Notify <b>OMEX</b> DSV specific value for Omex service goods <b>PersonalDeliveryService</b> DSV specific value for PDS - Personal delivery service <b>PreAdvice</b> DSV specific value for PADV - Pre-advice <b>Rail_FCL</b> Rail - Full Container Load <b>Rail_LCL</b> Road - Less Than Truckload <b>Road_FTL</b> Road - Full Truckload <b>Road_LTL</b> Road - Less Than Truckload <b>Sea_FCL</b> Sea - Full Container Load <b>Sea_LCL</b> Sea - Less Than Container Load <b>ePallet</b> DSV specific value for EPLT - E-service pallet <b>eParcel</b> DSV specific value for EPRC- E-service collie
PriorityCode	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SERVICE PRIORITY CODE Only provided for Main Service (First TransportService) <b>Applicable Codes</b> <b>Express</b> Express Service <b>HighSpeed</b> High Speed Service <b>Normal</b> Normal Service
ServiceGroup <Services>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ServiceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
TransportService	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportService <b>Examples</b> <TransportService> <ServiceCode>OMEX</ServiceCode> </TransportService>
xs:sequence	<b>Occurrence</b> 1 .. 1
ServiceCode	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> Type of SERVICE CODE <b>Applicable Codes</b> <b>Air_IATA</b> Air - IATA <b>Air_LSE</b> Air - LSE <b>Before10</b> DSV specific value for Express 10: 00 <b>Before12</b> DSV specific value for Express 12: 00 <b>Before16</b> DSV specific value for Express 16:

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>Before7</b> 00 DSV specific value for Express 07: 00 <b>Crane</b> DSV specific value for Crane required loading or unloading or both <b>HAZ</b> DSV specific value for Hazardous goods <b>InNightproduct</b> DSV specific value for INGT - InNight product <b>Lift</b> DSV specific value for LIFT-Tail lift <b>Notification</b> DSV specific value for NTFY - Notify <b>OMEX</b> DSV specific value for Omex service goods <b>PersonalDeliveryService</b> DSV specific value for PDS - Personal delivery service <b>PreAdvice</b> DSV specific value for PADV - Pre- advice <b>Rail_FCL</b> Rail - Full Container Load <b>Rail_LCL</b> Road - Less Than Truckload <b>Road_FTL</b> Road - Full Truckload <b>Road_LTL</b> Road - Less Than Truckload <b>Sea_FCL</b> Sea - Full Container Load <b>Sea_LCL</b> Sea - Less Than Container Load <b>ePallet</b> DSV specific value for EPLT - E- service pallet <b>eParcel</b> DSV specific value for EPRC- E- service collie
<b>FreeTextData</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> FreeTextList <b>Examples</b> <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> FreeText
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required
	<b>Applicable Codes</b> <b>ServiceDescription</b> Service Description <b>ServiceNote</b> Service Note
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Dates</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DateList
	<b>Examples</b> <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date> </Dates>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Date</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Date

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute		Annotation
	<i>Type</i>	Type xs:string
		Use required
		<b>Applicable Codes</b>
		<b>Booked</b> Booked
	<i>Format</i>	Type xs:string
		Use required
		<b>Applicable Codes</b>
		<b>DateTimeSec</b> CCYYMMDDHHMMSS
	xs:sequence	Occurrence 1 .. 1
		Occurrence 0 .. 1
		Type xs:string
		<b>DateTime</b>
	<b>Parties</b>	Occurrence 0 .. 1
		Type PartiesList
		<b>General Notes</b> TRANSPORT SERVICES PARTY
		<b>Examples</b> <Parties> <Party> <PartyDetails Role="Contractor"> <Id>124563556</Id> <Assignor>DSV</Assignor> <PartyName>XYZ</PartyName> <AddressLine1>.</AddressLine1> <AddressLine2>AWDC</AddressLine2> <AddressLine3>AWDC</AddressLine3> <CityName>City</CityName> <State>State</State> <PostCode>1234</PostCode> <CountryCode>XY</CountryCode> </PartyDetails><Locations> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="UN"> <LocationIdentifier>ZAJNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> <LocationIdentification Type="IATA"> <LocationIdentifier>JNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> <Contact Type="InformationContact"> <ContactId>XYX</ContactId> <Name>AGHJFGH</Name> <Phone>123456789</Phone> <Mobile>1234567890</Mobile> <Fax>12345678</Fax> <Email>XYZ@ABC.COM</Email> </Contact> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> </ReferenceGroup> </References>

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation		
	<b>Examples</b> </ReferenceGroup> </References> </Party> </Parties>		
xs:sequence	<b>Occurrence</b> 1 .. 1		
<b>Party</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Party		
xs:sequence	<b>Occurrence</b> 1 .. 1		
<b>PartyDetails</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartyDetails <b>Examples</b> <PartyDetails Role="Contractor"> <Id>124563556</Id> <Assignor>DSV</Assignor> <PartyName>XYZ</PartyName> <AddressLine1>.</AddressLine1> <AddressLine2>AWDC</AddressLine2> <AddressLine3>AWDC</AddressLine3> <CityName>City</CityName> <State>State</State> <PostCode>1234</PostCode> <CountryCode>XY</CountryCode> </PartyDetails>		
<i>Role</i>	<b>Type</b> xs:string <b>Use</b> required <b>Applicable Codes</b> <table> <tr> <td><b>Contractor</b></td><td>Service Contractor</td></tr> </table>	<b>Contractor</b>	Service Contractor
<b>Contractor</b>	Service Contractor		
xs:sequence	<b>Occurrence</b> 1 .. 1		
<b>Id</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>Assignor</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>PartyName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>AddressLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>AddressLine2</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>AddressLine3</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>CityName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>State</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>PostCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>CountryCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string		
<b>Locations</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> LocationGroupList <b>Examples</b> <Locations> <LocationGroup> <Location Type="Departure"> <LocationIdentification Type="UN">		

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
<b>Examples</b> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination"> <LocationIdentification Type="UN"> <LocationIdentifier>ZAJNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> <LocationIdentification Type="IATA"> <LocationIdentifier>JNB</LocationIdentifier> <LocationName>Johannesburg</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations>	
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> LocationGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Location</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Location
Type	<b>Type</b> xs:string <b>Use</b> required
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentification</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> LocationIdentification
Type	<b>Type</b> xs:string
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>LocationName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Contact</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Contact
<b>Examples</b> <Contact Type="InformationContact"> <ContactId>XYX</ContactId> <Name>AGHJFGH</Name> <Phone>123456789</Phone> <Mobile>1234567890</Mobile> <Fax>12345678</Fax> <Email>XYZ@ABC.COM</Email> </Contact>	
Type	<b>Type</b> xs:string <b>Use</b> required
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ContactId</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Name</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Phone</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Mobile</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
<b>Fax</b>	Occurrence 0 .. 1 Type xs:string
<b>Email</b>	Occurrence 0 .. 1 Type xs:string
<b>References</b>	Occurrence 0 .. 1 Type ReferenceGroupList  <b>Examples</b> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
<b>ReferenceGroup</b>	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
<b>Reference</b>	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required
<i>Identifier</i>	Type xs:string Use optional
<b>References</b>	Occurrence 0 .. 1 Type ReferenceGroupList <b>General Notes</b> TRANSPORT SERVICES REFERENCES  <b>Examples</b> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
<b>ReferenceGroup</b>	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
<b>Reference</b>	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required
<b>Applicable Codes</b>	
<b>ServiceCount</b>	
<b>ServiceReference</b>	
<i>Identifier</i>	Type xs:string Use optional
<b>Date</b>	Occurrence 0 .. 1 Type Date
<i>Type</i>	Type xs:string Use required
<i>Format</i>	Type xs:string Use required
xs:sequence	Occurrence 1 .. 1
<b>DateTime</b>	Occurrence 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
<b>MonetaryAmounts</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> MonetaryAmountList <b>General Notes</b> SHIPMENT MONETARY AMOUNTS  <b>Examples</b> <MonetaryAmounts> <MonetaryAmount Type="InvoiceValue"> <Amount>100.01</Amount> <Currency>DKK</Currency> </MonetaryAmount> </MonetaryAmounts>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>MonetaryAmount</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> MonetaryAmount
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> MONETARY AMOUNT TYPE
	<b>Applicable Codes</b>
	<b>COD</b> Cash On Delivery Amount <b>InvoiceValue</b> Invoice Value
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Amount</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MONETARY AMOUNT
<b>Currency</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MONETARY AMOUNT ISO CURRENCY
<b>FreeTextData</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> FreeTextList <b>General Notes</b> SHIPMENT FREE TEXT  <b>Examples</b> <FreeTextData> <FreeText Type="DeliveryInstructions"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> <TextLine2>DeliveryInstructions Text Line 2</TextLine2> <TextLine3>DeliveryInstructions Text Line 3</TextLine3> <TextLine4>DeliveryInstructions Text Line 4</TextLine4> <TextLine5>DeliveryInstructions Text Line 5</TextLine5> </FreeText> <FreeText Type="HandlingInstructions"> <TextLine1>Handling Instructions Text Line 1</TextLine1> </FreeText> <FreeText Type="PickupInstructions"> <TextLine1>Pickup Instructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> FreeText
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> FREE TEXT TYPE  Predefined Types listed, additional FreeText types to be agreed

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>AdditionalDetails</b> Additional Details <b>ConsignmentDetails</b> Consignment Details (Status, RegDate, Remarks, Originater) <b>DeliveryInstructions</b> Delivery Instructions <b>DeliveryRemarks</b> Delivery Remarks <b>GeneralInformation</b> General information <b>GoodsDescription</b> Goods Description <b>MarinePollutant</b> DG Marine Pollutant <b>NatureOfCargo</b> Nature Of Cargo <b>PickupInstructions</b> Pickup Instructions <b>ProperShippingName</b> DG Proper Shipping Name <b>ReportInformation</b> Report Information <b>SpecialHandling</b> Special Handling <b>SpecialInstructions</b> Special Instructions <b>StatusRemarks</b> Status Remarks <b>WarehouseInstructionsExport</b> Warehouse Instructions Export
xs:sequence	Occurrence 1 .. 1
DescriptionCode	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT DESCRIPTION CODE Use to be agreed
TextLine1	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 1
TextLine2	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 2
TextLine3	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 3
TextLine4	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 4
TextLine5	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 5
ControlTotals	Occurrence 0 .. 1 Type ControlTotalList <b>General Notes</b> SHIPMENT CONTROL TOTALS <b>Examples</b> <ControlTotals> <ControlTotal Type="NumberOfPackages"> <Quantity>20</Quantity> </ControlTotal> <ControlTotal Type="GrossWeight" Uom="KGM"> <Quantity>101.01</Quantity> </ControlTotal> <ControlTotal Type="Volume" Uom="MTQ"> <Quantity>2</Quantity> </ControlTotal> <ControlTotal Type="LoadingMeters" Uom="MTR"> <Quantity>12</Quantity> </ControlTotal>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																		
	<b>Examples</b> <ControlTotal Type="PalletSpaces" Uom="PLL"> <Quantity>10</Quantity> </ControlTotal> </ControlTotals>																		
xs:sequence	<b>Occurrence</b> 1 .. 1																		
<b>ControlTotal</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ControlTotal																		
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> CONTROL TOTAL TYPE																		
	<b>Applicable Codes</b> <table> <tr><td><b>ChargableWeight</b></td><td>Chargable Weight</td></tr> <tr><td><b>GrossWeight</b></td><td>Gross Weight</td></tr> <tr><td><b>LoadingMeters</b></td><td>Loading Meters</td></tr> <tr><td><b>NumberOfInnerPackages</b></td><td>Number Of Inner Packages</td></tr> <tr><td><b>NumberOfPackages</b></td><td>Number Of Packages</td></tr> <tr><td><b>PalletSpaces</b></td><td>Pallet Spaces</td></tr> <tr><td><b>TotalNetWeightOfShipment</b></td><td>Total net weight of shipment</td></tr> <tr><td><b>TotalNumberOfShipments</b></td><td>Total number of shipments</td></tr> <tr><td><b>Volume</b></td><td>Volume</td></tr> </table>	<b>ChargableWeight</b>	Chargable Weight	<b>GrossWeight</b>	Gross Weight	<b>LoadingMeters</b>	Loading Meters	<b>NumberOfInnerPackages</b>	Number Of Inner Packages	<b>NumberOfPackages</b>	Number Of Packages	<b>PalletSpaces</b>	Pallet Spaces	<b>TotalNetWeightOfShipment</b>	Total net weight of shipment	<b>TotalNumberOfShipments</b>	Total number of shipments	<b>Volume</b>	Volume
<b>ChargableWeight</b>	Chargable Weight																		
<b>GrossWeight</b>	Gross Weight																		
<b>LoadingMeters</b>	Loading Meters																		
<b>NumberOfInnerPackages</b>	Number Of Inner Packages																		
<b>NumberOfPackages</b>	Number Of Packages																		
<b>PalletSpaces</b>	Pallet Spaces																		
<b>TotalNetWeightOfShipment</b>	Total net weight of shipment																		
<b>TotalNumberOfShipments</b>	Total number of shipments																		
<b>Volume</b>	Volume																		
Uom	<b>Type</b> xs:string <b>General Notes</b> QUANTITY UNIT OF MEASURE																		
	<b>Applicable Codes</b> <table> <tr><td><b>CTN</b></td><td>Cartons</td></tr> <tr><td><b>KGM</b></td><td>Kilograms</td></tr> <tr><td><b>MTQ</b></td><td>Cubic meters</td></tr> <tr><td><b>MTR</b></td><td>Linear meters</td></tr> <tr><td><b>PCE</b></td><td>Pieces</td></tr> <tr><td><b>PKG</b></td><td>Packages</td></tr> <tr><td><b>UNT</b></td><td>Units</td></tr> </table>	<b>CTN</b>	Cartons	<b>KGM</b>	Kilograms	<b>MTQ</b>	Cubic meters	<b>MTR</b>	Linear meters	<b>PCE</b>	Pieces	<b>PKG</b>	Packages	<b>UNT</b>	Units				
<b>CTN</b>	Cartons																		
<b>KGM</b>	Kilograms																		
<b>MTQ</b>	Cubic meters																		
<b>MTR</b>	Linear meters																		
<b>PCE</b>	Pieces																		
<b>PKG</b>	Packages																		
<b>UNT</b>	Units																		
xs:sequence	<b>Occurrence</b> 1 .. 1																		
Quantity	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTROL TOTAL QUANTITY																		
<b>Documents</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DocumentList <b>General Notes</b> SHIPMENT DOCUMENTS																		
	<b>Examples</b> <Documents> <Document> <DocumentCode>EBL</DocumentCode> <DocumentCopies>1</DocumentCopies> <DocumentOriginals>0</DocumentOriginals> </Document> </Documents>																		
xs:sequence	<b>Occurrence</b> 1 .. 1																		
<b>Document</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Document																		
xs:sequence	<b>Occurrence</b> 1 .. 1																		
<b>DocumentCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DOCUMENT CODE																		

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>EBL</b> Non-negotiable maritime transport document <b>OBO</b> Original Bill - Surrendered at origin <b>OBP</b> Original BL - Print at destination <b>OBR</b> Bill of lading original <b>T1</b> Despatch note model T1 <b>T2</b> Despatch note model T2 <b>T2L</b> Despatch note model T2L <b>T5</b> Control Document T5
DocumentCopies	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> NUMBER OF COPIES
DocumentOriginals	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> NUMBER OF ORIGINALS
Locations	<b>Occurrence</b> 0 .. 1 <b>Type</b> LocationGroupList <b>General Notes</b> SHIPMENT LOCATIONS  <b>Examples</b> <Locations> <LocationGroup> <Location Type="BranchLocation"> <LocationIdentification Type="DSVBranch"> <LocationIdentifier>HOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationGroup	<b>Occurrence</b> 0 .. unbounded <b>Type</b> LocationGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
Location	<b>Occurrence</b> 0 .. 1 <b>Type</b> Location
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> LOCATION TYPE  <b>Applicable Codes</b> <b>DSVOrigin</b> DSV Origin
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationIdentification	<b>Occurrence</b> 1 .. unbounded <b>Type</b> LocationIdentification
Type	<b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER TYPE  <b>Applicable Codes</b> <b>DSVBookingOffice</b> DSV Booking Office (Only to be used for CargoLink Road Freight) <b>DSVBranch</b> DSV Branch (Only to be used for Air, Sea & Rail) <b>DSVDepartment</b> DSV Department (Only to be used for Air, Sea & Rail) <b>ISOCountry</b> Originating Country ISO Code (Only used for Air, Sea & Rail)
xs:sequence	<b>Occurrence</b> 1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
LocationIdentifier	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER
TermsOfDelivery	<b>Occurrence</b> 0 .. 1 <b>Type</b> TermsGroup <b>Examples</b> <TermsOfDelivery> <Terms> <TermsCode>CIP</TermsCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>
xs:sequence	<b>Occurrence</b> 1 .. 1
Terms	<b>Occurrence</b> 0 .. 1 <b>Type</b> Terms
xs:sequence	<b>Occurrence</b> 1 .. 1
TermsCode	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TERM CODE
CodeId	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TYPE OF TERM CODE <b>Applicable Codes</b> <b>CombiTerm</b> Combi Term <b>Incoterm</b> INCO Term
Location	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Location
Type	<b>Type</b> xs:string <b>Use</b> required <b>Applicable Codes</b> <b>NamedPlace</b> Term Named Place
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationIdentification	<b>Occurrence</b> 1 .. unbounded <b>Type</b> LocationIdentification
Type	<b>Type</b> xs:string <b>Applicable Codes</b> <b>Name</b> Only Location Name provided <b>UN</b> UN Location Code
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationIdentifier	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
LocationName	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
References	<b>Occurrence</b> 0 .. 1 <b>Type</b> ReferenceGroupList <b>Examples</b> <References> <ReferenceGroup> <Reference Type="ShipperReference">ShpRef1</Reference> <Date Type="ReferenceDate" Format="Date">

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Examples</b> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">ConsRef1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="RoadWaybill">Waybill1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>2025081309000000</DateTime> </Date> </Dates> </ReferenceGroup> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Reference <b>General Notes</b> SHIPMENT REFERENCE
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> SHIPMENT REFERENCE TYPE  Predefined Types listed, additional reference types to be agreed
<b>Applicable Codes</b>	
<b>ASMShipmentId</b>	Assembly Master Shipment Id
<b>AgentsReference</b>	Agent's reference
<b>AviationSecurity</b>	Aviation Security
<b>CLPartnerCode</b>	CargoLink Partner Code
<b>CargoManifestNo</b>	Cargo manifest number, Transport Id
<b>ConsigneeOrderNumber</b>	Consignee's order number
<b>ConsigneeReference</b>	Consignee Reference
<b>ConsignmentId</b>	Consignment id, carrier assigned
<b>CustomField</b>	Custom Field
<b>CustomerAccountCode</b>	Customer Account Code
<b>CustomerReferenceNumber</b>	Customer reference number
<b>DeliveryAgreement</b>	Delivery Agreement
<b>DocumentReference</b>	Document Reference
<b>EventCode</b>	DSV specific value for Event Code
<b>ExternalReference</b>	DSV specific value for External reference customer reference number
<b>GINCNumber</b>	Waybill number, GINC
<b>HazardousReference</b>	Hazardous Reference
<b>HouseBill</b>	House bill of lading number
<b>IDSReference</b>	DSV specific value for IDS reference
<b>InspectionType</b>	Inspection Type
<b>MasterBill</b>	Master bill of lading number
<b>OnSightAuthorizationCode</b>	DSV specific value for On sight authorization code
<b>OrderReference</b>	Order Reference
<b>PackageNumber</b>	Package Number
<b>ProofOfDeliveryNumber</b>	Proof of delivery reference number
<b>QualityCode</b>	Quality Code

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>QualitySource</b> Quality Source <b>RoadWaybill</b> Road Waybill number, SIS <b>ShipmentReference</b> Shipment reference number <b>ShipperReference</b> Shipper Reference <b>TrafficFrom</b> Traffic From <b>TransportInstructionNumber</b> Transport instruction number <b>VehicleId</b> Vehicle identification number ( VIN) <b>VesselCountryOfRegistration</b> DSV specific value for Vessel Country of Registration <b>VesselId</b> Vessel identifier
<i>CustomFieldType</i>	<b>Type</b> xs:string <b>Use</b> optional <b>General Notes</b> CUSTOM FIELD TYPE  Use to be agreed
<b>Date</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Date <b>General Notes</b> REFERENCE DATE
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> REFERENCE DATE
<i>Format</i>	<b>Applicable Codes</b> <b>ReferenceDate</b> Reference Date <b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> REFERENCE DATE FORMAT
<i>xs:sequence</i>	<b>Applicable Codes</b> <b>DateTime</b> CCYYMMDDHHMM <b>DateTimeSec</b> CCYYMMDDHHMMSS
<b>DateTime</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> REFERENCE DATE/TIME
<b>Requirements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> RequirementList <b>General Notes</b> GOVERNMENT AND DOCUMENT REQUIREMENTS  <b>Examples</b> <Requirements> <Requirement> <GovernmentalRequirements> <TransportMovementCode>Export</TransportMovementCode> <InvolvementCode>NotApplicable</InvolvementCode> </GovernmentalRequirements> <Documents> <Document> <DocumentCode>EBL</DocumentCode> </Document> </Documents> </Requirement> </Requirements>
<i>xs:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>Requirement</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Requirement
<i>xs:sequence</i>	<b>Occurrence</b> 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<b>GovernmentalRequirements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> GovernmentalRequirements
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportMovementCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORT MOVEMENT TYPE <b>Applicable Codes</b> Export Import Transit
<b>InvolvementCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> INVOLVEMENT CODE <b>Applicable Codes</b> Completed NotApplicable
<b>Documents</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DocumentList
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Document</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Document
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DocumentCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> ROAD TRANSPORTATION DOCUMENT TYPE <b>Applicable Codes</b> EBL Non-negotiable maritime transport document OBO Original Bill - Surrendered at origin OBP Original BL - Print at destination OBR Bill of lading original T1 Despatch note model T1 T2 Despatch note model T2 T2L Despatch note model T2L T5 Control document T5
<b>ChargeMethodology</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ChargeMethodologyList <b>General Notes</b> CHARGE METHODOLOGY <b>Examples</b> <ChargeMethodology> <PaymentInstructions> <PaymentInstruction> <PaymentCode>Prepaid</PaymentCode> </PaymentInstruction> </PaymentInstructions> </ChargeMethodology>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PaymentInstructions</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> PaymentInstructions
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PaymentInstruction</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PaymentInstruction
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PaymentCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>General Notes</b> PAYMENT TYPE <b>Applicable Codes</b> <b>Collect</b> Collect Shipment <b>Prepaid</b> Prepaid Shipment <b>ThirdParty</b> Third Party Shipment
<b>TransportStages</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportStageList <b>General Notes</b> TRANSPORT STAGES
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportStage</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> TransportStage
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Stage</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Stage <b>General Notes</b> TRANSPORTATION STAGE  <b>Examples</b> <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> <TransportId>12345X</TransportId> <CarrierId>12345678</CarrierId> <CarrierName>Carrier Name</CarrierName> <TransportType>Main</TransportType> <TransportMeansName>Vessel name</TransportMeansName> <TransportMeansNationality>PA</TransportMeansNationality> </Stage>
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> TRANSPORTATION STAGE TYPE <b>Applicable Codes</b> <b>MainCarriage</b> Main Carriage <b>PlannedLeg</b> Planned Leg <b>PlannedLeg1</b> Main carriage - first carrier <b>PlannedLeg2</b> Main carriage - second carrier <b>PlannedLeg3</b> Main carriage - third carrier <b>PlannedLeg4</b> Main carriage - fourth carrier <b>PlannedLeg5</b> Main carriage - fifth carrier
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ModeOfTransport</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MODE OF TRANSPORTATION <b>Applicable Codes</b> <b>Air</b> Air transportation <b>Rail</b> Rail transportation <b>Road</b> Road transportation <b>Sea</b> Sea transportation
<b>TransportId</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORT IDENTIFICATION Air: Flight number Sea: Voyage number Road: Not used
<b>CarrierId</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CARRIER IDENTIFICATION Air & Sea: DSV carrier identifier

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation												
	Road: Not used												
<b>CarrierName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CARRIER NAME Road: Not used												
<b>TransportType</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORT TYPE Road: Not used <b>Applicable Codes</b> <table> <tr> <td><b>Flight1</b></td><td>First Flight</td></tr> <tr> <td><b>Flight2</b></td><td>Second Flight</td></tr> <tr> <td><b>Flight3</b></td><td>Third Flight</td></tr> <tr> <td><b>Flight4</b></td><td>Fourth Flight</td></tr> <tr> <td><b>Main</b></td><td>Main Carriage</td></tr> <tr> <td><b>Other</b></td><td>Other</td></tr> </table>	<b>Flight1</b>	First Flight	<b>Flight2</b>	Second Flight	<b>Flight3</b>	Third Flight	<b>Flight4</b>	Fourth Flight	<b>Main</b>	Main Carriage	<b>Other</b>	Other
<b>Flight1</b>	First Flight												
<b>Flight2</b>	Second Flight												
<b>Flight3</b>	Third Flight												
<b>Flight4</b>	Fourth Flight												
<b>Main</b>	Main Carriage												
<b>Other</b>	Other												
<b>TransportMeansName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORT MEANS NAME Sea: Vessel Name Air & Road: Not used												
<b>TransportMeansNationality</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORT MEANS NATIONALITY Sea: Vessel flag Air & Road: Not used												
<b>Dates</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DateList <b>General Notes</b> TRANSPORTATION DATES <b>Examples</b> <Dates> <Date Format="DateTimeSec" Type="ScheduledDeparture"> <DateTime>20250821093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentDeparture"> <DateTime>20250821093000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledArrival"> <DateTime>20250819000100</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledShipmentArrival"> <DateTime>20250819000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDeparture"> <DateTime>20250821093500</DateTime> </Date> </Dates>												
xs:sequence	<b>Occurrence</b> 1 .. 1												
<b>Date</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Date												
<b>Type</b>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> TRANSPORTATION DATE TYPE												

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>ActualArrival</b> Actual Time of Arrival <b>ActualDelivery</b> Actual Delivery date/time <b>ActualDeparture</b> Actual Time of Departure <b>EstimatedArrival</b> Estimated Time of Arrival <b>EstimatedDelivery</b> Delivery date/time, estimated <b>EstimatedDeparture</b> Estimated Time of Departure <b>ScheduledArrival</b> Scheduled Time of Arrival <b>ScheduledDeparture</b> Scheduled Time of Departure <b>ScheduledShipmentArrival</b> Scheduled Shipment Time of Arrival <b>ScheduledShipmentDeparture</b> Scheduled Shipment Time of Departure
<i>Format</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> TRANSPORTATION DATE FORMAT <b>Applicable Codes</b> <b>DateTime</b> CCYYMMDDHHMM <b>DateTimeInterval</b> CCYYMMDDHHMM- CCYYMMDDHHMM <b>DateTimeSec</b> CCYYMMDDHHMMSS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> TRANSPORTATION DATE/TIME
<b>TransportServices</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ServiceGroupList <b>General Notes</b> TRANSPORT STAGES TRANSPORT SERVICE
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ServiceGroup <b>Examples</b> <ServiceGroup> <TransportService> <ServiceCode>AIR_LSE</ServiceCode> <PriorityCode>Normal</PriorityCode> </TransportService> </ServiceGroup>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportService</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportService
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>Applicable Codes</b> <b>Air_IATA</b> Air - IATA <b>Air_LSE</b> Air - LSE <b>Before10</b> DSV specific value for Express 10: 00 <b>Before12</b> DSV specific value for Express 12: 00 <b>Before16</b> DSV specific value for Express 16: 00 <b>Before7</b> DSV specific value for Express 07: 00 <b>Crane</b> DSV specific value for Crane required loading or unloading or both

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>HAZ</b> DSV specific value for Hazardous goods <b>InNightproduct</b> DSV specific value for INGT - InNight product <b>Lift</b> DSV specific value for LIFT-Tail lift <b>Notification</b> DSV specific value for NTFY - Notify <b>OMEX</b> DSV specific value for Omex service goods <b>PersonalDeliveryService</b> DSV specific value for PDS - Personal delivery service <b>PreAdvice</b> DSV specific value for PADV - Pre-advice <b>Rail_FCL</b> Rail - Full Container Load <b>Rail_LCL</b> Road - Less Than Truckload <b>Road_FTL</b> Road - Full Truckload <b>Road_LTL</b> Road - Less Than Truckload <b>Sea_FCL</b> Sea - Full Container Load <b>Sea_LCL</b> Sea - Less Than Container Load <b>ePallet</b> DSV specific value for EPLT - E-service pallet <b>eParcel</b> DSV specific value for EPRC- E-service collie
<b>PriorityCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>Applicable Codes</b> <b>Express</b> Express Service <b>HighSpeed</b> High Speed Service <b>Normal</b> Normal Service
<b>ServiceGroup &lt;Services&gt;</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ServiceGroup <b>Examples</b> <ServiceGroup> <TransportService> <ServiceCode>PreAdvice</ServiceCode> <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData> <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date> </Dates> <Parties> <Party> <PartyDetails Role="Contractor"> <Id>123456789XYZ</Id> <Assignor>DSV</Assignor> <PartyName>ABCDEF</PartyName> <AddressLine1>ASDF</AddressLine1> <AddressLine2>XYZ</AddressLine2> <CityName>CITY</CityName> <PostCode>POCODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>ASDFGRT</Name> <Phone>123456789</Phone>

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Examples</b> </Contact> </Party> </Parties> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References> </TransportService> </ServiceGroup>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportService</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportService
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
	<b>Applicable Codes</b>
	<b>Air_IATA</b> Air - IATA
	<b>Air_LSE</b> Air - LSE
	<b>Before10</b> DSV specific value for Express 10: 00
	<b>Before12</b> DSV specific value for Express 12: 00
	<b>Before16</b> DSV specific value for Express 16: 00
	<b>Before7</b> DSV specific value for Express 07: 00
	<b>Crane</b> DSV specific value for Crane required loading or unloading or both
	<b>HAZ</b> DSV specific value for Hazardous goods
	<b>InNightproduct</b> DSV specific value for INGT - InNight product
	<b>Lift</b> DSV specific value for LIFT-Tail lift
	<b>Notification</b> DSV specific value for NTFY - Notify
	<b>OMEX</b> DSV specific value for Omex service goods
	<b>PersonalDeliveryService</b> DSV specific value for PDS - Personal delivery service
	<b>PreAdvice</b> DSV specific value for PADV - Pre- advice
	<b>Rail_FCL</b> Rail - Full Container Load
	<b>Rail_LCL</b> Road - Less Than Truckload
	<b>Road_FTL</b> Road - Full Truckload
	<b>Road_LTL</b> Road - Less Than Truckload
	<b>Sea_FCL</b> Sea - Full Container Load
	<b>Sea_LCL</b> Sea - Less Than Container Load
	<b>ePallet</b> DSV specific value for EPLT - E- service pallet
	<b>eParcel</b> DSV specific value for EPRC- E- service collie
<b>FreeTextData</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> FreeTextList
xs:sequence	<b>Occurrence</b> 1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	<div>FreeText</div>	<div>Occurence0 .. unbounded</div> <div>TypeFreeText</div>
	<div>Type</div>	<div>Typexs:string</div> <div>Userequired</div>
	<div>xs:sequence</div>	<div>Occurence1 .. 1</div>
	<div>TextLine1</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div>
	<div>Locations</div>	<div>Occurence0 .. 1</div> <div>TypeLocationGroupList</div> <div>General NotesTRANSPORTATION LOCATIONS</div> <div>Examples</div> <div>&lt;Locations&gt;</div> <div>&lt;LocationGroup&gt;</div> <div>&lt;Location Type="Departure"&gt;</div> <div>&lt;LocationIdentification Type="UN"&gt;</div> <div>&lt;LocationIdentifier&gt;DKHOR&lt;/LocationIdentifier&gt;</div> <div>&lt;/LocationIdentification&gt;</div> <div>&lt;/Location&gt;</div> <div>&lt;/LocationGroup&gt;</div> <div>&lt;LocationGroup&gt;</div> <div>&lt;Location Type="Destination"&gt;</div> <div>&lt;LocationIdentification Type="UN"&gt;</div> <div>&lt;LocationIdentifier&gt;ZAJNB&lt;/LocationIdentifier&gt;</div> <div>&lt;LocationName&gt;Johannesburg&lt;/LocationName&gt;</div> <div>&lt;/LocationIdentification&gt;</div> <div>&lt;LocationIdentification Type="IATA"&gt;</div> <div>&lt;LocationIdentifier&gt;JNB&lt;/LocationIdentifier&gt;</div> <div>&lt;LocationName&gt;Johannesburg&lt;/LocationName&gt;</div> <div>&lt;/LocationIdentification&gt;</div> <div>&lt;/Location&gt;</div> <div>&lt;/LocationGroup&gt;</div> <div>&lt;/Locations&gt;</div>
	<div>xs:sequence</div>	<div>Occurence1 .. 1</div>
	<div>LocationGroup</div>	<div>Occurence0 .. unbounded</div> <div>TypeLocationGroup</div>
	<div>xs:sequence</div>	<div>Occurence1 .. 1</div>
	<div>Location</div>	<div>Occurence0 .. 1</div> <div>TypeLocation</div>
	<div>Type</div>	<div>Typexs:string</div> <div>Userequired</div> <div>General NotesTRANSPORTATION LOCATION TYPE</div> <div>Applicable Codes</div> <div>Departure</div> <div>Place of Departure</div> <div>Destination</div> <div>Place of Destination</div> <div>GoodsItemLocation</div> <div>Goods Item Storage Location</div> <div>PlaceOfConsolidation</div> <div>Place of Consolidation</div> <div>PlaceOfDeconsolidation</div> <div>Place of Deconsolidation</div> <div>PlaceOfLoading</div> <div>Place of Loading</div> <div>PlaceOfUnloading</div> <div>Place of Unloading</div>
	<div>xs:sequence</div>	<div>Occurence1 .. 1</div>
	<div>LocationIdentification</div>	<div>Occurence1 .. unbounded</div> <div>TypeLocationIdentification</div> <div>General NotesOne Location can result in up to three LocationIdentification elements.</div>
	<div>Type</div>	<div>Typexs:string</div> <div>General NotesLOCATION IDENTIFIER TYPE</div>

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>DSVBookingOffice</b> DSV Booking Office <b>IATA</b> IATA airport code <b>UN</b> UN Location code
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER
<b>LocationName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> LOCATION NAME
<b>References</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ReferenceGroupList <b>General Notes</b> TRANSPORTATION STAGE REFERENCES  <b>Examples</b> <References> <ReferenceGroup> <Reference Type="MasterBill">Master1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="TransportMasterType">AGT</Reference> </ReferenceGroup> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Reference
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>Applicable Codes</b> <b>AgentsReference</b> Agent's reference <b>CLPartnerCode</b> CargoLink Partner Code <b>CargoManifestNo</b> Cargo manifest number, Transport Id <b>ConsigneeOrderNumber</b> Consignee's order number <b>ConsigneeReference</b> Consignee Reference <b>ConsignmentId</b> Consignment id, carrier assigned <b>ConsolContainerMode</b> Consol Container Mode <b>ConsolServiceLevel</b> Consol Service Level <b>CustomerAccountCode</b> Customer Account Code <b>CustomerReferenceNumber</b> Customer reference number <b>DeliveryAgreement</b> Delivery Agreement <b>DocumentReference</b> Document Reference <b>EventCode</b> DSV specific value for Event Code <b>ExternalReference</b> DSV specific value for External reference customer reference number  <b>GINCNumber</b> Waybill number, GINC <b>HouseBill</b> House bill of lading number <b>IDSReference</b> DSV specific value for IDS reference <b>MasterBill</b> Master bill of lading number <b>OnSightAuthorizationCode</b> DSV specific value for On sight authorization code  <b>OrderReference</b> Order Reference <b>ProofOfDeliveryNumber</b> Proof of delivery reference number

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>QualityCode</b> Quality Code <b>QualitySource</b> Quality Source <b>RoadWaybill</b> Road Waybill number, SIS <b>ShipmentReference</b> Shipment reference number <b>ShipperReference</b> Shipper Reference <b>TrafficFrom</b> Traffic From <b>TransportInstructionNumber</b> Transport instruction number <b>TypeOfService</b> Type of Service <b>VehicleId</b> Vehicle identification number ( VIN) <b>VesselCountryOfRegistration</b> DSV specific value for Vessel Country of Registration <b>VesselId</b> Vessel identifier
<i>Identifier</i>	<b>Type</b> xs:string <b>Use</b> optional
<i>CustomFieldType</i>	<b>Type</b> xs:string <b>Use</b> optional
<b>Parties</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartiesList <b>General Notes</b> SHIPMENT PARTY INFORMATION
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Party</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Party
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PartyDetails</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartyDetails <b>General Notes</b> PARTY DETAILS  <b>Examples</b> <PartyDetails Role="Consignor"> <Id>ConsignorID</Id> <Assignor>Consignor</Assignor> <PartyName>Consignor Name</PartyName> <AddressLine1>Consignor Addr Line 1</AddressLine1> <AddressLine2>Consignor Addr Line 2</AddressLine2> <AddressLine3>Consignor Addr Line 3</AddressLine3> <CityName>Consignor City</CityName> <State>Consignor State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails>
<i>Role</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY ROLE  <b>Applicable Codes</b> <b>AcceptingParty</b> <b>Agent</b> <b>Buyer</b> <b>Carrier</b> Carrier Party <b>Consignee</b> Consignee Party <b>Consignor</b> Consignor Party <b>Consolidator</b> Consolidator <b>Deconsolidator</b> Deconsolidator <b>Delivery</b> Delivery Party <b>DeliveryAgent</b> Delivery Agent <b>DeliveryLocalCartage</b> Delivery Local Cartage <b>Despatch</b> Despatch Party <b>Forwarder</b> Forwarder

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>FreightForwarder</b> Freight Forwarder <b>FreightPayer</b> Freight/charges Payer <b>Notify</b> Notify Party <b>OrderingCustomer</b> Ordering Customer <b>PickupAgent</b> Pickup Agent <b>PickupLocalCartage</b> Pickup Local Cartage <b>ShipFrom</b> Ship From <b>ShipTo</b> Ship To <b>Supplier</b> Supplier
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER
Assignor	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER ASSIGNOR <b>Applicable Codes</b> <b>Consignor</b> Consignor Assigned <b>DSV</b> DSV Assigned <b>GS1</b> GS1 Assigned
PartyName	Occurrence 0 .. 1 Type xs:string General Notes PARTY NAME
AddressLine1	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1 Type xs:string General Notes PARTY CITY NAME
State	Occurrence 0 .. 1 Type xs:string General Notes PARTY STATE OR PROVINCE
PostCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY LOCATION ISO COUNTRY CODE
Locations	Occurrence 0 .. 1 Type LocationGroupList General Notes PHYSICAL LOCATION <b>Examples</b> <Locations> <LocationGroup>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> <Location Type="PhysicalLocation"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> LocationGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Location</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Location
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PHYSICAL LOCATION TYPE
	<b>Applicable Codes</b> <b>Physicallocation</b> Party Location
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentification</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> LocationIdentification
<i>Type</i>	<b>Type</b> xs:string <b>General Notes</b> PHYSICAL LOCATION IDENTIFIER TYPE
	<b>Applicable Codes</b> <b>UN</b> UN Location Code
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PHYSICAL LOCATION IDENTIFIER
<b>LocationName</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PHYSICAL LOCATION NAME
<b>Contact</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Contact <b>General Notes</b> PARTY CONTACT DETAILS
	<b>Examples</b> <Contact Type="InformationContact"> <ContactId>Contact ID</ContactId> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY CONTACT TYPE
	<b>Applicable Codes</b> <b>GoodsReceivingContact</b> Goods Receiving Contact <b>InformationContact</b> Party Information Contact
xs:sequence	<b>Occurrence</b> 1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
<b>ContactId</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT ID
<b>Name</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT NAME
<b>Phone</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT PHONE NUMBER
<b>Mobile</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT MOBILE NUMBER
<b>Fax</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT FAX NUMBER
<b>Email</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT E-MAIL ADDRESS
<b>References</b>	Occurrence 0 .. 1 Type ReferenceGroupList <b>General Notes</b> PARTY REFERENCES  <b>Examples</b> <References> <ReferenceGroup> <Reference Type="VAT" Identifier="DK">VatNo</Reference> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
<b>ReferenceGroup</b>	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
<b>Reference</b>	Occurrence 0 .. 1 Type Reference <b>General Notes</b> PARTY REFERENCE
<b>Type</b>	Type xs:string Use required <b>General Notes</b> PARTY REFERENCE TYPE  Predefined Types listed, additional reference types to be agreed
<b>Applicable Codes</b>	
<b>VAT</b>	VAT Number
<b>Identifier</b>	Type xs:string Use optional <b>General Notes</b> PARTY REFERENCE IDENTIFIER
<b>CustomFieldType</b>	Type xs:string Use optional <b>General Notes</b> PARTY REFERENCE CUSTOM FIELD TYPE  Use to be agreed

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
Party <DSVOperator>	<p><b>Occurrence</b> 0 .. unbounded <b>Type</b> Party</p> <p><b>Examples</b>            &lt;Party&gt;            &lt;PartyDetails Role="Consignor"&gt;            &lt;Id&gt;1234567890&lt;/Id&gt;            &lt;Assignor&gt;DSV&lt;/Assignor&gt;            &lt;PartyName&gt;ABCDEF&lt;/PartyName&gt;            &lt;AddressLine1&gt;XYZSD&lt;/AddressLine1&gt;            &lt;AddressLine2&gt;ASDFTG&lt;/AddressLine2&gt;            &lt;CityName&gt;CITY&lt;/CityName&gt;            &lt;PostCode&gt;POCODE&lt;/PostCode&gt;            &lt;CountryCode&gt;XY&lt;/CountryCode&gt;            &lt;/PartyDetails&gt;            &lt;Contact Type="InformationContact"&gt;            &lt;Name&gt;CONTACT NAME&lt;/Name&gt;            &lt;Phone&gt;123456789&lt;/Phone&gt;            &lt;/Contact&gt;            &lt;/Party&gt;</p>
xs:sequence	<b>Occurrence</b> 1 .. 1
PartyDetails	<p><b>Occurrence</b> 0 .. 1 <b>Type</b> PartyDetails <b>General Notes</b> PARTY DETAILS</p> <p><b>Examples</b>            &lt;PartyDetails Role="Consignor"&gt;            &lt;/PartyDetails&gt;</p>
Role	<p><b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY ROLE</p> <p><b>Applicable Codes</b>  <b>DSVOperator</b> DSV Operator</p>
Contact	<p><b>Occurrence</b> 0 .. unbounded <b>Type</b> Contact <b>General Notes</b> PARTY CONTACT DETAILS</p> <p><b>Examples</b>            &lt;Contact Type="InformationContact"&gt;            &lt;Name&gt;Contact name&lt;/Name&gt;            &lt;Phone&gt;Contact Phone&lt;/Phone&gt;            &lt;Email&gt;Contact Email&lt;/Email&gt;            &lt;/Contact&gt;</p>
Type	<p><b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY CONTACT TYPE</p> <p><b>Applicable Codes</b>  <b>InformationContact</b> Party Information Contact</p>
xs:sequence	<b>Occurrence</b> 1 .. 1
Name	<p><b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT NAME</p>
Phone	<p><b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT PHONE NUMBER</p>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation		
<div> <div>Email</div> </div>	<p>Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PARTY CONTACT E-MAIL ADDRESS</p>		
<div> <div>GoodsItems</div> </div>	<p>Occurrence 0 .. 1 Type GoodsItemList <b>General Notes</b> SHIPMENT LINE ITEMS</p>		
<div> <div>xs:sequence</div> <div> <div>GoodsItem</div> </div> </div>	<p>Occurrence 1 .. 1 Occurrence 0 .. unbounded Type GoodsItem</p>		
<div> <div>xs:sequence</div> <div> <div>Item</div> </div> </div>	<p>Occurrence 1 .. 1 Occurrence 0 .. 1 Type Item <b>General Notes</b> GOODS ITEM DETAILS</p> <p><b>Examples</b>  &lt;Item&gt;    &lt;ItemNumber&gt;1&lt;/ItemNumber&gt;    &lt;PackageQty&gt;20&lt;/PackageQty&gt;    &lt;PackageType&gt;PKG&lt;/PackageType&gt;  &lt;/Item&gt;</p>		
<div> <div>xs:sequence</div> <div> <div>Sequence</div> </div> </div>	<p>Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string <b>General Notes</b> LINE SEQUENCE NUMBER</p>		
<div> <div>ItemNumber</div> </div>	<p>Occurrence 0 .. 1 Type xs:string <b>General Notes</b> LINE ITEM NUMBER</p>		
<div> <div>PackageQty</div> </div>	<p>Occurrence 0 .. 1 Type xs:string <b>General Notes</b> LINE ITEM PACKAGE QUANTITY</p>		
<div> <div>PackageType</div> </div>	<p>Occurrence 0 .. 1 Type xs:string <b>General Notes</b> LINE ITEM PACKAGE TYPE</p> <p><b>Applicable Codes</b></p> <table> <tr> <td>UNT</td><td>Units</td></tr> </table>	UNT	Units
UNT	Units		
<div> <div>HandlingInstructions</div> </div>	<p>Occurrence 0 .. 1 Type HandlingInstructions <b>General Notes</b> LINE ITEM HANDLING INSTRUCTION</p> <p>Only used for Road Freight Stacked Cargo</p> <p><b>Examples</b>  &lt;HandlingInstructions&gt;    &lt;HandlingInstruction&gt;      &lt;Code&gt;Stacked&lt;/Code&gt;      &lt;Description&gt;10&lt;/Description&gt;    &lt;/HandlingInstruction&gt;  &lt;/HandlingInstructions&gt;</p>		
<div> <div>xs:sequence</div> <div> <div>HandlingInstruction</div> </div> </div>	<p>Occurrence 1 .. 1 Occurrence 0 .. unbounded Type CodeDescription <b>General Notes</b> LINE ITEM HANDLING INSTRUCTION</p>		

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> <HandlingInstructions> <HandlingInstruction> <Code>Stacked</Code> <Description>10</Description> </HandlingInstruction> </HandlingInstructions>
xs:sequence	<b>Occurrence</b> 1 .. 1
Code	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> HANDLING DESCRIPTION CODE <b>Applicable Codes</b> NotStacked Cargo Not Stacked Stacked Stacked Cargo
Description	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> HANDLING DESCRIPTION Number of stacked units
TemperatureControl	<b>Occurrence</b> 0 .. 1 <b>Type</b> TemperatureControl <b>General Notes</b> LINE ITEM TEMPERATURE CONTROL <b>Examples</b> <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> </TemperatureControl>
Type	<b>Type</b> xs:string <b>Use</b> required
Uom	<b>Type</b> xs:string
xs:sequence	<b>Occurrence</b> 1 .. 1
Fixed	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
RangeDetails	<b>Occurrence</b> 0 .. 1 <b>Type</b> RangeDetails <b>General Notes</b> LINE ITEM TEMPERATURE RANGE <b>Examples</b> <RangeDetails Type="Allowance" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> TEMPERATURE RANGE TYPE <b>Applicable Codes</b> Allowance Temperature Range Allowance
Uom	<b>Type</b> xs:string <b>General Notes</b> TEMPERATURE RANGE UNIT OF MEASURE <b>Applicable Codes</b> CEL Celsius FAH Fahrenheit
xs:sequence	<b>Occurrence</b> 1 .. 1
Minimum	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>General Notes</b> MINIMUM TEMPERATAURE
Maximum	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MAXIMUM TEMPERATAURE
Locations	<b>Occurrence</b> 0 .. 1 <b>Type</b> LocationGroupList <b>General Notes</b> LINE ITEM COUNTRY OF ORIGIN  <b>Examples</b> <Locations> <LocationGroup> <Location Type="CountryOfOrigin"> <LocationIdentification Type="ISOCountry"> <LocationIdentifier>DK</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationGroup	<b>Occurrence</b> 0 .. unbounded <b>Type</b> LocationGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
Location	<b>Occurrence</b> 0 .. 1 <b>Type</b> Location
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> LOCATION TYPE  <b>Applicable Codes</b> <b>CountryOfOrigin</b> Line item Country of Origin
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationIdentification	<b>Occurrence</b> 1 .. unbounded <b>Type</b> LocationIdentification
Type	<b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER TYPE  <b>Applicable Codes</b> <b>ISOCountry</b> ISO Country Code
xs:sequence	<b>Occurrence</b> 1 .. 1
LocationIdentifier	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER ISO Country Code for Country of Origin
MonetaryAmounts	<b>Occurrence</b> 0 .. 1 <b>Type</b> MonetaryAmountList <b>General Notes</b> LINE ITEM MONETARY AMOUNTS  <b>Examples</b> <MonetaryAmounts> <MonetaryAmount Type="LineInvoiceValue"> <Amount>100.01</Amount> <Currency>DKK</Currency> </MonetaryAmount> </MonetaryAmounts>
xs:sequence	<b>Occurrence</b> 1 .. 1
MonetaryAmount	<b>Occurrence</b> 0 .. unbounded <b>Type</b> MonetaryAmount

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute		Annotation
	Type	Type xs:string Use required <b>General Notes</b> MONETARY AMOUNT TYPE
		<b>Applicable Codes</b>
		<b>LineInvoiceValue</b> Line Item Invoice Value
	xs:sequence	Occurrence 1 .. 1
	Amount	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> MONETARY AMOUNT
	Currency	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> MONETARY AMOUNT ISO CURRENCY CODE
		<b>Applicable Codes</b>
		<b>InvoiceValue</b>
	ProductIds	Occurrence 0 .. 1 Type ProductIdsList <b>General Notes</b> LINE ITEM PRODUCT IDENTIFICATION
		<b>Examples</b> <ProductIds> <ProductId Type="ProductId"> <ItemId>ITEM ID</ItemId> <ItemType>HarmonizedCode</ItemType> </ProductId> </ProductIds>
	xs:sequence	Occurrence 1 .. 1
	ProductId	Occurrence 0 .. unbounded Type ProductId
	Type	Type xs:string Use required <b>General Notes</b> PRODUCT IDENTIFICATION TYPE
		<b>Applicable Codes</b>
		<b>ProductId</b> Product Identification
	xs:sequence	Occurrence 1 .. 1
	ItemId	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PRODUCT IDENTIFICATION
	ItemType	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> PRODUCT IDENTIFIER TYPE
		<b>Applicable Codes</b>
		<b>CommodityCode</b> Commodity Code
		<b>HarmonizedCode</b> Harmonized Tariff Code
	FreeTextData	Occurrence 0 .. 1 Type FreeTextList <b>General Notes</b> LINE ITEM FREE TEXT
		<b>Examples</b> <FreeTextData> <FreeText Type="GoodsDescription"> <TextLine1>Goods Description Line</TextLine1> </FreeText> <FreeText Type="AdditionalDetails"> <TextLine1>Additional Details Line</TextLine1> </FreeText> </FreeTextData>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> </FreeTextData>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> FreeText
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> FREE TEXT TYPE
	<b>Applicable Codes</b> <b>AdditionalDetails</b> Additional Details <b>ConsignmentDetails</b> Consignment Details (Status, RegDate, Remarks, Originater) <b>DeliveryInstructions</b> Delivery Instructions <b>DeliveryRemarks</b> Delivery Remarks <b>GeneralInformation</b> General information <b>GoodsDescription</b> Goods Description <b>MarinePollutant</b> DG Marine Pollutant <b>NatureOfGoods</b> Nature Of Goods <b>PickupInstructions</b> Pickup Instructions <b>ProperShippingName</b> DG Proper Shipping Name <b>ReportInformation</b> Report Information <b>SpecialHandling</b> Special Handling <b>SpecialInstructions</b> Special Instructions <b>StatusRemarks</b> Status Remarks
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DescriptionCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT DESCRIPTION CODE
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 1
<b>TextLine2</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 2
<b>TextLine3</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 3
<b>TextLine4</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 4
<b>TextLine5</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 5
<b>Measurements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> MeasurementList <b>General Notes</b> LINE ITEM MEASUREMENTS <b>Examples</b> <Measurements> <Measurement Type="GrossWeight" Uom="KGM"> <Measure>10.03</Measure> </Measurement> <Measurement Type="NetWeight" Uom="KGM"> <Measure>8.03</Measure>

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation										
	<b>Examples</b> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.03</Measure> </Measurement> <Measurement Type="LoadingMeters" Uom="MTR"> <Measure>2.05</Measure> </Measurement> <Measurement Type="PalletSpaces" Uom="PLL"> <Measure>5</Measure> </Measurement> </Measurements>										
xs:sequence	<b>Occurrence</b> 1 .. 1										
<b>Measurement</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Measurement										
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> MEASUREMENT TYPE										
	<b>Applicable Codes</b> <table> <tr> <td><b>GrossWeight</b></td><td>Line Item Gross Weight</td></tr> <tr> <td><b>LoadingMeters</b></td><td>Line Item Loading Meters</td></tr> <tr> <td><b>NetWeight</b></td><td>Line Item Net Weight</td></tr> <tr> <td><b>PalletSpaces</b></td><td>Line Item Pallet Spaces</td></tr> <tr> <td><b>Volume</b></td><td>Line Item Volume</td></tr> </table>	<b>GrossWeight</b>	Line Item Gross Weight	<b>LoadingMeters</b>	Line Item Loading Meters	<b>NetWeight</b>	Line Item Net Weight	<b>PalletSpaces</b>	Line Item Pallet Spaces	<b>Volume</b>	Line Item Volume
<b>GrossWeight</b>	Line Item Gross Weight										
<b>LoadingMeters</b>	Line Item Loading Meters										
<b>NetWeight</b>	Line Item Net Weight										
<b>PalletSpaces</b>	Line Item Pallet Spaces										
<b>Volume</b>	Line Item Volume										
<i>Uom</i>	<b>Type</b> xs:string <b>General Notes</b> MEASUREMENT UNIT OF MEASURE										
	<b>Applicable Codes</b> <table> <tr> <td><b>KGM</b></td><td>Kilograms</td></tr> <tr> <td><b>MTQ</b></td><td>Cubic Meters</td></tr> <tr> <td><b>MTR</b></td><td>Linear Meters</td></tr> <tr> <td><b>PLL</b></td><td>Pallets</td></tr> </table>	<b>KGM</b>	Kilograms	<b>MTQ</b>	Cubic Meters	<b>MTR</b>	Linear Meters	<b>PLL</b>	Pallets		
<b>KGM</b>	Kilograms										
<b>MTQ</b>	Cubic Meters										
<b>MTR</b>	Linear Meters										
<b>PLL</b>	Pallets										
xs:sequence	<b>Occurrence</b> 1 .. 1										
<b>Measure</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MEASUREMENT VALUE										
<b>Dimensions</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DimensionsList <b>General Notes</b> LINE ITEM DIMENSIONS										
	<b>Examples</b> <Dimensions> <Dimension Type="Gross" Uom="MTR"> <Length>0.6</Length> <Width>0.2</Width> <Height>0.8</Height> </Dimension> </Dimensions>										
xs:sequence	<b>Occurrence</b> 1 .. 1										
<b>Dimension</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Dimension										
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> DIMENSION TYPE										
	<b>Applicable Codes</b> <table> <tr> <td><b>Consignment</b></td><td>Consignment Dimensions</td></tr> </table>	<b>Consignment</b>	Consignment Dimensions								
<b>Consignment</b>	Consignment Dimensions										

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>GoodsItem</b> Goods Item Dimensions <b>Gross</b> Line Item Gross Dimensions
<i>Uom</i>	<b>Type</b> xs:string <b>General Notes</b> DIMENSIONS UNIT OF MEASURE <b>Applicable Codes</b> <b>CMT</b> Centimeters <b>MTR</b> Meters
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Length</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION - LENGTH
<b>Width</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION - WIDTH
<b>Height</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION - HEIGHT
<b>NumberOfUnits</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION - NUMBER OF UNITS
<b>References</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ReferenceGroupList <b>General Notes</b> GOODS ITEM REFERENCES <b>Examples</b> <References> <ReferenceGroup> <Reference Type="OrderLineNumber">10</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="Agreed" CustomFieldType="String">ABCDEFGH</Reference> </ReferenceGroup> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Reference
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> GOODS ITEM REFERENCE <b>Applicable Codes</b> <b>PackListLineId</b> Pack List Line Identifier <b>PackageNumber</b> Package Number
<b>Packagelds</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Packagelds <b>General Notes</b> PACKAGE IDENTIFICATION AND MARKINGS <b>Examples</b> <Packagelds> <Packageld> <InstructionCode>PackageMarks</InstructionCode>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> <Marks> <ShippingMark>Package1</ShippingMark> <ShippingMark>Package2</ShippingMark> <ShippingMark>Package3</ShippingMark> </Marks> </PackageId> <GoodsIdentities Type="SerialNumber"> <GoodsIdentifier>12345678912345678900</GoodsIdentifier> <GoodsIdentifier>78945612332145698712</GoodsIdentifier> <GoodsIdentifier>85296374125814736979</GoodsIdentifier> </GoodsIdentities> <GoodsIdentities Type="SSCC"> <GoodsIdentifier>SSCC Code</GoodsIdentifier> <GoodsIdentifier>SSCC Code</GoodsIdentifier> <GoodsIdentifier>SSCC Code</GoodsIdentifier> </GoodsIdentities> </PackageIds>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PackageId</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> PackageId <b>General Notes</b> PACKAGE MARKS & NUMBERS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>InstructionCode</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> PACKAGE MARKS TYPE
	<b>Applicable Codes</b> <b>PackageMarks</b> Package Marks and Numbers
<b>Marks</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Marks
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ShippingMark</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> xs:string <b>General Notes</b> PACKAGE MARK
<b>GoodsIdentities</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> GoodsIdentity <b>General Notes</b> PACKAGE BAR CODES
<b>Type</b>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> TYPE OF IDENTIFIER
	<b>Applicable Codes</b> <b>SSCC</b> Serial Shipping Container Code <b>SerialNumber</b> Package/Pallet Serial Number
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>GoodsIdentifier</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> xs:string <b>General Notes</b> GOODS IDENTIFIER  SSCC codes should not include the leading "00" qualifier, length of value should be 18 characters
<b>GoodsPlacementIds</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> GoodsPlacementIds <b>General Notes</b> GOODS PLACEMENT For containerized Sea Freight, container number the line

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<p>item is packed in</p> <p><b>Examples</b></p> <pre>&lt;GoodsPlacementIds&gt;   &lt;GoodsPlacementId&gt;123456789&lt;/GoodsPlacementId&gt; &lt;/GoodsPlacementIds&gt;</pre>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>GoodsPlacementId</b>	<p><b>Occurrence</b> 1 .. unbounded</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> SHIPPING CONTAINER NUMBER</p>
<b>DangerousGoodsDetails</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> DangerousGoodsDetailList</p> <p><b>General Notes</b> DANGEROUS / HAZARDOUS GOODS DETAILS</p> <p>Only included if line item contains dangerous/hazardous cargo</p> <p><b>Examples</b></p> <pre>&lt;DangerousGoodsDetails&gt; &lt;DangerousGoodsDetail&gt; &lt;DangerousGoods&gt;   &lt;Regulation&gt;ADR&lt;/Regulation&gt;   &lt;HazardClass&gt;9&lt;/HazardClass&gt;   &lt;AdditionalHazardClass&gt;3&lt;/AdditionalHazardClass&gt;   &lt;HazardVersionId&gt;5&lt;/HazardVersionId&gt;   &lt;UNDGNumber&gt;3082&lt;/UNDGNumber&gt;   &lt;FlashPointDescription&gt;FlashDesc&lt;/FlashPointDescription&gt;   &lt;FlashPointTemperature FlashpointUom="CEL"&gt;10&lt;/FlashPointTemperature&gt;   &lt;DangerLevelCode&gt;III&lt;/DangerLevelCode&gt;   &lt;EMSNumber&gt;EMS No&lt;/EMSNumber&gt;   &lt;MFAGNumber&gt;MFAG No&lt;/MFAGNumber&gt;   &lt;TremCardNumber&gt;Trem No&lt;/TremCardNumber&gt;   &lt;UpperPlate&gt;Upper&lt;/UpperPlate&gt;   &lt;LowerPlate&gt;Lower&lt;/LowerPlate&gt;   &lt;Labels&gt;     &lt;Label&gt;Lab1&lt;/Label&gt;   &lt;/Labels&gt;   &lt;TunnelCode&gt;E&lt;/TunnelCode&gt;   &lt;FreeTextData&gt;     &lt;FreeText Type="MarinePollutant"&gt;       &lt;TextLine&gt;MP&lt;/TextLine&gt;     &lt;/FreeText&gt;     &lt;FreeText Type="ProperShippingName"&gt;       &lt;TextLine&gt;Proper Shipping Name&lt;/TextLine&gt;     &lt;/FreeText&gt;     &lt;FreeText Type="TechnicalName"&gt;       &lt;TextLine&gt;Technical Name&lt;/TextLine&gt;     &lt;/FreeText&gt;     &lt;FreeText Type="IntTechnicalName"&gt;       &lt;TextLine&gt;Int Technical Name&lt;/TextLine&gt;     &lt;/FreeText&gt;     &lt;FreeText Type="DGAdditionalInfo"&gt;       &lt;TextLine&gt;DG Additional Info Line&lt;/TextLine&gt;     &lt;/FreeText&gt;   &lt;/FreeTextData&gt;   &lt;Measurements&gt;     &lt;Measurement Type="NetWeight" Uom="KGM"&gt;       &lt;Measure&gt;5.01&lt;/Measure&gt;     &lt;/Measurement&gt;   &lt;/Measurements&gt; &lt;/DangerousGoodsDetail&gt; &lt;/DangerousGoodsDetails&gt;</pre>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> <Measurement Type="ExplosiveWeight" Uom="KGM"> <Measure>2.02</Measure> </Measurement> <Measurement Type="NumberOfPackages" Uom="PKG"> <Measure>3</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.002</Measure> </Measurement> </Measurements> <Quantities> <Quantity Type="NetWeight" Uom="KGM"> <Quantity>5.01</Quantity> </Quantities> </DangerousGoods> </DangerousGoodsDetail> </DangerousGoodsDetails>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DangerousGoodsDetail</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> DangerousGoodsDetail
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DangerousGoods</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DangerousGoods <b>General Notes</b> DANGEROUS GOODS INFORMATION  <b>Examples</b> <DangerousGoods> <Regulation>ADR</Regulation> <HazardClass>9</HazardClass> <AdditionalHazardClass>3</AdditionalHazardClass> <HazardVersionId>5</HazardVersionId> <UNDGNumber>3082</UNDGNumber> <FlashPointDescription>FlashDesc</FlashPointDescription> <FlashPointTemperature FlashpointUom="CEL">10</FlashPointTemperature> <DangerLevelCode>III</DangerLevelCode> <EMSNumber>EMS No</EMSNumber> <MFAGNumber>MFAG No</MFAGNumber> <TremCardNumber>Trem No</TremCardNumber> <UpperPlate>Upper</UpperPlate> <LowerPlate>Lower</LowerPlate> <Labels> <Label>Lab1</Label> </Labels> <TunnelCode>E</TunnelCode> </DangerousGoods>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Regulation</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DANGEROUS GOODS REGULATION TYPE  <b>Applicable Codes</b> ADR European Road Agreement IMO IMO IMDG
<b>HazardClass</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> HAZARDOUS CLASS

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute				Annotation
			<b>AdditionalHazardClass</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> ADDITIONAL HAZARDOUS CLASS / SUBRISK
			<b>HazardVersionId</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> HAZARDOUS VERSION ID
			<b>UNDGNumber</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> UNDG NUMBER
			<b>FlashPointDescription</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> FLASH POINT DESCRIPTION
			<b>FlashPointTemperature</b>	Occurrence 0 .. 1 Type extension (xs:string) <b>General Notes</b> FLASHPOINT TEMPERATURE Integer value only
			<i>FlashpointUom</i>	Type xs:string <b>General Notes</b> FLASHPOINT TEMPERATURE UNIT OF MEASURE <b>Applicable Codes</b> CEL Celsius FAH Fahrenheit
			<b>DangerLevelCode</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> DANGER LEVEL CODE / PACKING GROUP <b>Applicable Codes</b> I Packing Group I - Great danger II Packing Group II - Medium danger III Packing Group III - Minor danger
			<b>EMSNumber</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> EMERGENCY SCHEDULE NUMBER
			<b>MFAGNumber</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> MEDICAL FIRST AID GUIDE
			<b>TremCardNumber</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> TREMCARD NUMBER
			<b>UpperPlate</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> ORANGE HAZARD PLACARD UPPER PLATE
			<b>LowerPlate</b>	Occurrence 0 .. 1 Type xs:string <b>General Notes</b> ORANGE HAZARD PLACARD LOWER PLATE
			<b>Labels</b>	Occurrence 0 .. 1 <b>General Notes</b> HAZARDOUS LABELS
			<i>xs:sequence</i>	Occurrence 1 .. 1
			<b>Label</b>	Occurrence 1 .. 4 Type xs:string <b>General Notes</b> HAZARDOUS LABEL

Bold = Element, *Italic* = Attribute, Grey = Group





Element/Attribute			Annotation										
		<div>PackingInstruction</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div> <div>General NotesPACKING INSTRUCTION</div>										
		<div>TransportMeansCode</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div> <div>General NotesTRANSPORT MEANS CODE</div>										
		<div>TunnelCode</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div> <div>General NotesTUNNEL CODE</div>										
		<div>FreeTextData</div>	<div>Occurence0 .. 1</div> <div>TypeFreeTextList</div> <div>General NotesDANGEROUS GOODS FREE TEXT</div> <div>Examples&lt;FreeTextData&gt;&lt;FreeText Type="MarinePollutant"&gt;&lt;TextLine&gt;MP&lt;/TextLine&gt;&lt;/FreeText&gt;&lt;FreeText Type="ProperShippingName"&gt;&lt;TextLine&gt;Proper Shipping Name&lt;/TextLine&gt;&lt;/FreeText&gt;&lt;FreeText Type="TechnicalName"&gt;&lt;TextLine&gt;Technical Name&lt;/TextLine&gt;&lt;/FreeText&gt;&lt;FreeText Type="IntTechnicalName"&gt;&lt;TextLine&gt;Int Technical Name&lt;/TextLine&gt;&lt;/FreeText&gt;&lt;FreeText Type="DGAdditionalInfo"&gt;&lt;TextLine&gt;DG Additional Info Line&lt;/TextLine&gt;&lt;/FreeText&gt;&lt;/FreeTextData&gt;</div>										
		<div>xs:sequence</div>	<div>Occurence1 .. 1</div>										
		<div>FreeText</div>	<div>Occurence0 .. unbounded</div> <div>TypeFreeText</div>										
		<div>Type</div>	<div>Typexs:string</div> <div>Userequired</div> <div>General NotesFREE TEXT TYPE</div> <div>Applicable Codes</div> <table><tr><td>DGAdditionalInfo</td><td>Additional Dangerous Goods Information</td></tr><tr><td>IntTechnicalName</td><td>Dangerous Goods Int. Technical Name</td></tr><tr><td>MarinePollutant</td><td>Marine Pollutant</td></tr><tr><td>ProperShippingName</td><td>Dangerous Goods Proper Shipping Name</td></tr><tr><td>TechnicalName</td><td>Dangerous Goods Technical Name</td></tr></table>	DGAdditionalInfo	Additional Dangerous Goods Information	IntTechnicalName	Dangerous Goods Int. Technical Name	MarinePollutant	Marine Pollutant	ProperShippingName	Dangerous Goods Proper Shipping Name	TechnicalName	Dangerous Goods Technical Name
DGAdditionalInfo	Additional Dangerous Goods Information												
IntTechnicalName	Dangerous Goods Int. Technical Name												
MarinePollutant	Marine Pollutant												
ProperShippingName	Dangerous Goods Proper Shipping Name												
TechnicalName	Dangerous Goods Technical Name												
		<div>xs:sequence</div>	<div>Occurence1 .. 1</div>										
		<div>DescriptionCode</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div> <div>General NotesDG FREE TEXT DESCRIPTION CODE</div>										
		<div>TextLine1</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div> <div>General NotesDG FREE TEXT LINE 1</div>										
		<div>TextLine2</div>	<div>Occurence0 .. 1</div> <div>Typexs:string</div>										

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>General Notes</b> DG FREE TEXT LINE 2
TextLine3	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DG FREE TEXT LINE 3
TextLine4	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DG FREE TEXT LINE 4
TextLine5	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DG FREE TEXT LINE 5
Measurements	<b>Occurrence</b> 0 .. 1 <b>Type</b> MeasurementList <b>General Notes</b> DANGEROUS GOODS MEASUREMENTS  <b>Examples</b> <Measurements> <Measurement Type="NetWeight" Uom="KGM"> <Measure>5.01</Measure> </Measurement> <Measurement Type="ExplosiveWeight" Uom="KGM"> <Measure>2.02</Measure> </Measurement> <Measurement Type="NumberOfPackages" Uom="PKG"> <Measure>3</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.002</Measure> </Measurement> </Measurements>
xs:sequence	<b>Occurrence</b> 1 .. 1
Measurement	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Measurement
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> MEASUREMENT TYPE  <b>Applicable Codes</b> <b>ExplosiveWeight</b> Dangerous Goods Explosive Weight <b>LoadingMeters</b> Loading Meters <b>NetNetWeight</b> Dangerous Goods Net Weight
Uom	<b>Type</b> xs:string <b>General Notes</b> MEASUREMENT UNIT OF MEASURE  <b>Applicable Codes</b> <b>KGM</b> Kilograms <b>PCE</b> Pieces
xs:sequence	<b>Occurrence</b> 1 .. 1
Measure	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MEASURE
Quantities	<b>Occurrence</b> 0 .. 1 <b>Type</b> QuantitiesList <b>General Notes</b> DANGEROUS GOODS QUANTITIES  <b>Examples</b> <Quantities>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> <Quantity Type="NetWeight" Uom="KGM"> <Quantity>5.01</Quantity> </Quantities>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Quantity</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Quantity
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> QUANTITY TYPE
	<b>Applicable Codes</b> <b>NumberOfPackages</b> Number of Dangerous Goods Packages
Uom	<b>Type</b> xs:string <b>General Notes</b> QUANTITY UNIT OF MEASURE
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Quantity</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> QUANTITY
<b>ContainerNumber</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPPING CONTAINER NUMBER
	<b>Examples</b> <ContainerNumber>ADFC5689</ContainerNumber>
<b>EquipmentUnits</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> EquipmentUnitList <b>General Notes</b> EQUIPMENT INFORMATION
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>EquipmentUnit</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> EquipmentUnit <b>General Notes</b> EQUIPMENT UNIT DETAILS
	<b>Examples</b> For containerized sea freight: <EquipmentUnit> <EquipmentType> <Type>Container</Type> <UnitId>MSCU1234567</UnitId> <SizeTypeCode>40GP</SizeTypeCode> </EquipmentType> <SealIds> <Seal> <SealId>Seal1</SealId> <SealParty>Shipper</SealParty> </Seal> </SealIds> </EquipmentUnit> For EUR pallet road freight: <EquipmentUnit> <EquipmentType> <Type>EFP</Type> </EquipmentType>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation														
	<b>Examples</b> <NumberOfUnits>3</NumberOfUnits> </EquipmentUnit>														
xs:sequence	<b>Occurrence</b> 1 .. 1														
<b>EquipmentType</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> EquipmentType <b>General Notes</b> EQUIPMENT TYPE INFORMATION  <b>Examples</b> <EquipmentType> <Type>Container</Type> <UnitId>UNIT ID</UnitId> <SizeTypeCode>12AB</SizeTypeCode> <ISOCODE>13B1</ISOCODE> <PackingMode>FCL</PackingMode> <FullOrEmptyIndicator>Full</FullOrEmptyIndicator> </EquipmentType>														
xs:sequence	<b>Occurrence</b> 1 .. 1														
<b>Type</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> EQUIPMENT TYPE  <b>Applicable Codes</b> <table> <tr> <td><b>Container</b></td><td>Shipping Container</td></tr> <tr> <td><b>EFB</b></td><td>Euro Flat Pallet</td></tr> <tr> <td><b>EUR</b></td><td>Euro Pallet</td></tr> </table>	<b>Container</b>	Shipping Container	<b>EFB</b>	Euro Flat Pallet	<b>EUR</b>	Euro Pallet								
<b>Container</b>	Shipping Container														
<b>EFB</b>	Euro Flat Pallet														
<b>EUR</b>	Euro Pallet														
<b>UnitId</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPPING CONTAINER NUMBER														
<b>SizeTypeCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTAINER SIZE AND TYPE DSV specified Container Type for Shipping Container  <b>Applicable Codes</b> <table> <tr> <td><b>20GP</b></td><td>20 ft General Purpose</td></tr> <tr> <td><b>20RE</b></td><td>20 ft Reefer</td></tr> <tr> <td><b>40GP</b></td><td>40 ft General Purpose</td></tr> <tr> <td><b>40HC</b></td><td>40 ft High Cube</td></tr> <tr> <td><b>40NOR</b></td><td>40 ft high Cube, self powered Reefer</td></tr> <tr> <td><b>40RE</b></td><td>40 ft Reefer</td></tr> <tr> <td><b>40REHC</b></td><td>40 ft High Cube Reefer</td></tr> </table>	<b>20GP</b>	20 ft General Purpose	<b>20RE</b>	20 ft Reefer	<b>40GP</b>	40 ft General Purpose	<b>40HC</b>	40 ft High Cube	<b>40NOR</b>	40 ft high Cube, self powered Reefer	<b>40RE</b>	40 ft Reefer	<b>40REHC</b>	40 ft High Cube Reefer
<b>20GP</b>	20 ft General Purpose														
<b>20RE</b>	20 ft Reefer														
<b>40GP</b>	40 ft General Purpose														
<b>40HC</b>	40 ft High Cube														
<b>40NOR</b>	40 ft high Cube, self powered Reefer														
<b>40RE</b>	40 ft Reefer														
<b>40REHC</b>	40 ft High Cube Reefer														
<b>ISOCODE</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPPING CONTAINER ISO CODE														
<b>PackingMode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>Applicable Codes</b> <table> <tr> <td><b>FCL</b></td><td>Full Container Load</td></tr> <tr> <td><b>LCL</b></td><td>Less than full Container Load</td></tr> </table>	<b>FCL</b>	Full Container Load	<b>LCL</b>	Less than full Container Load										
<b>FCL</b>	Full Container Load														
<b>LCL</b>	Less than full Container Load														
<b>EquipmentSizeDescription</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string														
<b>FullOrEmptyIndicator</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FULL OR EMPTY INDICATOR														

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>Empty</b> Empty <b>Full</b> Full
<b>NumberOfUnits</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:decimal <b>General Notes</b> NUMBER OF UNITS For Road freight pallets Only used for Returnable items.  <b>Examples</b> <NumberOfUnits>1</NumberOfUnits>
<b>Measurements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> MeasurementList <b>General Notes</b> EQUIPMENT MEASUREMENTS  <b>Examples</b> <Measurements> <Measurement Type="Volume" Uom="KGM"> <Measure>12.5</Measure> </Measurement> </Measurements>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Measurement</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Measurement
<b>Type</b>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> EQUIPMENT MEASUREMENT TYPE  <b>Applicable Codes</b> <b>TareWeight</b> <b>Volume</b> <b>Weight</b>
<b>Uom</b>	<b>Type</b> xs:string <b>General Notes</b> EQUIPMENT MEASUREMENT UNIT OF MEASURE  <b>Applicable Codes</b> <b>KGM</b> Kilograms <b>MTQ</b> Cubic metres
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Measure</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> EQUIPMENT MEASUREMENT
<b>Dimensions</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DimensionsList <b>General Notes</b> EQUIPMENT DIMENSIONS  <b>Examples</b> <Dimensions Type="Container" Uom="MTR"> <Length>2.5</Length> <Width>5</Width> <Height>3</Height> <Dimension> </Dimension> </Dimensions>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Dimension</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Dimension

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	<i>Type</i>	Type xs:string Use required <b>General Notes</b> EQUIPMENT DIMENSION TYPE
		<b>Applicable Codes</b>
		<b>Container</b>
	<i>Uom</i>	Type xs:string <b>General Notes</b> EQUIPMENT DIMENSION UNIT OF MEASURE
		<b>Applicable Codes</b>
		<b>MTR</b>
	xs:sequence	<b>Occurrence</b> 1 .. 1
	<b>Length</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> EQUIPMENT DIMENSION LENGTH
	<b>Width</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> EQUIPMENT DIMENSION WIDTH
	<b>Height</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> EQUIPMENT DIMENSION HEIGHT
	<b>SealIds</b>	<b>Occurrence</b> 0 .. 1 Type SealList <b>General Notes</b> SEAL INFORMATION FOR SHIPPING CONTAINERS
		<b>Examples</b> <SealIds> <Seal> <SealId>XX-12345678</SealId> </Seal> </SealIds>
	xs:sequence	<b>Occurrence</b> 1 .. 1
	<b>Seal</b>	<b>Occurrence</b> 0 .. unbounded Type Seal
	xs:sequence	<b>Occurrence</b> 1 .. 1
	<b>SealId</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> SEAL NUMBER
	<b>SealParty</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> SEALING PARTY
		<b>Applicable Codes</b>
		<b>Shipper</b> Shipper Sealing Party
	<b>References</b>	<b>Occurrence</b> 0 .. 1 Type ReferenceGroupList <b>General Notes</b> EQUIPMENT REFERENCES
		<b>Examples</b> <References> <ReferenceGroup> <Reference Type="PackingMode">FCL</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="DeliveryMode">FCL</Reference> </ReferenceGroup>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> Reference <b>General Notes</b> EQUIPMENT REFERENCE
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> EQUIPMENT REFERENCE TYPE
	<b>Applicable Codes</b> <b>DeliveryMode</b> Container Delivery Mode <b>InterimUnitId</b> <b>PackingMode</b> Container Packing Mode <b>VerificationMethod</b> <b>VerificationStatus</b>
<b>Dates</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DateList <b>General Notes</b> CONTAINER DATES  <b>Examples</b> <Dates> <Date Format="DateTimeSec" Type="EstimatedCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="RequestedCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="ScheduledCollection"> <DateTime>20250818120500</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualCollection"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedDelivery"> <DateTime>20250802124800</DateTime> </Date> <Date Format="DateTimeSec" Type="ActualDelivery"> <DateTime>20250823090200</DateTime> </Date> <Date Format="DateTimeSec" Type="EstimatedFullPickup"> <DateTime>20250830000000</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLOnBoardVessel"> <DateTime>20250806013500</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLUnloadFromVessel"> <DateTime>20250815135900</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateIn"> <DateTime>20250801085600</DateTime> </Date> <Date Format="DateTimeSec" Type="FCLWharfGateOut"> <DateTime>20250818101000</DateTime> </Date> <Date Format="DateTimeSec"

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> Type="ContainerParkEmptyPickupGateOut"> <DateTime>20250830121700</DateTime> </Date> </Dates>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Date</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Date
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> CONTAINER DATE TYPE
	<b>Applicable Codes</b>
	<b>VerifiedDate</b>
<i>Format</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> CONTAINER DATE FORMAT
	<b>Applicable Codes</b>
	<b>DateTimeInterval</b>
	<b>DateTimeSec</b>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTAINER DATE/TIME
<b>TransportMovements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportMovementList <b>General Notes</b> EQUIPMENT TRANSPORT MOVEMENTS
	<b>Examples</b> <TransportMovements> <TransportMovement Type="DeliveryMode"> <Code>CFS</Code> <Description>DSC</Description> </TransportMovement> </TransportMovements>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportMovement</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> CodeDescription
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> optional <b>Applicable Codes</b>
	<b>DeliveryMode</b>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Code</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> EQUIPMENT MOVEMENT CODE
	<b>Applicable Codes</b>
	CFS/CFS
	CFS/CY
	CFS/DR
	CY/CFS
	CY/CY
	CY/DR
	DR/CFS
	DR/CY
	DR/DR

Bold = Element, *Italic* = Attribute, Grey = Group





Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>FCL/FCL</b> <b>FCL/LCL</b> <b>LCL/FCL</b> <b>LCL/LCL</b> <b>RO/RO</b>
Description	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> EQUIPMENT MOVEMENT DESCRIPTION
TransportServices	<b>Occurrence</b> 0 .. 1 <b>Type</b> ServiceGroupList <b>General Notes</b> EQUIPMENT UNIT TRANSPORT SERVICES  <b>Examples</b> <pre> &lt;TransportServices&gt; &lt;ServiceGroup&gt; &lt;TransportService&gt; &lt;ServiceCode&gt;FCL&lt;/ServiceCode&gt; &lt;PriorityCode&gt;Normal&lt;/PriorityCode&gt; &lt;/TransportService&gt; &lt;/ServiceGroup&gt; &lt;ServiceGroup&gt; &lt;TransportService&gt; &lt;ServiceCode&gt;STD&lt;/ServiceCode&gt; &lt;FreeTextData&gt;   &lt;FreeText Type="ServiceNote"&gt;     &lt;TextLine1&gt;DeliveryInstructions Text Line 1&lt;/TextLine1&gt;   &lt;/FreeText&gt; &lt;/FreeTextData&gt; &lt;Dates&gt;   &lt;Date Type="BookedDate" Format="DateTimeSec"&gt;     &lt;DateTime&gt;202508130900&lt;/DateTime&gt;   &lt;/Date&gt; &lt;/Dates&gt; &lt;Parties&gt; &lt;Party&gt; &lt;PartyDetails Role="Contractor"&gt; &lt;Id&gt;123456789&lt;/Id&gt; &lt;Assignor&gt;DSV&lt;/Assignor&gt; &lt;PartyName&gt;AXDFR&lt;/PartyName&gt; &lt;AddressLine1&gt;XYZ&lt;/AddressLine1&gt; &lt;AddressLine2&gt;ABC&lt;/AddressLine2&gt; &lt;CityName&gt;CITY NAME&lt;/CityName&gt; &lt;PostCode&gt;PO CODE&lt;/PostCode&gt; &lt;CountryCode&gt;XY&lt;/CountryCode&gt; &lt;/PartyDetails&gt; &lt;Contact Type="InformationContact"&gt; &lt;Name&gt;CONTACT NAME&lt;/Name&gt; &lt;Phone&gt;123456789&lt;/Phone&gt; &lt;/Contact&gt; &lt;/Party&gt; &lt;/Parties&gt; &lt;References&gt; &lt;ReferenceGroup&gt;   &lt;Reference Type="ServiceReference"&gt;SerRef1&lt;/Reference&gt;   &lt;Date Type="ReferenceDate" Format="DateTimeSec"&gt;     &lt;DateTime&gt;20250803&lt;/DateTime&gt;   &lt;/Date&gt; &lt;/ReferenceGroup&gt; &lt;/References&gt; &lt;/TransportService&gt; </pre>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> </ServiceGroup> </TransportServices>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ServiceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportService</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> TransportService <b>Examples</b> <TransportService> <ServiceCode>LTL</ServiceCode> </TransportService>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ServiceCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>FreeTextData</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> FreeTextList <b>Examples</b> <FreeTextData> <FreeText Type="ServiceDescription"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> FreeText
Type	<b>Type</b> xs:string <b>Use</b> required
<b>Applicable Codes</b>	
<b>ServiceDescription</b>	
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>FreeText &lt;Notes&gt;</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> FreeText <b>Examples</b> <FreeTextData> <FreeText Type="ServiceNote"> <TextLine1>DeliveryInstructions Text Line 1</TextLine1> </FreeText> </FreeTextData>
Type	<b>Type</b> xs:string <b>Use</b> required
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Dates</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> DateList <b>Examples</b> <Dates> <Date Type="BookedDate" Format="DateTimeSec"> <DateTime>202508130900</DateTime> </Date>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>Examples</b> </Dates>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Date</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Date
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required
<i>Format</i>	<b>Type</b> xs:string <b>Use</b> required
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<b>Parties</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartiesList  <b>Examples</b> <Parties> <Party> <PartyDetails Role="Contractor"> <Id>123456789</Id> <Assignor>DSV</Assignor> <PartyName>AXDFR</PartyName> <AddressLine1>XYZ</AddressLine1> <AddressLine2>ABC</AddressLine2> <CityName>CITY NAME</CityName> <PostCode>PO CODE</PostCode> <CountryCode>XY</CountryCode> </PartyDetails> <Contact Type="InformationContact"> <Name>CONTACT NAME</Name> <Phone>123456789</Phone> </Contact> </Party> </Parties>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Party</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Party
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PartyDetails</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartyDetails
<i>Role</i>	<b>Type</b> xs:string <b>Use</b> required
<i>AddressOverride</i>	<b>Type</b> xs:boolean <b>Default</b> false <b>Use</b> optional
xs:sequence	<b>Occurrence</b> 1 .. 1
<i>Id</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<i>Assignor</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<i>PartyName</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<i>AddressLine1</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<i>AddressLine2</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
<i>AddressLine3</i>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute		Annotation	
	<b>CityName</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>State</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>PostCode</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>CountryCode</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Locations</b>	Occurrence	0 .. 1
		Type	LocationGroupList
	xs:sequence	Occurrence	1 .. 1
	<b>LocationGroup</b>	Occurrence	0 .. unbounded
		Type	LocationGroup
	xs:sequence	Occurrence	1 .. 1
	<b>Location</b>	Occurrence	0 .. 1
		Type	Location
	Type	Type	xs:string
		Use	required
	xs:sequence	Occurrence	1 .. 1
	<b>LocationIdentification</b>	Occurrence	1 .. unbounded
		Type	LocationIdentification
	Type	Type	xs:string
	xs:sequence	Occurrence	1 .. 1
	<b>LocationIdentifier</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>LocationName</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Contact</b>	Occurrence	0 .. unbounded
		Type	Contact
	Type	Type	xs:string
		Use	required
	xs:sequence	Occurrence	1 .. 1
	<b>ContactId</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Name</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Phone</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Mobile</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Fax</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>Email</b>	Occurrence	0 .. 1
		Type	xs:string
	<b>References</b>	Occurrence	0 .. 1
		Type	ReferenceGroupList
	xs:sequence	Occurrence	1 .. 1
	<b>ReferenceGroup</b>	Occurrence	0 .. unbounded
		Type	ReferenceGroup
	xs:sequence	Occurrence	1 .. 1
	<b>Reference</b>	Occurrence	0 .. 1
		Type	Reference
	Type	Type	xs:string
		Use	required
	<b>Identifier</b>	Type	xs:string
		Use	optional

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
<i>CustomFieldType</i>	Type xs:string Use optional
<b>References</b>	Occurrence 0 .. 1 Type ReferenceGroupList <b>Examples</b> <References> <ReferenceGroup> <Reference Type="ServiceReference">SerRef1</Reference> <Date Type="ReferenceDate" Format="DateTimeSec"> <DateTime>20250803</DateTime> </Date> </ReferenceGroup> </References>
xs:sequence	Occurrence 1 .. 1
<b>ReferenceGroup</b>	Occurrence 0 .. unbounded Type ReferenceGroup
xs:sequence	Occurrence 1 .. 1
<b>Reference</b>	Occurrence 0 .. 1 Type Reference
<i>Type</i>	Type xs:string Use required
<i>Identifier</i>	Type xs:string Use optional
<i>CustomFieldType</i>	Type xs:string Use optional
<b>Date</b>	Occurrence 0 .. 1 Type Date
<i>Type</i>	Type xs:string Use required
<i>Format</i>	Type xs:string Use required
xs:sequence	Occurrence 1 .. 1
<b>DateTime</b>	Occurrence 0 .. 1 Type xs:string
<b>TemperatureControl</b>	Occurrence 0 .. 1 Type TemperatureControl <b>General Notes</b> CONTAINER TEMPERATURE <b>Examples</b> <TemperatureControl Type="Container" Uom="CEL"> <Fixed>10</Fixed> <HumidityPercentage>25</HumidityPercentage> </TemperatureControl>
<i>Type</i>	Type xs:string Use required <b>General Notes</b> TEMPERATURE CONTROL TYPE <b>Applicable Codes</b> <b>Container</b>
<i>Uom</i>	Type xs:string <b>General Notes</b> TEMPERATURE UNIT OF MEASURE <b>Applicable Codes</b> <b>CEL</b> Celsius <b>FAH</b> Fahrenheit
xs:sequence	Occurrence 1 .. 1
<b>Fixed</b>	Occurrence 0 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>General Notes</b> TEMPERATURE
HumidityPercentage	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> HUMIDITY PERCENTAGE
RangeDetails	<b>Occurrence</b> 0 .. 1 <b>Type</b> RangeDetails <b>General Notes</b> RANGE DETAILS  <b>Examples</b> <RangeDetails Type="Container" Uom="CEL"> <Minimum>-5</Minimum> <Maximum>5</Maximum> </RangeDetails>
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> RANGE DETAILS TYPE  <b>Applicable Codes</b> <b>Container</b>
Uom	<b>Type</b> xs:string <b>General Notes</b> TEMPERATURE UNIT OF MEASURE
xs:sequence	<b>Occurrence</b> 1 .. 1
Minimum	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
Maximum	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
Parties	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartiesList <b>General Notes</b> EQUIPMENT PARTY INFORMATION
xs:sequence	<b>Occurrence</b> 1 .. 1
Party	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Party
xs:sequence	<b>Occurrence</b> 1 .. 1
PartyDetails	<b>Occurrence</b> 0 .. 1 <b>Type</b> PartyDetails <b>General Notes</b> PARTY DETAILS  <b>Examples</b> <PartyDetails Role="VGM"> <Id>VGMID</Id> <Assignor>DSV</Assignor> <PartyName>VGM Name</PartyName> <AddressLine1>VGM Addr Line 1</AddressLine1> <AddressLine2>VGM Addr Line 2</AddressLine2> <AddressLine3>VGM Addr Line 3</AddressLine3> <CityName>VGM City</CityName> <State>VGM State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails>
Role	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY ROLE
xs:sequence	<b>Occurrence</b> 1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute		Annotation
	<b>Id</b>	Occurrence 0 .. 1 Type xs:string
	<b>Assignor</b>	Occurrence 0 .. 1 Type xs:string
	<b>PartyName</b>	Occurrence 0 .. 1 Type xs:string
	<b>AddressLine1</b>	Occurrence 0 .. 1 Type xs:string
	<b>AddressLine2</b>	Occurrence 0 .. 1 Type xs:string
	<b>AddressLine3</b>	Occurrence 0 .. 1 Type xs:string
	<b>CityName</b>	Occurrence 0 .. 1 Type xs:string
	<b>State</b>	Occurrence 0 .. 1 Type xs:string
	<b>PostCode</b>	Occurrence 0 .. 1 Type xs:string
	<b>CountryCode</b>	Occurrence 0 .. 1 Type xs:string
	<b>Locations</b>	Occurrence 0 .. 1 Type LocationGroupList <b>General Notes</b> PARTY LOCATION  <b>Examples</b> <Locations> <LocationGroup> <Location Type="VerifiedBy"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </LocationGroup> </Locations>
	xs:sequence	Occurrence 1 .. 1
	<b>LocationGroup</b>	Occurrence 0 .. unbounded Type LocationGroup
	xs:sequence	Occurrence 1 .. 1
	<b>Location</b>	Occurrence 0 .. 1 Type Location
	<i>Type</i>	Type xs:string Use required <b>General Notes</b> PARTY LOCATION TYPE  <b>Applicable Codes</b> <b>PhysicalLocation</b> <b>VerifiedBy</b>
	xs:sequence	Occurrence 1 .. 1
	<b>LocationIdentification</b>	Occurrence 1 .. unbounded Type LocationIdentification
	<i>Type</i>	Type xs:string <b>General Notes</b> PARTY LOCATION IDENTIFIER TYPE  <b>Applicable Codes</b> <b>UN</b> UN location code
	xs:sequence	Occurrence 1 .. 1
	<b>LocationIdentifier</b>	Occurrence 0 .. 1 Type xs:string

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	<b>General Notes</b> PARTY LOCATION IDENTIFIER
LocationName	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY LOCATION NAME
Contact	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Contact <b>General Notes</b> PARTY CONTACT DETAILS  <b>Examples</b> <Contact Type="VerifiedBy"> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> PARTY CONTACT TYPE
xs:sequence	<b>Occurrence</b> 1 .. 1
ContactId	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT ID
Name	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT NAME
Phone	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT PHONE NUMBER
Mobile	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT MOBILE NUMBER
Fax	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT FAX NUMBER
Email	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CONTACT E-MAIL ADDRESS
References	<b>Occurrence</b> 0 .. 1 <b>Type</b> ReferenceGroupList  <b>Examples</b> <References> <ReferenceGroup> <Reference Type="VAT">VatNo</Reference> </ReferenceGroup> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
ReferenceGroup	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
Reference	<b>Occurrence</b> 0 .. 1 <b>Type</b> Reference

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required
	<b>Applicable Codes</b>
	<b>VAT</b> VAT Number
<b>Flags</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> FlagList  <b>Examples</b> <Flags> <Flag Type="IsSealOk">OK</Flag> </Flags>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Flag</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> Flag
<i>Type</i>	<b>Type</b> xs:string <b>Applicable Codes</b> <b>IsDamaged</b> <b>IsSealOk</b> <b>IsShipperOwned</b>

Bold = Element, *Italic* = Attribute, Grey = Group