



Message Implementation Guideline

## **DSV\_StatusMessage**

Model: DSV\_STD\_XML\_STATUSMESSAGE\_V1\_OUT  
Version: 1.1  
Variant:  
Issue date: 2019-10-23  
Author: DSV Panalpina A/S, EDI

3 Structure .....	2
4 Guideline .....	6



**Structure**

Occurrence	Element/Attribute
	<b>DSV_StatusMessage</b>
1 .. 1	xs:sequence
<b>1 .. 1</b>	<b>Header</b>
1 .. 1	xs:sequence
1 .. 1	<b>MessageId</b>
1 .. 1	<b>SenderId</b>
1 .. 1	<b>ReceiverId</b>
<b>1 .. 1</b>	<b>DocumentDate</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
1 .. 1	<b>DocumentCode</b>
1 .. 1	<b>Function</b>
1 .. 1	<b>Version</b>
<b>1 .. 1</b>	<b>ShipmentStatus</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>Shipments</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Shipment</b>
1 .. 1	xs:sequence
1 .. 1	<b>ShipmentId</b>
<b>0 .. 1</b>	<b>ControlTotals</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ControlTotal</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Quantity</b>
<b>0 .. unbounded</b>	<b>StatusDetails</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Status</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>StatusEventCode</b>
0 .. 5	<b>StatusReasonCode</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>FreeTextData</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>FreeText</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
0 .. 1	<b>TextLine2</b>
0 .. 1	<b>TextLine3</b>
0 .. 1	<b>TextLine4</b>
0 .. 1	<b>TextLine5</b>
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>PartyDetails</b>
required	<i>Role</i>
1 .. 1	xs:sequence
0 .. 1	<b>Id</b>
0 .. 1	<b>Assignor</b>
0 .. 1	<b>PartyName</b>
0 .. 1	<b>AddressLine1</b>
0 .. 1	<b>AddressLine2</b>
0 .. 1	<b>AddressLine3</b>
0 .. 1	<b>CityName</b>
0 .. 1	<b>State</b>
0 .. 1	<b>PostCode</b>
0 .. 1	<b>CountryCode</b>
<b>0 .. unbounded</b>	<b>Contact</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>Name</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. 1</b>	<b>TransportStages</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>TransportStage</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Stage</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>ModeOfTransport</b>
0 .. 1	<b>TransportId</b>
0 .. 1	<b>CarrierId</b>
0 .. 1	<b>CarrierName</b>
0 .. 1	<b>TransportType</b>
0 .. 1	<b>TransportMeansName</b>
0 .. 1	<b>TransportMeansNationality</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
<b>0 .. 1</b>	<b>GoodsItems</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>GoodsItem</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Item</b>
1 .. 1	xs:sequence
0 .. 1	<b>ItemNumber</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
<b>0 .. 1</b>	<b>Measurements</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Measurement</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Measure</b>
<b>0 .. 1</b>	<b>Dimensions</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Dimension</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
required	<ul style="list-style-type: none"> <li><i>Type</i></li> <li><i>Uom</i></li> <li>xs:sequence                             <ul style="list-style-type: none"> <li><b>Length</b></li> <li><b>Width</b></li> <li><b>Height</b></li> </ul> </li> </ul>
1 .. 1	
0 .. 1	
0 .. 1	
0 .. 1	
<b>0 .. 1</b>	<b>Packagelds</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Packageld</b>
1 .. 1	xs:sequence
1 .. 1	<b>InstructionCode</b>
<b>0 .. unbounded</b>	<b>GoodsIdentities</b>
required	<ul style="list-style-type: none"> <li><i>Type</i></li> <li>xs:sequence                             <ul style="list-style-type: none"> <li><b>GoodsIdentifier</b></li> </ul> </li> </ul>
1 .. 1	
1 .. unbounded	

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



**Guideline**

Element/Attribute	Annotation
<b>DSV_StatusMessage</b>	Type <i>dsv_statusmessage:DSV_StatusMessage</i>
xs:sequence	Occurrence 1 .. 1
<b>Header</b>	Occurrence 1 .. 1 Type <i>shardelements:Header</i> General Notes MESSAGE HEADER
	<b>Examples</b>
	<pre> &lt;Header&gt;   &lt;MessageId&gt;12485236&lt;/MessageId&gt;   &lt;SenderId&gt;SenderIdentification&lt;/SenderId&gt;   &lt;ReceiverId&gt;ReceiverIdentification&lt;/ReceiverId&gt;   &lt;DocumentDate Type="DocumentDate" Format="DateTime"&gt;     &lt;DateTime&gt;201902120000&lt;/DateTime&gt;   &lt;/DocumentDate&gt;   &lt;DocumentCode&gt;ConsignmentStatusReport&lt;/DocumentCode&gt;   &lt;Function&gt;New&lt;/Function&gt;   &lt;Version&gt;1.0&lt;/Version&gt; &lt;/Header&gt;           </pre>
xs:sequence	Occurrence 1 .. 1
<b>MessageId</b>	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes MESSAGE IDENTIFICATION
<b>SenderId</b>	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes SENDER IDENTIFICATION Mutually agreed
<b>ReceiverId</b>	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes RECEIVER IDENTIFICATION Mutually agreed
<b>DocumentDate</b>	Occurrence 1 .. 1 Type <i>shardelements:Date</i>
Type	Type <i>xs:string</i> Use required General Notes DOCUMENT / MESSAGE DATE TYPE
	<b>Applicable Codes</b>
Format	<b>DocumentDate</b> Document Date Type <i>xs:string</i> Use required General Notes DOCUMENT / MESSAGE DATE FORMAT
	<b>Applicable Codes</b>
DateTime	<b>DateTime</b> CCYYMMDDHHMM
xs:sequence	Occurrence 1 .. 1
<b>DateTime</b>	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes DOCUMENT / MESSAGE DATE/TIME
<b>DocumentCode</b>	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes DOCUMENT TYPE
	<b>Applicable Codes</b>
	<b>ConsignmentStatusReport</b> Consignment Status Report

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation																										
<b>Function</b>	<p>Occurrence 1 .. 1                      Type <i>xs:string</i>                      General Notes DOCUMENT/MESSAGE FUNCTION</p> <p><b>Applicable Codes</b></p> <p><b>New</b> New</p>																										
<b>Version</b>	<p>Occurrence 1 .. 1                      Type <i>xs:string</i>                      General Notes MESSAGE VERSION</p> <p><b>Applicable Codes</b></p> <p><b>1.0</b> Version 1.0</p>																										
<b>ShipmentStatus</b>	<p>Occurrence 1 .. 1                      Type <i>shipmentstatus:ShipmentStatus</i>                      General Notes SHIPMENT STATUS</p>																										
<i>xs:sequence</i> <b>Dates</b>	<p>Occurrence 1 .. 1                      Type <i>shipmentstatus:DateList</i>                      General Notes SHIPMENT STATUS DATES</p> <p><b>Examples</b></p> <pre>&lt;Dates&gt;   &lt;Date Type="IssueDate" Format="DateTime"&gt;     &lt;DateTime&gt;201902130900&lt;/DateTime&gt;   &lt;/Date&gt;   &lt;Date Type="ActualCollection" Format="Date"&gt;     &lt;DateTime&gt;20190220&lt;/DateTime&gt;   &lt;/Date&gt;   &lt;Date Type="EstimatedDelivery" Format="DateTimeInterval"&gt;     &lt;DateTime&gt;201903021200-201903021700&lt;/DateTime&gt;   &lt;/Date&gt; &lt;/Dates&gt;</pre>																										
<i>xs:sequence</i> <b>Date</b>	<p>Occurrence 1 .. 1                      Occurrence 0 .. unbounded                      Type <i>sharedelements:Date</i></p>																										
<b>Type</b>	<p>Type <i>xs:string</i>                      Use required                      General Notes SHIPMENT STATUS DATE TYPE</p> <p><b>Applicable Codes</b></p> <table border="0"> <tr><td><b>ActualArrival</b></td><td>Actual Arrival (ATA)</td></tr> <tr><td><b>ActualCollection</b></td><td>Actual Collection</td></tr> <tr><td><b>ActualDelivery</b></td><td>Actual Delivery</td></tr> <tr><td><b>ActualDeparture</b></td><td>Actual Departure (ATD)</td></tr> <tr><td><b>Collection</b></td><td>Collection</td></tr> <tr><td><b>DeliveryRequested</b></td><td>Delivery Requested</td></tr> <tr><td><b>EstimatedCollection</b></td><td>Estimated Collection</td></tr> <tr><td><b>EstimatedDelivery</b></td><td>Estimated Delivery</td></tr> <tr><td><b>IssueDate</b></td><td>Document Issued Date</td></tr> <tr><td><b>ScheduledArrival</b></td><td>Scheduled Arrival</td></tr> <tr><td><b>ScheduledDeparture</b></td><td>Scheduled Departure</td></tr> <tr><td><b>ScheduledShipmentArrival</b></td><td>Scheduled Shipment Arrival</td></tr> <tr><td><b>ScheduledShipmentDeparture</b></td><td>Scheduled Shipment Departure</td></tr> </table>	<b>ActualArrival</b>	Actual Arrival (ATA)	<b>ActualCollection</b>	Actual Collection	<b>ActualDelivery</b>	Actual Delivery	<b>ActualDeparture</b>	Actual Departure (ATD)	<b>Collection</b>	Collection	<b>DeliveryRequested</b>	Delivery Requested	<b>EstimatedCollection</b>	Estimated Collection	<b>EstimatedDelivery</b>	Estimated Delivery	<b>IssueDate</b>	Document Issued Date	<b>ScheduledArrival</b>	Scheduled Arrival	<b>ScheduledDeparture</b>	Scheduled Departure	<b>ScheduledShipmentArrival</b>	Scheduled Shipment Arrival	<b>ScheduledShipmentDeparture</b>	Scheduled Shipment Departure
<b>ActualArrival</b>	Actual Arrival (ATA)																										
<b>ActualCollection</b>	Actual Collection																										
<b>ActualDelivery</b>	Actual Delivery																										
<b>ActualDeparture</b>	Actual Departure (ATD)																										
<b>Collection</b>	Collection																										
<b>DeliveryRequested</b>	Delivery Requested																										
<b>EstimatedCollection</b>	Estimated Collection																										
<b>EstimatedDelivery</b>	Estimated Delivery																										
<b>IssueDate</b>	Document Issued Date																										
<b>ScheduledArrival</b>	Scheduled Arrival																										
<b>ScheduledDeparture</b>	Scheduled Departure																										
<b>ScheduledShipmentArrival</b>	Scheduled Shipment Arrival																										
<b>ScheduledShipmentDeparture</b>	Scheduled Shipment Departure																										
<b>Format</b>	<p>Type <i>xs:string</i>                      Use required                      General Notes SHIPMENT STATUS DATE FORMAT</p> <p><b>Applicable Codes</b></p> <p><b>Date</b> CCYYMMDD</p>																										

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b>
	<b>DateTime</b> CCYYMMDDHHMM
	<b>DateTimeInterval</b> CCYYMMDDHHMM-CCYYMMDDHHMM
	<b>DateTimeSec</b> CCYYMMDDHHMMSS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> SHIPMENT STATUS DATE/TIME
<b>Shipments</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>shipmentstatus:ShipmentList</i>
	<b>General Notes</b> SHIPMENTS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Shipment</b>	<b>Occurrence</b> 0 .. <i>unbounded</i>
	<b>Type</b> <i>shipmentstatus:Shipment</i>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ShipmentId</b>	<b>Occurrence</b> 1 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> SHIPMENT IDENTIFICATION
	<b>Examples</b>
	<code>&lt;ShipmentId&gt;SampleShipment&lt;/ShipmentId&gt;</code>
<b>ControlTotals</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>shipmentstatus:ControlTotalList</i>
	<b>General Notes</b> SHIPMENT CONTROL TOTALS
	<b>Examples</b>
	<code>&lt;ControlTotals&gt;</code>
	<code>&lt;ControlTotal Type="NumberOfPackages"&gt;</code>
	<code>&lt;Quantity&gt;20&lt;/Quantity&gt;</code>
	<code>&lt;/ControlTotal&gt;</code>
	<code>&lt;ControlTotal Type="GrossWeight" Uom="KGM"&gt;</code>
	<code>&lt;Quantity&gt;101.01&lt;/Quantity&gt;</code>
	<code>&lt;/ControlTotal&gt;</code>
	<code>&lt;ControlTotal Type="Volume" Uom="MTQ"&gt;</code>
	<code>&lt;Quantity&gt;2&lt;/Quantity&gt;</code>
	<code>&lt;/ControlTotal&gt;</code>
	<code>&lt;ControlTotal Type="LoadingMeters" Uom="MTR"&gt;</code>
	<code>&lt;Quantity&gt;12&lt;/Quantity&gt;</code>
	<code>&lt;/ControlTotal&gt;</code>
	<code>&lt;ControlTotal Type="PalletSpaces" Uom="PLL"&gt;</code>
	<code>&lt;Quantity&gt;10&lt;/Quantity&gt;</code>
	<code>&lt;/ControlTotal&gt;</code>
	<code>&lt;/ControlTotals&gt;</code>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ControlTotal</b>	<b>Occurrence</b> 0 .. <i>unbounded</i>
	<b>Type</b> <i>shardelements:ControlTotal</i>
<b>Type</b>	<b>Type</b> <i>xs:string</i>
	<b>Use</b> required
	<b>General Notes</b> SHIPMENT CONTROL TOTAL TYPE
	<b>Applicable Codes</b>
	<b>GrossWeight</b> Gross Weight
	<b>LoadingMeters</b> Loading Meters
	<b>NumberOfPackages</b> Number Of Packages
	<b>PalletSpaces</b> Pallet Spaces
	<b>Volume</b> Volume
<b>Uom</b>	<b>Type</b> <i>xs:string</i>

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
	<b>General Notes</b> SHIPMENT CONTROL TOTAL UNIT OF MEASURE
	<b>Applicable Codes</b>
	<b>CTN</b> Cartons
	<b>KGM</b> Kilograms
	<b>MTQ</b> Cubic metres
	<b>MTR</b> Linear Metres
	<b>PKG</b> Packages
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Quantity</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
	<b>General Notes</b> SHIPMENT QUANTITY
<b>StatusDetails</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shipmentstatus:StatusDetailslist
	<b>General Notes</b> STATUS DETAILS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Status</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> sharedelements:Status
	<b>General Notes</b> SHIPMENT STATUS
	<b>Examples</b>
	<Status Type="Consignment" > <StatusEventCode>Delivered</StatusEventCode> <StatusReason>Z</StatusReason> </Status>
<b>Type</b>	<b>Type</b> xs:string <b>Use</b> required
	<b>General Notes</b> SHIPMENT STATUS TYPE
	<b>Applicable Codes</b>
	<b>Consignment</b> Consignment Level
	<b>GoodsItem</b> Goods Item Level
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>StatusEventCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string
	<b>General Notes</b> STATUS EVENT CODE
	<b>Applicable Codes</b>
	<b>Arrived</b> Arrived
	<b>Collected</b> Collected
	<b>Delivered</b> Delivered
	<b>Departed/Loaded</b> Departed / Loaded
	<b>NotCollected</b> Not Collected
	<b>NotDelivered</b> Not Delivered
<b>StatusReasonCode</b>	<b>Occurrence</b> 0 .. 5 <b>Type</b> xs:string
	<b>General Notes</b> STATUS REASON CODE
	<b>Applicable Codes</b>
	<b>AppointmentScheduled</b> Appointment scheduled
	<b>AttemptUnsuccessful</b> Attempt unsuccessful
	<b>ChangedSchedule</b> Changed schedule
	<b>Damaged</b> Damaged
	<b>DamagedPackaging</b> Damaged Packaging
	<b>DeliveredWithoutSignature</b> Delivered without signature
	<b>Discrepancy</b> Discrepancy
	<b>GoodsNotBarcoded</b> Goods not barcoded
	<b>HandledByDriverWithoutScanner</b> Handled by driver without scanner
	<b>IncorrectAddress</b> Incorrect address

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation																										
L	<p><b>Applicable Codes</b></p> <table border="0"> <tr><td><b>MechanicalBreakdown</b></td><td>Mechanical breakdown</td></tr> <tr><td><b>MissingDocuments</b></td><td>Missing and/or incorrect documents</td></tr> <tr><td><b>NewDeliveryArrangements</b></td><td>New delivery arrangements</td></tr> <tr><td><b>Notloaded</b></td><td>Not loaded</td></tr> <tr><td><b>Opened</b></td><td>Opened</td></tr> <tr><td><b>PackageNotReady</b></td><td>Package not ready</td></tr> <tr><td><b>PhotoTaken</b></td><td>Photo taken</td></tr> <tr><td><b>RefusedWithoutreasonGiven</b></td><td>Refused without reason given</td></tr> <tr><td><b>Torn</b></td><td>Torn</td></tr> <tr><td><b>UnacceptableCondition</b></td><td>Unacceptable condition</td></tr> <tr><td><b>Unknown</b></td><td>Unknown</td></tr> <tr><td><b>WeatherConditions</b></td><td>Weather conditions</td></tr> <tr><td><b>Wet</b></td><td>Wet</td></tr> </table>	<b>MechanicalBreakdown</b>	Mechanical breakdown	<b>MissingDocuments</b>	Missing and/or incorrect documents	<b>NewDeliveryArrangements</b>	New delivery arrangements	<b>Notloaded</b>	Not loaded	<b>Opened</b>	Opened	<b>PackageNotReady</b>	Package not ready	<b>PhotoTaken</b>	Photo taken	<b>RefusedWithoutreasonGiven</b>	Refused without reason given	<b>Torn</b>	Torn	<b>UnacceptableCondition</b>	Unacceptable condition	<b>Unknown</b>	Unknown	<b>WeatherConditions</b>	Weather conditions	<b>Wet</b>	Wet
<b>MechanicalBreakdown</b>	Mechanical breakdown																										
<b>MissingDocuments</b>	Missing and/or incorrect documents																										
<b>NewDeliveryArrangements</b>	New delivery arrangements																										
<b>Notloaded</b>	Not loaded																										
<b>Opened</b>	Opened																										
<b>PackageNotReady</b>	Package not ready																										
<b>PhotoTaken</b>	Photo taken																										
<b>RefusedWithoutreasonGiven</b>	Refused without reason given																										
<b>Torn</b>	Torn																										
<b>UnacceptableCondition</b>	Unacceptable condition																										
<b>Unknown</b>	Unknown																										
<b>WeatherConditions</b>	Weather conditions																										
<b>Wet</b>	Wet																										
References	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>shipmentstatus:ReferenceGroupList</i>  <b>General Notes</b> STATUS REFERENCES</p> <p><b>Examples</b></p> <pre>&lt;References&gt;   &lt;ReferenceGroup&gt;     &lt;Reference Type="HouseBill" &gt;ABC0013200&lt;/Reference&gt;   &lt;/ReferenceGroup&gt;   &lt;ReferenceGroup&gt;     &lt;Reference Type="OrderReference" &gt;ABCREF123&lt;/Reference&gt;   &lt;/ReferenceGroup&gt;   &lt;ReferenceGroup&gt;     &lt;Reference Type="ConsignmentId" &gt;DEFG00132&lt;/Reference&gt;   &lt;/ReferenceGroup&gt; &lt;/References&gt;</pre>																										
xs:sequence	<b>Occurrence</b> 1 .. 1																										
ReferenceGroup	<p><b>Occurrence</b> 0 .. <i>unbounded</i>  <b>Type</b> <i>shipmentstatus:ReferenceGroup</i></p>																										
xs:sequence	<b>Occurrence</b> 1 .. 1																										
Reference	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>sharedelements:Reference</i>  <b>General Notes</b> STATUS REFERENCE</p>																										
Type	<p><b>Type</b> <i>xs:string</i>  <b>Use</b> required  <b>General Notes</b> STATUS REFERENCE TYPE</p> <p><i>Predefined Types listed, additional reference types to be agreed</i></p>																										
L	<p><b>Applicable Codes</b></p> <table border="0"> <tr><td><b>ConsigneeOrderNumber</b></td><td>Consignee's order number</td></tr> <tr><td><b>ConsigneeReference</b></td><td>Consignee Reference</td></tr> <tr><td><b>ConsignmentId</b></td><td>Consignment id, carrier assigned</td></tr> <tr><td><b>CustomField</b></td><td>Custom Field</td></tr> <tr><td><b>CustomerAccountCode</b></td><td>Customer Account Code</td></tr> <tr><td><b>CustomerReferenceNumber</b></td><td>Customer reference number</td></tr> <tr><td><b>DeliveryAgreement</b></td><td>Delivery Agreement</td></tr> <tr><td><b>DocumentReference</b></td><td>Document Reference</td></tr> <tr><td><b>EventCode</b></td><td>Event Code</td></tr> <tr><td><b>ExternalReference</b></td><td>External reference customer reference number</td></tr> <tr><td><b>GINCNumber</b></td><td>Waybill number, GINC</td></tr> <tr><td><b>HouseBill</b></td><td>House bill of lading number</td></tr> <tr><td><b>IDSReference</b></td><td>IDS reference</td></tr> </table>	<b>ConsigneeOrderNumber</b>	Consignee's order number	<b>ConsigneeReference</b>	Consignee Reference	<b>ConsignmentId</b>	Consignment id, carrier assigned	<b>CustomField</b>	Custom Field	<b>CustomerAccountCode</b>	Customer Account Code	<b>CustomerReferenceNumber</b>	Customer reference number	<b>DeliveryAgreement</b>	Delivery Agreement	<b>DocumentReference</b>	Document Reference	<b>EventCode</b>	Event Code	<b>ExternalReference</b>	External reference customer reference number	<b>GINCNumber</b>	Waybill number, GINC	<b>HouseBill</b>	House bill of lading number	<b>IDSReference</b>	IDS reference
<b>ConsigneeOrderNumber</b>	Consignee's order number																										
<b>ConsigneeReference</b>	Consignee Reference																										
<b>ConsignmentId</b>	Consignment id, carrier assigned																										
<b>CustomField</b>	Custom Field																										
<b>CustomerAccountCode</b>	Customer Account Code																										
<b>CustomerReferenceNumber</b>	Customer reference number																										
<b>DeliveryAgreement</b>	Delivery Agreement																										
<b>DocumentReference</b>	Document Reference																										
<b>EventCode</b>	Event Code																										
<b>ExternalReference</b>	External reference customer reference number																										
<b>GINCNumber</b>	Waybill number, GINC																										
<b>HouseBill</b>	House bill of lading number																										
<b>IDSReference</b>	IDS reference																										

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
L	<p><b>Applicable Codes</b></p> <p><b>MasterBill</b> Master bill of lading number  <b>OnSightAuthorizationCode</b> On sight authorization code  <b>OrderReference</b> Order Reference  <b>PackageNumber</b> Package Number  <b>ProofOfDeliveryNumber</b> Proof of delivery reference number  <b>QualityCode</b> Quality Code  <b>QualitySource</b> Quality Source  <b>RoadWaybill</b> Road Waybill number, SIS  <b>ShipmentReference</b> Shipment reference number  <b>ShipperReference</b> Shipper Reference  <b>TrafficFrom</b> Traffic From  <b>TransportInstructionNumber</b> Transport instruction number  <b>VehicleId</b> Vehicle identification number ( VIN)  <b>VesselCountryOfRegistration</b> Vessel Country of Registration  <b>VesselId</b> Vessel identifier</p>
Dates	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>shipmentstatus:DateList</i>  <b>General Notes</b> STATUS DATES</p> <p><b>Examples</b></p> <pre>&lt;Dates&gt;   &lt;Date Type="StatusDate" Format="DateTime"&gt;     &lt;DateTime&gt;201902130900&lt;/DateTime&gt;   &lt;/Date&gt; &lt;/Dates&gt;</pre>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
Date	<p><b>Occurrence</b> 0 .. unbounded  <b>Type</b> <i>shardelements:Date</i></p>
Type	<p><b>Type</b> <i>xs:string</i>  <b>Use</b> required  <b>General Notes</b> STATUS DATE TYPE</p>
Format	<p><b>Applicable Codes</b></p> <p><b>StatusDate</b> Status change date/time</p> <p><b>Type</b> <i>xs:string</i>  <b>Use</b> required  <b>General Notes</b> STATUS DATE FORMAT</p>
xs:sequence	<p><b>Applicable Codes</b></p> <p><b>Date</b> CCYYMMDD  <b>DateTime</b> CCYYMMDDHHMM  <b>DateTimeInterval</b> CCYYMMDDHHMM-CCYYMMDDHHMM  <b>DateTimeSec</b> CCYYMMDDHHMMSS</p>
DateTime	<p><b>Occurrence</b> 1 .. 1  <b>Occurrence</b> 0 .. 1  <b>Type</b> <i>xs:string</i>  <b>General Notes</b> STATUS DATE / TIME</p>
FreeTextData	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>shipmentstatus:FreeTextList</i>  <b>General Notes</b> STATUS FREE TEXT</p> <p><b>Examples</b></p> <pre>&lt;FreeTextData&gt;   &lt;FreeText Type="StatusRemarks" &gt;     &lt;TextLine1&gt;Statusremarks 1&lt;/TextLine1&gt;   &lt;/FreeText&gt; &lt;/FreeTextData&gt;</pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<b>xs:sequence</b>	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. <i>unbounded</i> <b>Type</b> <i>shardelements:FreeText</i>
<b>Type</b>	<b>Type</b> <i>xs:string</i> <b>Use</b> required <b>General Notes</b> STATUS FREE TEXT TYPE
<b>Applicable Codes</b>	
	<b>StatusRemarks</b> Status Remarks
<b>xs:sequence</b>	<b>Occurrence</b> 1 .. 1
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> STATUS FREE TEXT LINE 1
<b>TextLine2</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> STATUS FREE TEXT LINE 2
<b>TextLine3</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> STATUS FREE TEXT LINE 3
<b>TextLine4</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> STATUS FREE TEXT LINE 4
<b>TextLine5</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> STATUS FREE TEXT LINE 5
<b>Parties</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>shipmentstatus:PartiesList</i> <b>General Notes</b> SHIPMENT PARTY INFORMATION
<b>xs:sequence</b>	<b>Occurrence</b> 1 .. 1
<b>Party</b>	<b>Occurrence</b> 0 .. <i>unbounded</i> <b>Type</b> <i>shipmentstatus:PartyList</i>
<b>xs:sequence</b>	<b>Occurrence</b> 1 .. 1
<b>PartyDetails</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> <i>shardelements:PartyDetails</i> <b>General Notes</b> PARTY DETAILS
<b>Examples</b>	
	<pre> &lt;PartyDetails Role="Consignor"&gt;   &lt;Id&gt;ConsignorID&lt;/Id&gt;   &lt;Assignor&gt;Consignor&lt;/Assignor&gt;   &lt;PartyName&gt;Consignor Name&lt;/PartyName&gt;   &lt;AddressLine1&gt;Consignor Addr Line 1&lt;/AddressLine1&gt;   &lt;AddressLine2&gt;Consignor Addr Line 2&lt;/AddressLine2&gt;   &lt;AddressLine3&gt;Consignor Addr Line 3&lt;/AddressLine3&gt;   &lt;CityName&gt;Consignor City&lt;/CityName&gt;   &lt;State&gt;Consignor State&lt;/State&gt;   &lt;PostCode&gt;PostCd&lt;/PostCode&gt;   &lt;CountryCode&gt;DK&lt;/CountryCode&gt; &lt;/PartyDetails&gt;           </pre>
<b>Role</b>	<b>Type</b> <i>xs:string</i> <b>Use</b> required <b>General Notes</b> PARTY ROLE
<b>Applicable Codes</b>	
	<b>AcceptingParty</b> Accepting Party

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b>
	Consignee Consignor Delivery Despatch
	Consignee Consignor Delivery Despatch
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER
Assignor	Occurrence 0 .. 1 Type xs:string General Notes PARTY IDENTIFIER ASSIGNOR
	<b>Applicable Codes</b>
	Consignor DSV GS1
	Consignor assigned DSV Assigned GS1 Assigned
PartyName	Occurrence 0 .. 1 Type xs:string General Notes PARTY NAME
AddressLine1	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1 Type xs:string General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1 Type xs:string General Notes PARTY CITY NAME
State	Occurrence 0 .. 1 Type xs:string General Notes PARTY STATE OR PROVINCE
PostCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1 Type xs:string General Notes PARTY COUNTRY ISO CODE
Contact	Occurrence 0 .. unbounded Type sharedelements:Contact General Notes PARTY CONTACT DETAILS
	<b>Examples</b>
	<Contact Type="InformationContact"> <Name>Contact name</Name> </Contact>
Type	Type xs:string Use required General Notes PARTY CONTACT TYPE

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b>
	<b>GoodsReceivingContact</b> Goods Receiving Contact
	<b>InformationContact</b> Information Contact
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Name</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> PARTY CONTACT NAME
<b>Locations</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>shipmentstatus:LocationList</i>
	<b>General Notes</b> STATUS LOCATIONS
	<b>Examples</b>
	<pre> &lt;Locations&gt;   &lt;Location Type="StatusLocation"&gt;     &lt;LocationIdentification Type="UN"&gt;       &lt;LocationIdentifier&gt;DKHOR&lt;/LocationIdentifier&gt;       &lt;LocationName&gt;Horsens&lt;/LocationName&gt;     &lt;/LocationIdentification&gt;   &lt;/Location&gt; &lt;/Locations&gt;                     </pre>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Location</b>	<b>Occurrence</b> 0 .. unbounded
	<b>Type</b> <i>sharedelements:Location</i>
<b>Type</b>	<b>Type</b> <i>xs:string</i>
	<b>Use</b> required
	<b>General Notes</b> STATUS LOCATION TYPE
	<b>Applicable Codes</b>
	<b>StatusLocation</b> Status Location
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentification</b>	<b>Occurrence</b> 1 .. unbounded
	<b>Type</b> <i>sharedelements:LocationIdentification</i>
<b>Type</b>	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> STATUS LOCATION IDENTIFIER TYPE
	<b>Applicable Codes</b>
	<b>UN</b> UN Location Code
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> STATUS LOCATION IDENTIFIER
<b>LocationName</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> STATUS LOCATION NAME
<b>TransportStages</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>shipmentstatus:TransportStageList</i>
	<b>General Notes</b> TRANSPORTATION STAGES Road: Not used
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportStage</b>	<b>Occurrence</b> 0 .. unbounded
	<b>Type</b> <i>shipmentstatus:TransportStage</i>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Stage</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>sharedelements:Stage</i>
	<b>General Notes</b> TRANSPORTATION STAGE

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>Examples</b></p> <pre>&lt;Stage Type="MainCarriage"&gt;   &lt;ModeOfTransport&gt;Sea&lt;/ModeOfTransport&gt;   &lt;TransportId&gt;0123W&lt;/TransportId&gt;   &lt;CarrierId&gt;61616161&lt;/CarrierId&gt;   &lt;CarrierName&gt;Carrier name&lt;/CarrierName&gt;   &lt;TransportType&gt;Main&lt;/TransportType&gt;   &lt;TransportMeansName&gt;Vessel name&lt;/TransportMeansName&gt;   &lt;TransportMeansNationality&gt;PA&lt;/TransportMeansNationality&gt; &lt;/Stage&gt;</pre>
Type	<p>Type <i>xs:string</i>            Use required  <b>General Notes</b> TRANSPORTATION STAGE TYPE</p> <p><b>Applicable Codes</b></p> <p><b>MainCarriage</b> Main Carriage</p>
xs:sequence	<p>Occurrence 1 .. 1</p>
ModeOfTransport	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> MODE OF TRANSPORTATION</p> <p><b>Applicable Codes</b></p> <p><b>Air</b> Air transportation  <b>Sea</b> Sea transportation</p>
TransportId	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> TRANSPORT IDENTIFICATION  <i>Air: Flight number</i>  <i>Sea: Voyage number</i>  <i>Road: Not used</i></p>
CarrierId	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> CARRIER IDENTIFICATION  <i>Air &amp; Sea: DSV carrier identifier</i>  <i>Road: Not used</i></p>
CarrierName	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> CARRIER NAME  <i>Road: Not used</i></p>
TransportType	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> TRANSPORT TYPE  <i>Road: Not used</i></p>
TransportMeansName	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> TRANSPORT MEANS NAME  <i>Sea: Vessel Name</i>  <i>Air &amp; Road: Not used</i></p>
TransportMeansNationality	<p>Occurrence 0 .. 1            Type <i>xs:string</i>  <b>General Notes</b> TRANSPORT MEANS NATIONALITY  <i>Sea: Vessel flag</i>  <i>Air &amp; Road: Not used</i></p>
Locations	<p>Occurrence 0 .. 1            Type <i>shipmentstatus:LocationList</i></p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>General Notes</b> TRANSPORTATION LOCATIONS
	<b>Examples</b> <Locations> <Location Type="PlaceOfLoading" > <LocationIdentification Type="UN" > <LocationIdentifier>USHOU</LocationIdentifier> </LocationIdentification> </Location> <Location Type="PlaceOfUnloading" > <LocationIdentification Type="UN" > <LocationIdentifier>HKHKG</LocationIdentifier> </LocationIdentification> </Location> </Locations>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Location</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:Location
Type	<b>Type</b> xs:string <b>Use</b> required
	<b>General Notes</b> TRANSPORTATION LOCATION TYPE
	<b>Applicable Codes</b>
	<b>PlaceOfLoading</b> Place of Loading
	<b>PlaceOfUnloading</b> Place of Unloading
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentification</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> sharedelements:LocationIdentification
Type	<b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER TYPE
	<b>Applicable Codes</b>
	<b>UN</b> UN Location Code
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> LOCATION IDENTIFIER
<b>References</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> shipmentstatus:ReferenceGroupList <b>General Notes</b> TRANSPORTATION STAGE REFERENCES
	<b>Examples</b> <References> <ReferenceGroup> <Reference Type="MasterBill">MasterBill</Reference> </ReferenceGroup> </References>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shipmentstatus:ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> sharedelements:Reference <b>General Notes</b> TRANSPORTATION STAGE REFERENCE

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
Type	Type <i>xs:string</i> Use required <b>General Notes</b> REFERENCE TYPE
GoodsItems	<b>Applicable Codes</b> <b>MasterBill</b> Master Bill Occurrence 0 .. 1 Type <i>shipmentstatus:GoodsItemList</i> <b>General Notes</b> SHIPMENT LINE ITEMS
GoodsItem	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type <i>shipmentstatus:GoodsItem</i>
Item	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>sharedelements:Item</i> <b>General Notes</b> GOODS ITEM DETAILS <b>Examples</b> <Item> <ItemNumber>1</ItemNumber> <PackageQty>20</PackageQty> <PackageType>PKG</PackageType> </Item>
ItemNumber	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>xs:string</i> <b>General Notes</b> LINE ITEM NUMBER
Locations	Occurrence 0 .. 1 Type <i>shipmentstatus:LocationList</i> <b>General Notes</b> LINE ITEM GOODS LOCATION <b>Examples</b> <Locations> <Location Type="GoodsItemLocation"> <LocationIdentification Type="UN"> <LocationIdentifier>DKHOR</LocationIdentifier> </LocationIdentification> </Location> </Locations>
Location	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type <i>sharedelements:Location</i>
Type	Type <i>xs:string</i> Use required <b>General Notes</b> LOCATION TYPE <b>Applicable Codes</b> <b>GoodsItemLocation</b> Goods Item Location
LocationIdentification	Occurrence 1 .. 1 Occurrence 1 .. unbounded Type <i>sharedelements:LocationIdentification</i>
LocationIdentifier	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>xs:string</i> <b>General Notes</b> LOCATION IDENTIFIER

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation										
<b>Measurements</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>shipmentstatus:MeasurementsList</i>  <b>General Notes</b> LINE ITEM MEASUREMENTS</p> <p><b>Examples</b></p> <pre>&lt;Measurements&gt;   &lt;Measurement Type="GrossWeight" Uom="KGM"&gt;     &lt;Measure&gt;10.03&lt;/Measure&gt;   &lt;/Measurement&gt;   &lt;Measurement Type="NetWeight" Uom="KGM"&gt;     &lt;Measure&gt;8.03&lt;/Measure&gt;   &lt;/Measurement&gt;   &lt;Measurement Type="Volume" Uom="MTQ"&gt;     &lt;Measure&gt;2.03&lt;/Measure&gt;   &lt;/Measurement&gt;   &lt;Measurement Type="LoadingMeters" Uom="MTR"&gt;     &lt;Measure&gt;2.05&lt;/Measure&gt;   &lt;/Measurement&gt;   &lt;Measurement Type="PalletSpaces" Uom="PLL"&gt;     &lt;Measure&gt;5&lt;/Measure&gt;   &lt;/Measurement&gt; &lt;/Measurements&gt;</pre>										
xs:sequence	<b>Occurrence</b> 1 .. 1										
<b>Measurement</b>	<p><b>Occurrence</b> 0 .. unbounded  <b>Type</b> <i>sharedelements:Measurement</i></p>										
Type	<p><b>Type</b> <i>xs:string</i>  <b>Use</b> required  <b>General Notes</b> MEASUREMENT TYPE</p> <p><b>Applicable Codes</b></p> <table border="0"> <tr> <td><b>GrossWeight</b></td> <td>Line Item Gross Weight</td> </tr> <tr> <td><b>LoadingMeters</b></td> <td>Line Item Loading Meters</td> </tr> <tr> <td><b>NetWeight</b></td> <td>Line Item Net Weight</td> </tr> <tr> <td><b>PalletSpaces</b></td> <td>Line Item Pallet Spaces</td> </tr> <tr> <td><b>Volume</b></td> <td>Line Item Volume</td> </tr> </table>	<b>GrossWeight</b>	Line Item Gross Weight	<b>LoadingMeters</b>	Line Item Loading Meters	<b>NetWeight</b>	Line Item Net Weight	<b>PalletSpaces</b>	Line Item Pallet Spaces	<b>Volume</b>	Line Item Volume
<b>GrossWeight</b>	Line Item Gross Weight										
<b>LoadingMeters</b>	Line Item Loading Meters										
<b>NetWeight</b>	Line Item Net Weight										
<b>PalletSpaces</b>	Line Item Pallet Spaces										
<b>Volume</b>	Line Item Volume										
Uom	<p><b>Type</b> <i>xs:string</i>  <b>General Notes</b> MEASUREMENT UNIT OF MEASURE</p> <p><b>Applicable Codes</b></p> <table border="0"> <tr> <td><b>KGM</b></td> <td>Kilograms</td> </tr> <tr> <td><b>MTQ</b></td> <td>Cubic Metres</td> </tr> <tr> <td><b>MTR</b></td> <td>Linear Metre</td> </tr> <tr> <td><b>PLL</b></td> <td>Pallet Spaces</td> </tr> </table>	<b>KGM</b>	Kilograms	<b>MTQ</b>	Cubic Metres	<b>MTR</b>	Linear Metre	<b>PLL</b>	Pallet Spaces		
<b>KGM</b>	Kilograms										
<b>MTQ</b>	Cubic Metres										
<b>MTR</b>	Linear Metre										
<b>PLL</b>	Pallet Spaces										
xs:sequence	<b>Occurrence</b> 1 .. 1										
<b>Measure</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>xs:string</i>  <b>General Notes</b> MEASUREMENT VALUE</p>										
<b>Dimensions</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> <i>shipmentstatus:DimensionsList</i>  <b>General Notes</b> LINE ITEM DIMENSIONS</p> <p><b>Examples</b></p> <pre>&lt;Dimensions&gt;   &lt;Dimension Type="Gross" Uom="MTR"&gt;     &lt;Length&gt;0.6&lt;/Length&gt;     &lt;Width&gt;0.2&lt;/Width&gt;     &lt;Height&gt;0.8&lt;/Height&gt;   &lt;/Dimension&gt;</pre>										

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Examples</b> </Dimensions>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Dimension</b>	<b>Occurrence</b> 0 .. <i>unbounded</i>
	<b>Type</b> <i>sharedelements:Dimension</i>
Type	<b>Type</b> <i>xs:string</i>
	<b>Use</b> <i>required</i>
	<b>General Notes</b> <i>DIMENSION TYPE</i>
	<b>Applicable Codes</b>
	<b>Gross</b> <i>Line Item Gross Dimensions</i>
Uom	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> <i>DIMENSIONS UNIT OF MEASURE</i>
	<b>Applicable Codes</b>
	<b>CMT</b> <i>Centimetres</i>
	<b>MTR</b> <i>Metres</i>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Length</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> <i>DIMENSION - LENGTH</i>
<b>Width</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> <i>DIMENSION - WIDTH</i>
<b>Height</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>xs:string</i>
	<b>General Notes</b> <i>DIMENSION - HEIGHT</i>
<b>PackageIds</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> <i>shipmentstatus:PackageIds</i>
	<b>General Notes</b> <i>PACKAGE IDENTIFICATION AND MARKINGS</i>
	<b>Examples</b> <PackageIds> <PackageId> <InstructionCode>PackageMarks</InstructionCode> <Marks> <ShippingMark>Package1</ShippingMark> <ShippingMark>Package2</ShippingMark> <ShippingMark>Package3</ShippingMark> </Marks> </PackageId> <GoodsIdentities Type="SerialNumber"> <GoodsIdentifier>00034306500101392630</GoodsIdentifier> <GoodsIdentifier>00034306500101392647</GoodsIdentifier> <GoodsIdentifier>00034306500101392654</GoodsIdentifier> </GoodsIdentities> <GoodsIdentities Type="SSCC"> <GoodsIdentifier>370716481208016082</GoodsIdentifier> <GoodsIdentifier>370716481208016099</GoodsIdentifier> <GoodsIdentifier>373323991620976376</GoodsIdentifier> </GoodsIdentities> </PackageIds>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>PackageId</b>	<b>Occurrence</b> 0 .. <i>unbounded</i>
	<b>Type</b> <i>sharedelements:PackageId</i>
	<b>General Notes</b> <i>PACKAGE MARKS &amp; NUMBERS</i>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>xs:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>InstructionCode</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> <i>xs:string</i> <b>General Notes</b> PACKAGE MARKS TYPE
	<b>Applicable Codes</b>
	<b>PackageMarks</b> Package Marks and Numbers
<b>GoodsIdentities</b>	<b>Occurrence</b> 0 .. <i>unbounded</i> <b>Type</b> <i>shardelements:GoodsIdentity</i> <b>General Notes</b> PACKAGE BAR CODES
<i>Type</i>	<b>Type</b> <i>xs:string</i> <b>Use</b> required <b>General Notes</b> TYPE OF IDENTIFIER
	<b>Applicable Codes</b>
	<b>SSCC</b> Serial Shipping Container Code
	<b>SerialNumber</b> Serial Number
<i>xs:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>GoodsIdentifier</b>	<b>Occurrence</b> 1 .. <i>unbounded</i> <b>Type</b> <i>xs:string</i> <b>General Notes</b> GOODS IDENTIFIER

Bold = Element, Italic = Attribute, Grey = Group