



Message Implementation Guideline

## **DSV\_BookingConfirmationMessage**

Model: DSV\_STD\_XML\_BOOKINGCONFIRMATION\_V1\_OUT  
Version: 1.0  
Issue date: 20-04-2020  
Author: DSV Panalpina, EDI

3 Structure .....	2
4 Guideline.....	6



**Structure**

Occurrence	Element/Attribute
	<b>DSV_BookingConfirmationMessage</b>
1 .. 1	xs:sequence
1 .. 1	<b>Header</b>
1 .. 1	xs:sequence
1 .. 1	<b>MessageId</b>
1 .. 1	<b>SenderId</b>
1 .. 1	<b>ReceiverId</b>
1 .. 1	<b>DocumentDate</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
1 .. 1	<b>DocumentCode</b>
1 .. 1	<b>Function</b>
1 .. 1	<b>Version</b>
1 .. 1	<b>BookingConfirmation</b>
1 .. 1	xs:sequence
0 .. 1	<b>BookingId</b>
0 .. 1	<b>Dates</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
0 .. 1	<b>FreeTextData</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>FreeText</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>TextLine1</b>
0 .. 1	<b>TextLine2</b>
0 .. 1	<b>TextLine3</b>
0 .. 1	<b>TextLine4</b>
0 .. 1	<b>TextLine5</b>
0 .. 1	<b>ControlTotals</b>
1 .. 1	xs:sequence
0 .. unbounded	<b>ControlTotal</b>
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Quantity</b>
0 .. 1	<b>TermsOfDelivery</b>
1 .. 1	xs:sequence
0 .. 1	<b>Terms</b>
1 .. 1	xs:sequence
0 .. 1	<b>TermCode</b>
0 .. 1	<b>CodeId</b>
0 .. unbounded	<b>Location</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
required 1 .. 1	Type
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
<b>0 .. 1</b>	<b>TransportStages</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>TransportStage</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Stage</b>
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>ModeOfTransport</b>
<b>0 .. 1</b>	<b>Dates</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Date</b>
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	<b>DateTime</b>
<b>0 .. 1</b>	<b>Locations</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Location</b>
required	<i>Type</i>
1 .. 1	xs:sequence
<b>1 .. unbounded</b>	<b>LocationIdentification</b>
1 .. 1	<i>Type</i>
0 .. 1	xs:sequence
0 .. 1	<b>LocationIdentifier</b>
0 .. 1	<b>LocationName</b>
<b>0 .. 1</b>	<b>References</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>ReferenceGroup</b>
1 .. 1	xs:sequence
0 .. 1	<b>Reference</b>
required	<i>Type</i>
optional	<i>Identifier</i>
<b>0 .. 1</b>	<b>Parties</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Party</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>PartyDetails</b>
required	<i>Role</i>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	<b>Id</b>
0 .. 1	<b>Assignor</b>
0 .. 1	<b>PartyName</b>
0 .. 1	<b>AddressLine1</b>
0 .. 1	<b>AddressLine2</b>
0 .. 1	<b>AddressLine3</b>
0 .. 1	<b>CityName</b>
0 .. 1	<b>State</b>
0 .. 1	<b>PostCode</b>
0 .. 1	<b>CountryCode</b>
<b>0 .. unbounded</b> required	<b>Contact</b>
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	<b>Name</b>
0 .. 1	<b>Phone</b>
0 .. 1	<b>Mobile</b>
0 .. 1	<b>Fax</b>
0 .. 1	<b>Email</b>
<b>0 .. 1</b>	<b>GoodsItems</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>GoodsItem</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>Item</b>
1 .. 1	xs:sequence
0 .. 1	<b>ItemNumber</b>
0 .. 1	<b>PackageQty</b>
0 .. 1	<b>PackageType</b>
<b>0 .. 1</b>	<b>Measurements</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>Measurement</b>
	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Measure</b>
<b>0 .. 1</b>	<b>Dimensions</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b> required	<b>Dimension</b>
	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	<b>Length</b>
0 .. 1	<b>Width</b>
0 .. 1	<b>Height</b>
0 .. 1	<b>NumberOfUnits</b>
<b>0 .. 1</b>	<b>Packagelds</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Packageld</b>
1 .. 1	xs:sequence
1 .. 1	<b>InstructionCode</b>
<b>0 .. 1</b>	<b>Marks</b>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. unbounded	ShippingMark
<b>0 .. unbounded</b>	<b>GoodsIdentities</b>
required	Type
1 .. 1	xs:sequence
1 .. unbounded	GoodsIdentifier
<b>0 .. 1</b>	<b>EquipmentUnits</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>EquipmentUnit</b>
1 .. 1	xs:sequence
<b>0 .. 1</b>	<b>EquipmentType</b>
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	ISOCODE
0 .. 1	NumberOfUnits
<b>0 .. 1</b>	<b>SealIds</b>
1 .. 1	xs:sequence
<b>0 .. unbounded</b>	<b>Seal</b>
1 .. 1	xs:sequence
0 .. 1	SealId
0 .. 1	SealParty

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



**Guideline**

Element/Attribute	Annotation
<b>DSV_BookingConfirmationMessage</b>	<p>Type dsv_bookingconfirmationmessage: DSV_BookingConfirmationMessage</p> <p><b>Occurrence</b> 1 .. 1</p>
<p>xs:sequence</p> <p><b>Header</b></p>	<p><b>Occurrence</b> 1 .. 1</p> <p>Type sharedelements:Header</p> <p><b>General Notes</b> MESSAGE HEADER</p> <p><b>Examples</b></p> <pre>&lt;Header&gt;   &lt;MessageId&gt;98235909&lt;/MessageId&gt;   &lt;SenderId&gt;Sender Identification&lt;/SenderId&gt;   &lt;ReceiverId&gt;Receiver Identification&lt;/ReceiverId&gt;   &lt;DocumentDate Type="IssueDate" Format="DateTimeSec" &gt;     &lt;DateTime&gt;20191125161900&lt;/DateTime&gt;   &lt;/DocumentDate&gt;   &lt;DocumentCode&gt;BookingConfirmation&lt;/DocumentCode&gt;   &lt;Function&gt;New&lt;/Function&gt;   &lt;Version&gt;1.0&lt;/Version&gt; &lt;/Header&gt;</pre>
<p>xs:sequence</p> <p><b>MessageId</b></p>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 1 .. 1</p> <p>Type xs:string</p> <p><b>General Notes</b> MESSAGE IDENTIFIER</p>
<b>SenderId</b>	<p><b>Occurrence</b> 1 .. 1</p> <p>Type xs:string</p> <p><b>General Notes</b> SENDER IDENTIFICATION Mutually agreed</p>
<b>ReceiverId</b>	<p><b>Occurrence</b> 1 .. 1</p> <p>Type xs:string</p> <p><b>General Notes</b> RECEIVER IDENTIFICATION Mutually agreed</p>
<b>DocumentDate</b>	<p><b>Occurrence</b> 1 .. 1</p> <p>Type sharedelements:Date</p> <p><b>General Notes</b> DOCUMENT / MESSAGE DATE</p>
<i>Type</i>	<p>Type xs:string</p> <p>Use required</p> <p><b>General Notes</b> DATE TYPE</p>
<i>Format</i>	<p><b>Applicable Codes</b></p> <p><b>IssueDate</b> Document Issued Date</p> <p>Type xs:string</p> <p>Use required</p> <p><b>General Notes</b> DATE FORMAT</p> <p><b>Applicable Codes</b></p> <p><b>Date</b> CCYYMMDD</p> <p><b>DateTime</b> CCYYMMDDHHMM</p> <p><b>DateTimeSec</b> CCYYMMDDHHMMSS</p>
<p>xs:sequence</p> <p><b>DateTime</b></p>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. 1</p> <p>Type xs:string</p> <p><b>General Notes</b> MESSAGE / DOCUMENT DATE</p>
<b>DocumentCode</b>	<p><b>Occurrence</b> 1 .. 1</p> <p>Type xs:string</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>General Notes</b> DOCUMENT CODE</p> <p><b>Applicable Codes</b></p> <p><b>BookingConfir</b> Booking Confirmation Message</p>
<b>Function</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> MESSAGE FUNCTION</p> <p><b>Applicable Codes</b></p> <p><b>Delete</b></p> <p><b>New</b></p> <p><b>Update</b></p>
<b>Version</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> MESSAGE VERSION</p> <p><b>Applicable Codes</b></p> <p><b>1.0</b> Version 1.0</p>
<b>BookingConfirmation</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Type</b> bookingconfirmation:BookingConfirmation</p>
xs:sequence	
<b>BookingId</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> BOOKING IDENTIFIER</p> <p><b>Examples</b></p> <p>&lt;BookingId&gt;BookingNo&lt;/BookingId&gt;</p>
<b>Dates</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> bookingconfirmation:DateList</p> <p><b>General Notes</b> BOOKING DATES</p> <p><b>Examples</b></p> <p>&lt;Dates&gt;</p> <p>&lt;Date Type="OrderReceived" Format="DateTimeSec" &gt;</p> <p>&lt;DateTime&gt;20191105061200&lt;/DateTime&gt;</p> <p>&lt;/Date&gt;</p> <p>&lt;Date Type="Collection" Format="DateTimeSec" &gt;</p> <p>&lt;DateTime&gt;20191112000000&lt;/DateTime&gt;</p> <p>&lt;/Date&gt;</p> <p>&lt;Date Type="DeliveryRequested" Format="DateTimeSec" &gt;</p> <p>&lt;DateTime&gt;20191113000000&lt;/DateTime&gt;</p> <p>&lt;/Date&gt;</p> <p>&lt;/Dates&gt;</p>
xs:sequence	
<b>Date</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. unbounded</p> <p><b>Type</b> sharedelements:Date</p> <p><b>General Notes</b> BOOKING DATE</p>
<b>Type</b>	<p><b>Type</b> xs:string</p> <p><b>Use</b> required</p> <p><b>General Notes</b> DATE TYPE</p> <p><b>Applicable Codes</b></p> <p><b>Collection</b> Collection date/time, earliest</p> <p><b>DeliveryReque</b> Delivery Requested date/time</p> <p><b>EstimatedColl</b> Shipment date/time, promised for</p> <p><b>EstimatedDeli</b> Delivery date/time, estimated</p> <p><b>OrderReceive</b> Order Received date/time</p> <p><b>RequestedColl</b> Shipment date/time, requested</p> <p><b>ScheduledColl</b> Goods collection or pick-up date/time, planned</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b>
	<b>ScheduledDeli</b> Delivery date/time, 1st schedule
<i>Format</i>	Type xs:string Use required <b>General Notes</b> DATE FORMAT
	<b>Applicable Codes</b>
	<b>DateTimeInter</b> YYYYMMDDHHMM-YYYYMMDDHHMM
	<b>DateTimeSec</b> CCYYMMDDHHMMSS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>DateTime</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> DATE/TIME
<b>FreeTextData</b>	<b>Occurrence</b> 0 .. 1 Type bookingconfirmation:FreeTextList <b>General Notes</b> BOOKING CONFIRMATION FREETEXT
	<b>Examples</b>
	<FreeTextData> <FreeText Type="PickupInstructions"> <TextLine1>Pickup Text Line 1</TextLine1> <TextLine2>Pickup Text Line 2</TextLine2> <TextLine3>Pickup Text Line 3</TextLine3> <TextLine4>Pickup Text Line 4</TextLine4> <TextLine5>Pickup Text Line 5</TextLine5> </FreeText> </FreeTextData>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>FreeText</b>	<b>Occurrence</b> 0 .. unbounded Type sharedelements:FreeText
<i>Type</i>	Type xs:string Use required <b>General Notes</b> BOOKING CONFIRMATION FREE TEXT TYPE
	<b>Applicable Codes</b>
	<b>AdditionalDeta</b> Additional Details
	<b>Consignment</b> Consignment Details (Status, RegDate, Remarks, Originater)
	<b>Consignment</b> Consignment Remarks
	<b>DeliveryInstru</b> Delivery Instructions
	<b>DeliveryRemar</b> Delivery Remarks
	<b>GeneralInform</b> General information
	<b>PickupInstruct</b> Pickup Instructions
	<b>SpecialHandli</b> Special Handling
	<b>SpecialInstruc</b> Special Instructions
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TextLine1</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 1
<b>TextLine2</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 2
<b>TextLine3</b>	<b>Occurrence</b> 0 .. 1 Type xs:string <b>General Notes</b> FREE TEXT LINE 3
<b>TextLine4</b>	<b>Occurrence</b> 0 .. 1 Type xs:string

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
	<b>General Notes</b> FREE TEXT LINE 4
<b>TextLine5</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> FREE TEXT LINE 5
<b>ControlTotals</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:ControlTotalList <b>General Notes</b> CONTROL TOTALS  <b>Examples</b> <ControlTotals> <ControlTotal Type="NumberOfPackages" Uom="PCE" > <Quantity>17</Quantity> </ControlTotal> <ControlTotal Type="GrossWeight" Uom="KGM" > <Quantity>5123</Quantity> </ControlTotal> <ControlTotal Type="Volume" Uom="MTQ" > <Quantity>49.685</Quantity> </ControlTotal> </ControlTotals>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ControlTotal</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:ControlTotal <b>General Notes</b> CONTROL TOTAL
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> CONTROL TOTAL TYPE  <b>Applicable Codes</b> <b>GrossWeight</b> Gross Weight <b>LoadingMeter</b> Loading Meters <b>NetWeight</b> Net Weight <b>NumberOfPac</b> Number Of Packages <b>PalletSpaces</b> Pallet Spaces <b>Volume</b> Volume
<i>Uom</i>	<b>Type</b> xs:string <b>General Notes</b> UNIT OF MEASURE  <b>Applicable Codes</b> <b>KGM</b> Kilograms <b>MTQ</b> Cubic meters <b>MTR</b> Linear meters <b>PCE</b> Pieces <b>PKG</b> Packages
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Quantity</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTROL TOTAL QUANTITY
<b>TermsOfDelivery</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:TermsGroup <b>General Notes</b> TERMS OF DELIVERY  <b>Examples</b> <TermsOfDelivery> <Terms> <TermCode>DAP</TermCode> </Terms> <Codeld>IncoTerms</Codeld>

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>Examples</b></p> <pre> &lt;/Terms&gt; &lt;Location Type="NamedPlace" &gt;   &lt;LocationIdentification&gt;     &lt;LocationName&gt;Copenhagen&lt;/LocationName&gt;   &lt;/LocationIdentification&gt; &lt;/Location&gt; &lt;/TermsOfDelivery&gt;                     </pre>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>Terms</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> sharedelements:Terms</p> <p><b>General Notes</b> TERMS</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>TermCode</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> TERM CODE</p>
<b>CodeId</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> CODE IDENTIFIER</p>
<b>Location</b>	<p><b>Occurrence</b> 0 .. unbounded</p> <p><b>Type</b> sharedelements:Location</p> <p><b>General Notes</b> LOCATION</p>
<i>Type</i>	<p><b>Type</b> xs:string</p> <p><b>Use</b> required</p> <p><b>General Notes</b> TYPE OF LOCATION</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>LocationIdentification</b>	<p><b>Occurrence</b> 1 .. unbounded</p> <p><b>Type</b> sharedelements:LocationIdentification</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>LocationIdentifier</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> LOCATION IDENTIFICATION</p>
<b>LocationName</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> LOCATION NAME</p>
<b>References</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> bookingconfirmation:ReferenceGroupList</p> <p><b>General Notes</b> BOOKING REFERENCES</p> <p><b>Examples</b></p> <pre> &lt;References&gt;   &lt;ReferenceGroup&gt;     &lt;Reference Type="ShipperReference" &gt;128359-5&lt;/Reference&gt;   &lt;/ReferenceGroup&gt;   &lt;ReferenceGroup&gt;     &lt;Reference Type="ExternalReference"     &gt;C0354581883&lt;/Reference&gt;   &lt;/ReferenceGroup&gt; &lt;/References&gt;                     </pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> bookingconfirmation:ReferenceGroup <b>General Notes</b> REFERENCE GROUPS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> sharedelements:Reference <b>General Notes</b> BOOKING REFERENCE VALUE
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> REFERENCE TYPE  Predefined Types listed, additional reference types to be agreed
<b>TransportStages</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:TransportStageList <b>General Notes</b> TRANSPORT STAGES
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>TransportStage</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> bookingconfirmation:TransportStage
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Stage</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> sharedelements:Stage <b>Examples</b> <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> </Stage>
<i>Type</i>	<b>Type</b> xs:string <b>Use</b> required <b>Applicable Codes</b> <b>MainCarriage</b> Main Carriage
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ModeOfTransport</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MODE OF TRANSPORT: Air Sea Road <b>Applicable Codes</b> <b>Air</b> Air transportation <b>Rail</b> Rail transportation <b>Road</b> Road transportation <b>Sea</b> Sea transportation
<b>Dates</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:DateList <b>General Notes</b> TRANSPORTATION DATES

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>Examples</b></p> <pre>&lt;Dates&gt;   &lt;Date Type="ScheduledDeparture" Format="Date" &gt;     &lt;DateTime&gt;20191112&lt;/DateTime&gt;   &lt;/Date&gt;   &lt;Date Type="ScheduledArrival" Format="DateTimeSec" &gt;     &lt;DateTime&gt;20191122235959&lt;/DateTime&gt;   &lt;/Date&gt;   &lt;Date Type="ScheduledShipmentDeparture" Format="DateTimeSec" &gt;     &lt;DateTime&gt;20191111000000&lt;/DateTime&gt;   &lt;/Date&gt;   &lt;Date Type="ScheduledShipmentArrival" Format="DateTime" &gt;     &lt;DateTime&gt;201911212230&lt;/DateTime&gt;   &lt;/Date&gt; &lt;/Dates&gt;</pre>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>Date</b>	<p><b>Occurrence</b> 0 .. unbounded  <b>Type</b> sharedelements:Date  <b>General Notes</b> TRANSPORTATION DATE</p>
<i>Type</i>	<p><b>Type</b> xs:string  <b>Use</b> required  <b>General Notes</b> TRANSPORTATION DATE TYPE</p> <p><b>Applicable Codes</b></p> <p><b>EstimatedDeli</b> Delivery date/time, estimated  <b>EstimatedDep</b> Estimated Time of Departure  <b>ScheduledArri</b> Scheduled Arrival  <b>ScheduledDep</b> Scheduled Departure  <b>ScheduledShi</b> Scheduled Shipment Arrival  <b>ScheduledShi</b> Scheduled Shipment Departure</p>
<i>Format</i>	<p><b>Type</b> xs:string  <b>Use</b> required  <b>General Notes</b> TRANSPORTATION DATE FORMAT</p> <p><b>Applicable Codes</b></p> <p><b>Date</b> CCYYMMDD  <b>DateTime</b> CCYYMMDDHHMM  <b>DateTimeInter</b> CCYYMMDDHHMM-CCYYMMDDHHMM  <b>DateTimeSec</b> CCYYMMDDHHMMSS</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>DateTime</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> xs:string  <b>General Notes</b> TRANSPORTATION DATE/TIME</p>
<b>Locations</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> bookingconfirmation:LocationList  <b>General Notes</b> TRANSPORTATION LOCATIONS</p> <p><b>Examples</b></p> <pre>&lt;Locations&gt;   &lt;Location Type="Departure" &gt;     &lt;LocationIdentification Type="UN"&gt;       &lt;LocationIdentifier&gt;DKCPH&lt;/LocationIdentifier&gt;       &lt;LocationName&gt;Copenhagen&lt;/LocationName&gt;     &lt;/LocationIdentification&gt;   &lt;/Location&gt;   &lt;Location Type="Destination" &gt;     &lt;LocationIdentification Type = "UN"&gt;</pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>Examples</b></p> <pre>&lt;LocationIdentifier&gt;GBLON&lt;/LocationIdentifier&gt; &lt;LocationName&gt;London&lt;/LocationName&gt; &lt;/LocationIdentification&gt; &lt;/Location&gt; &lt;Location Type="PlaceOfLoading" &gt; &lt;LocationIdentification Type = "IATA"&gt; &lt;LocationIdentifier&gt;LHR&lt;/LocationIdentifier&gt; &lt;LocationName&gt;Heathrow&lt;/LocationName&gt; &lt;/LocationIdentification&gt; &lt;/Location&gt; &lt;/Locations&gt;</pre>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Location</b>	<b>Occurrence</b> 0 .. unbounded
<i>Type</i>	<b>Type</b> sharedelements:Location
	<b>Type</b> xs:string
	<b>Use</b> required
	<b>General Notes</b> TRANSPORTATION LOCATION TYPE
	<b>Applicable Codes</b>
	<b>Departure</b> Place of Departure
	<b>Destination</b> Destination
	<b>PlaceOfLoadin</b> Place of Loading
	<b>PlaceOfUnloa</b> Place of Unloading
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentification</b>	<b>Occurrence</b> 1 .. unbounded
<i>Type</i>	<b>Type</b> sharedelements:LocationIdentification
	<b>Type</b> xs:string
	<b>General Notes</b> LOCATION IDENTIFIER TYPE
	<b>Applicable Codes</b>
	<b>IATA</b> IATA airport code
	<b>UN</b> UN Location code
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>LocationIdentifier</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> xs:string
	<b>General Notes</b> LOCATION IDENTIFIER
<b>LocationName</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> xs:string
	<b>General Notes</b> LOCATION NAME
<b>References</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> bookingconfirmation:ReferenceGroupList
	<b>General Notes</b> TRANSPORTATION STAGE REFERENCES
	<b>Examples</b>
	<pre>&lt;References&gt; &lt;ReferenceGroup&gt; &lt;Reference Type="MasterBill"&gt;Master1&lt;/Reference&gt; &lt;/ReferenceGroup&gt; &lt;/References&gt;</pre>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ReferenceGroup</b>	<b>Occurrence</b> 0 .. unbounded
	<b>Type</b> bookingconfirmation:ReferenceGroup
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Reference</b>	<b>Occurrence</b> 0 .. 1
	<b>Type</b> sharedelements:Reference

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>General Notes</b> TRANSPORTATION STAGE REFERENCE</p>
<i>Type</i>	<p><b>Type</b> xs:string  <b>Use</b> required  <b>General Notes</b> TRANSPORTATION STAGE REFERENCE TYPE</p>
	<p><b>Applicable Codes</b></p> <p><b>CargoManifest</b> Cargo manifest number, Transport Id  <b>DeliveryAgree</b> Delivery Agreement  <b>HouseBill</b> House bill of lading number  <b>MasterBill</b> Master bill of lading number  <b>VehicleId</b> Vehicle identification number ( VIN)</p>
<i>Identifier</i>	<p><b>Type</b> xs:string  <b>Use</b> optional  <b>General Notes</b> TRANSPORTATION STAGE REFERENCE IDENTIFIER</p>
<b>Parties</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> bookingconfirmation:PartiesList  <b>General Notes</b> SHIPMENT PARTY INFORMATION</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>Party</b>	<p><b>Occurrence</b> 0 .. unbounded  <b>Type</b> bookingconfirmation:PartyList</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>PartyDetails</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> sharedelements:PartyDetails  <b>General Notes</b> PARTY DETAILS</p> <p><b>Examples</b></p> <pre>&lt;PartyDetails Role="Consignor"&gt;   &lt;Id&gt;ConsignorID&lt;/Id&gt;   &lt;Assignor&gt;Consignor&lt;/Assignor&gt;   &lt;PartyName&gt;Consignor Name&lt;/PartyName&gt;   &lt;AddressLine1&gt;Consignor Addr Line 1&lt;/AddressLine1&gt;   &lt;AddressLine2&gt;Consignor Addr Line 2&lt;/AddressLine2&gt;   &lt;AddressLine3&gt;Consignor Addr Line 3&lt;/AddressLine3&gt;   &lt;CityName&gt;Consignor City&lt;/CityName&gt;   &lt;State&gt;Consignor State&lt;/State&gt;   &lt;PostCode&gt;PostCd&lt;/PostCode&gt;   &lt;CountryCode&gt;DK&lt;/CountryCode&gt; &lt;/PartyDetails&gt;</pre>
<i>Role</i>	<p><b>Type</b> xs:string  <b>Use</b> required  <b>General Notes</b> PARTY ROLE</p> <p><b>Applicable Codes</b></p> <p><b>Agent</b> Agent  <b>Carrier</b> Carrier Party  <b>Consignee</b> Consignee Party  <b>Consignor</b> Consignor Party  <b>FreightForwarder</b> Freight Forwarder</p>
xs:sequence	<p><b>Occurrence</b> 1 .. 1</p>
<b>Id</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> xs:string  <b>General Notes</b> PARTY IDENTIFIER</p>
<b>Assignor</b>	<p><b>Occurrence</b> 0 .. 1  <b>Type</b> xs:string  <b>General Notes</b> PARTY ASSIGNOR</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>Applicable Codes</b> <b>Consignor</b> Consignor assigned <b>DSV</b> DSV assigned <b>GS1</b> GS1 assigned
PartyName	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY NAME
AddressLine1	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY ADDRESS LINE1
AddressLine2	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY ADDRESS LINE2
AddressLine3	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY ADDRESS LINE3
CityName	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY CITY NAME
State	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY STATE
PostCode	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY POSTCODE
CountryCode	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> PARTY COUNTRY CODE
Contact	<b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:Contact <b>General Notes</b> PARTY CONTACT DETAILS  <b>Examples</b> <Contact Type="InformationContact"> <Name>Contact name</Name> <Phone>Contact Phone</Phone> <Mobile>Contact Mobile</Mobile> <Fax>Contact Fax</Fax> <Email>Contact Email</Email> </Contact>
Type	<b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> CONTACT TYPE
xs:sequence	<b>Applicable Codes</b> <b>InformationCo</b> Party Information Contact <b>Occurrence</b> 1 .. 1
Name	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONATCT NAME
Phone	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>General Notes</b> CONTACT PHONE
<b>Mobile</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTACT MOBILE
<b>Fax</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTACT FAX
<b>Email</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTACT EMAIL
<b>GoodsItems</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:GoodsItemList <b>General Notes</b> SHIPMENT LINE ITEMS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>GoodsItem</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> bookingconfirmation:GoodsItem
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Item</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> sharedelements:Item <b>General Notes</b> SHIPMENT LINE ITEM  <b>Examples</b> <Item> <ItemNumber>1</ItemNumber> <PackageQty>1</PackageQty> <PackageType>CLL</PackageType> </Item>
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>ItemNumber</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPMENT ITEM NUMBER
<b>PackageQty</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPMENT PACKAGE QUANTITY
<b>PackageType</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SHIPMENT PACKAGE TYPE
<b>Measurements</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:MeasurementsList  <b>Examples</b> <Measurements> <Measurement Type="GrossWeight" Uom="KGM" > <Measure>1</Measure> </Measurement> <Measurement Type="NetWeight" Uom="KGM" > <Measure>1</Measure> </Measurement> <Measurement Type="LoadingMeters" Uom="MTR" > <Measure>13.5</Measure> </Measurement> <Measurement Type="PalletSpaces" Uom="CLL" > <Measure>1</Measure> </Measurement>

Bold = Element, Italic = Attribute, Grey = Group





Element/Attribute	Annotation
	<p><b>Examples</b> &lt;/Measurements&gt;</p>
<p>xs:sequence <b>Measurement</b></p>	<p><b>Occurrence</b> 1 .. 1</p>
<p><i>Type</i></p>	<p><b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:Measurement <b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> MEASUREMENT TYPE</p>
	<p><b>Applicable Codes</b></p> <p><b>GrossWeight</b> Line Item Gross Weight <b>LoadingMeter</b> Line Item Loading Meters <b>NetWeight</b> Line Item Net Weight <b>PalletSpaces</b> Line Item Pallet Spaces <b>Volume</b> Line Item Volume</p>
<p><i>Uom</i></p>	<p><b>Type</b> xs:string <b>General Notes</b> MEASUREMENT UNIT OF MEASURE</p>
	<p><b>Applicable Codes</b></p> <p><b>KGM</b> Kilograms <b>MTQ</b> Cubic Meters <b>MTR</b> Linear Meters <b>PLL</b> Pallets</p>
<p>xs:sequence <b>Measure</b></p>	<p><b>Occurrence</b> 1 .. 1 <b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> MEASUREMENT VALUE</p>
<p><b>Dimensions</b></p>	<p><b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:DimensionsList <b>General Notes</b> LINE ITEM DIMENSIONS</p>
	<p><b>Examples</b> &lt;Dimensions&gt;                      &lt;Dimension Type="Gross" Uom="CMT" &gt;                      &lt;Length&gt;90&lt;/Length&gt;                      &lt;Width&gt;90&lt;/Width&gt;                      &lt;Height&gt;255&lt;/Height&gt;                      &lt;NumberOfUnits&gt;1&lt;/NumberOfUnits&gt;                      &lt;/Dimension&gt;</p>
<p>xs:sequence <b>Dimension</b></p>	<p><b>Occurrence</b> 1 .. 1 <b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:Dimension</p>
<p><i>Type</i></p>	<p><b>Type</b> xs:string <b>Use</b> required <b>General Notes</b> DIMENSION TYPE</p>
	<p><b>Applicable Codes</b></p> <p><b>Gross</b> Line Item Gross Dimensions</p>
<p><i>Uom</i></p>	<p><b>Type</b> xs:string <b>General Notes</b> DIMENSIONS UNIT OF MEASURE</p>
	<p><b>Applicable Codes</b></p> <p><b>CMT</b> Centimeters <b>MTR</b> Meters</p>
<p>xs:sequence <b>Length</b></p>	<p><b>Occurrence</b> 1 .. 1 <b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<b>General Notes</b> DIMENSION LENGTH
Width	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION WIDTH
Height	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION HEIGHT
NumberOfUnits	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> DIMENSION NUMBER OF UNITS
PackageIds	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:PackageIds <b>General Notes</b> PACKAGE IDENTIFICATION AND MARKINGS  <b>Examples</b> <PackageIds> <PackageId> <InstructionCode>PackageMarks</InstructionCode> <Marks> <ShippingMark>PCI24-1</ShippingMark> <ShippingMark>PCI24-2</ShippingMark> </Marks> </PackageId> <GoodsIdentities Type="SSCC" > <GoodsIdentifier>373323995919004597</GoodsIdentifier> <GoodsIdentifier>373323995919004603</GoodsIdentifier> <GoodsIdentifier>373323995919004610</GoodsIdentifier> <GoodsIdentifier>373323995919004627</GoodsIdentifier> <GoodsIdentifier>373323995919004634</GoodsIdentifier> <GoodsIdentifier>373323995919004641</GoodsIdentifier> </GoodsIdentities> </PackageIds>
xs:sequence	<b>Occurrence</b> 1 .. 1
PackageId	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shardelements:PackageId <b>General Notes</b> PACKAGE MARKS & NUMBERS
xs:sequence	<b>Occurrence</b> 1 .. 1
InstructionCode	<b>Occurrence</b> 1 .. 1 <b>Type</b> xs:string <b>General Notes</b> PACKAGE MARKS TYPE  <b>Applicable Codes</b> <b>PackageMarks</b> Package Marks and Numbers
Marks	<b>Occurrence</b> 0 .. 1 <b>Type</b> shardelements:Marks
xs:sequence	<b>Occurrence</b> 1 .. 1
ShippingMark	<b>Occurrence</b> 1 .. unbounded <b>Type</b> xs:string <b>General Notes</b> PACKAGE MARK
GoodsIdentities	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shardelements:GoodsIdentity <b>General Notes</b> PACKAGE BAR CODES
Type	<b>Type</b> xs:string <b>Use</b> required

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p><b>General Notes</b> BARCODE TYPE</p> <p><b>Applicable Codes</b></p> <p><b>SSCC</b> Serial Shipping Container Code</p> <p><b>SerialNumber</b> Package/Pallet Serial Number</p>
xs:sequence	
<b>GoodsIdentifier</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 1 .. unbounded</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> GOODS IDENTIFIER</p> <p>SSCC codes should not include the leading "00" qualifier, length of value should be 18 characters</p>
<b>EquipmentUnits</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> bookingconfirmation:EquipmentUnitsList</p> <p><b>General Notes</b> EQUIPMENT INFORMATION</p>
xs:sequence	
<b>EquipmentUnit</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. unbounded</p> <p><b>Type</b> bookingconfirmation:EquipmentUnit</p> <p><b>General Notes</b> EQUIPMENT UNIT DETAILS</p> <p><b>Examples</b></p> <pre>&lt;EquipmentUnits&gt;   &lt;EquipmentUnit&gt;     &lt;EquipmentType&gt;       &lt;Type&gt;Container&lt;/Type&gt;       &lt;UnitId&gt;TCLU1234567&lt;/UnitId&gt;       &lt;SizeTypeCode&gt;20GP&lt;/SizeTypeCode&gt;       &lt;ISOCCode&gt;22G0&lt;/ISOCCode&gt;     &lt;/EquipmentType&gt;     &lt;SealIds&gt;       &lt;Seal&gt;         &lt;SealId&gt;SealNo&lt;/SealId&gt;         &lt;SealParty&gt;Shipper&lt;/SealParty&gt;       &lt;/Seal&gt;     &lt;/SealIds&gt;   &lt;/EquipmentUnit&gt; &lt;/EquipmentUnits&gt;</pre>
xs:sequence	
<b>EquipmentType</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> sharedelements:EquipmentType</p> <p><b>General Notes</b> EQUIPMENT TYPE INFORMATION</p>
xs:sequence	
<b>Type</b>	<p><b>Occurrence</b> 1 .. 1</p> <p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> EQUIPMENT TYPE</p> <p><b>Applicable Codes</b></p> <p><b>Container</b> Shipping Container</p> <p><b>EFP</b> Euro Flat Pallet</p> <p><b>EUR</b> Euro Pallet</p>
<b>UnitId</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> SHIPPING CONTAINER NUMBER</p>
<b>SizeTypeCode</b>	<p><b>Occurrence</b> 0 .. 1</p> <p><b>Type</b> xs:string</p> <p><b>General Notes</b> CONTAINER SIZE AND TYPE</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	DSV specified Container Type for Shipping Container
	<b>Applicable Codes</b>
	<b>20GP</b> 20 ft General Purpose
	<b>20RE</b> 20 ft Reefer
	<b>40GP</b> 40 ft General Purpose
	<b>40HC</b> 40 ft High Cube
	<b>40NOR</b> 40 ft high Cube, self powered Reefer
	<b>40RE</b> 40 ft Reefer
	<b>40REHC</b> 40 ft High Cube Reefer
<b>ISOCode</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> CONTAINER ISO SIZE AND TYPE
	<b>Applicable Codes</b>
	<b>22G1</b> 20 ft General Purpose
	<b>22R1</b> 20 ft Reefer
	<b>42G1</b> 40 ft General Purpose
	<b>42R1</b> 40 ft Reefer
	<b>45G1</b> 40 ft High cube
	<b>45R1</b> 40 ft High cube Reefer
	<b>45R9</b> 40 ft High cube, self powered Reefer
<b>NumberOfUnits</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:decimal <b>General Notes</b> NUMBER OF UNITS
<b>SealIds</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> bookingconfirmation:SealList <b>General Notes</b> SEAL IDS
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>Seal</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> sharedelements:Seal
xs:sequence	<b>Occurrence</b> 1 .. 1
<b>SealId</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SEAL NUMBER
<b>SealParty</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xs:string <b>General Notes</b> SEALING PARTY
	<b>Applicable Codes</b>
	<b>Shipper</b> Shipper Sealing Party

Bold = Element, Italic = Attribute, Grey = Group